HEIMETS

Helmets BLACKSTONE

Auto-Darkening Welding Helmet

- Variable shades 9-13 (dark state), shade 4 (light state) · Contains sensitivity and
- delay time adjustment • Two sensors
- Solar powered no change of battery needed. Under normal welding conditions users can expect a battery life of
- more than five years · Fast, reliable switching speed, from light to dark in
- 1/25,000 seconds
- Constant UV/IR protection
- 1-3/4" x 3-3/4" viewing area
- · Automatic power on/off One year warranty
- Meets EN, DIN, ISO and ANSI Z87.1 standards

| Part No. | Description | Price /Each |
|----------|-----------------------|----------------|
| 0800101 | SH9-13ADF Weld Helmet | \$109.99 |

Helmet Accessories

| Part No. | Description | Price /Each |
|----------|------------------------|----------------|
| 0800701 | Outer Cover Lens - 5pk | \$1.65 |
| 0800704 | Inner Cover Lens - 5pk | 0.70 |
| 0800703 | Replacement Headgear | 9.99 |
| | | |

4.5 x 5.25 Fixed Shade Welding Helmet

- · Fixed shade #10 lens for
- arc welding
- Durable plastic shell
- · Adjustable ratchet headgear

| Part No. | Description | Price /Each |
|----------|---|----------------|
| 0801955 | 4-1/2" x 5-1/4" Fixed Shade, Standard Welding Helmet | \$24.99 |

Helmet Accessories

| | | Price |
|----------|--|--------|
| Part No. | Description | /Each |
| 0801956 | 4-1/2" x 5-1/4" Clear Outer Cover Lens | \$2.79 |
| 0801957 | 4-1/2" x 5-1/4" Clear Inner Cover Lens | 7.14 |
| 0801958 | 4-1/2" x 5-1/4" Shade 10 Lens | 3.18 |
| | | |

2 x 4 Flip Up Fixed Shade Welding Helmet

- Fixed shade #10 lens for arc welding
- Durable plastic shell · Adjustable ratchet headgear

| | | Price |
|----------|--------------------------------|---------|
| Part No. | Description | /Each |
| 0801951 | 2" x 4" Viewing Area, Flip | \$24.99 |
| | Up, Fixed Shade Welding Helmet | |

Helmet Accessories

| Part No. | Description | Price /Each |
|----------|--------------------------|----------------|
| 0801952 | 2" x 4" Outer Cover Lens | \$1.26 |
| 0801953 | 2" x 4" Inner Cover Lens | 2.46 |
| 0801954 | 2" x 4" Shade 10 Lens | 1.59 |

Bacou-Dalloz HARLEY-DAVIDSON

Harley-Davidson Welding Helmets

H-D[®] Premium Style Series - Flames

| Combining the most advanced ADF technology with cutting edge design, the H-D Flames welding helmet provides style with unrivaled performance. Variable shades 9-13 provide a wide range of shade options, while external shade selection knob allows for easy access shade selection. | |
|---|------|
| | Pric |

| Part No. | Description | /Each |
|----------|----------------|----------|
| 0850805 | HD 9-13 Flames | \$644.48 |

H-D® Premium Style Series - Racing



| | | Price |
|----------|----------------|----------|
| Part No. | Description | /Each |
| 0850806 | HD 9-13 Racing | \$644.48 |
| | | |

H-D[®] Signature Series - Shade 10 ADF

With ADF technology and classic Harley-Davidson® Bar and Shield graphics, this model offers style and advanced performance. Work in daylight until the arc is struck.

| Part No. | Description | Price /Each |
|----------|-----------------|----------------|
| 0850804 | HD Shade 10 ADF | \$358.28 |

H-D[®] Signature Series - Flip-Up

With classic Harley-Davidson® Bar and Shield Graphics, this model features a Shade 10 passive 2" x 4-1/4 flip-up filter that eliminates the need to raise and lower helmet.

| | | Price |
|----------|--------------------|---------|
| Part No. | Description | /Each |
| 0850802 | HD 2" x 4" Flip-Up | \$80.78 |

H-D[®] Signature Series - Wide-View

Classic Harley-Davidson® Bar and Shield graphics and a large viewing area make this model stylish and practical. The 4" x 5-1/2" wide view Shade 10 passive filter provides an expansive view of the work area.

| Part No. | Description | Price /Each |
|----------|----------------------|----------------|
| 0850803 | HD 4" x 5" Wide-view | \$80.78 |
| | | |

optrel

Optrel® Satellite Auto Darkening Welding Helmets

Optrel Satellite Helmets

In addition to Optrel's Auto Darkening Filter (ADF) technology, the Satellite features easily accessible external controls to give you complete command of shade range, shade level, sensitivity control and delay switching without removing your helmet. Injection-molded cover lens



reduces reflection and protects ADF cartridge from humidity, moisture and dust. Ideal for all your welding needs, including electrode welding, MIG steel, MAG and TIG micro plasma arc welding, gas metal arc welding, grinding and more. 2-year limited warranty.

- Shade Range 4/5-9 and 4/9-13 with manual shade selection knob
- · Automatically darkens within .04 millisecond
- · Solar energy ensures a continuous power supply, eliminating the need for on/off switches and battery changes
- One-touch button locks filter into shade 4 for grinding • Sensitivity and Delay are fully adjustable to match
- the users requirements

| | | Price |
|----------|-------|----------|
| Part No. | Color | /Each |
| 0850800 | Blue | \$446.86 |
| 0850801 | Black | 446.86 |



HSL 100 Helmet with NexGen

- · Narrow shell design is perfect for work in tight spaces and weighs only 13.8 ounces
- Extended front increases throat protection against sparks, slag and fumes
- 3N1 technology allows three modes of operation: Weld(shades 9-13), Grind(3) or Torch(5)
- Soft touch panel eliminates contaminates and protects from outside environment
- Standard size outer cover plate, 9 square inches of viewing area and four sensors

| | | Price |
|----------|-------------|----------|
| Part No. | Description | /Each |
| 0801839 | HSL 100 | \$412.00 |

HellRaiser Helmet with NexGen

- · Narrow shell design is perfect for work in tight spaces and weighs only 13.8 ounces
- · Extended front increases throat protection against sparks, slag and fumes
- 3N1 Technology allows three modes of operation: Weld
- (shades 9-13), Grind(3) or Torch(5) Soft touch panel eliminates contami
- nates and protects from outside environment
- Standard size outer cover plate, 9 square inches of viewing area and four sensors

| Part No. | Description | Price /Each |
|----------|----------------------|----------------|
| 0801841 | HellRaiser w/ NexGen | \$430.40 |

Welding Helmets & **Eye Protection**

HELMETS & HELMET KITS



- Variable shade 9-13
- · Sensitivity and delay sensors
- Auto-Off feature
- · Low voltage indicator lamp •Uses 2 "AAA" batteries

| 0000 2 70 | or ballonoo | |
|-----------|---------------|----------|
| | | Price |
| Part No. | Description | /Each |
| 0801835 | Flames Halo X | \$220.80 |

· Heat-resistant vulcanized fiber shelf for comfortable, cool, heavyduty welding

Part N

08018

| No. | Description | |
|-----|-------------|--|
| 345 | 451P | |





- Clear Nemesis VL spectacle
- 2 Inner safety plates
- 5 Outer safety plates

Part No.

0801842

Price

/Each

\$30.98





11-2 Welding

Internation Religious Figure 1 (1997) (197) (197

20

- · Narrow shell design is perfect for work in tight spaces and weighs
- only 13.8 ounces · Extended front increases throat
- and fumes • 1-3/4" x 3-3/4" viewing area

- Auto-Off feature

Low voltage indicator lamp

• Uses 2 "AAA" batteries

HELMET ACCESSORIES & WELDING HELMET LENSES



BLACKSTONE

Weld Helmet Bib

Attaches to inside bottom of any welding helmet with Hook and Loop adhesive strips. Provides protection to lower neck area from welding arc and spatter. 1 per package.



Part No 0800272 \$3.98

Lenses for Welding Helmets

BLACKSTONF

Welding Lens **Recommendation Chart**

| | Arc | Min. | Sug. |
|------------------|--------------------|-------|--------|
| Operation | Current | Shade | Shade |
| Stick Welding | 60 amp or Less | 7 | |
| | 60-160 | 8 | 10 |
| | 160-250 | 10 | 12 |
| | 250-550 | 11 | 14 |
| Mig and Flux | 60 amp or Less | 7 | |
| Cored Welding | 60-160 | 10 | 11 |
| | 160-250 | 10 | 12 |
| | 250-550 | 10 | 14 |
| Tig Welding | 150 amp or Less | 8 | 10 |
| | 150-500 | 8 | 12 |
| Air Carbon | 500. amp or Less | 10 | 12 |
| Arc Cutting | 500-1000 | 11 | 14 |
| Plasma Arc Cutti | ng 300 amp or Less | 8 | 9 |
| | 300-400 | 9 | 12 |
| | 400-800 | 10 | 14 |
| Gas Welding | Light | | 4 or 5 |
| | Medium | | 5 or 6 |
| | Heavy | | 6 or 8 |
| oxygen cutting | Light | | 3 or 4 |
| | Medium | | 4 or 5 |
| | Heavy | | 5 or 6 |
| Torch Brazing | | | 3 or 4 |
| Torch Soldering | | | 2 |

Refer to ANSI/ASC Z49.1-88 Standard for additional information.

Standard can be obtained by writing to:

American Welding Society, 550 N.W. LeJuene Road, Miami, Florida 33135 ANSI - American National Standards Institute

These charts are not intended to be the user's sole reference in the selection of eye and face protectors. Warning: All welding helmets and faceshields must be worn with spectacles and/or goggles.

Clear Cover Lenses

| 2 x 4.2 | 5 | |
|----------|--|----------------|
| Part No. | Description | Price /Each |
| 0800500 | Clear Polycarbonate Cover/Safety Lens | \$0.70 |
| 0800503 | Clear CR-39 Cover Lens - Scratch Resistant | 0.91 |
| 4.5 x 5 | 5.25 | |
| | | Price |
| Part No. | Description | /Each |
| 0800540 | Clear Polycarbonate Cover/Safety Lens | \$1.56 |
| 0800543 | Clear CR-39 Cover Lens-Scratch Resistant | 2.06 |

Shaded Lenses

(Lenses for welding helmets & goggles) 2" x 4-1/4" Size

| | 1.0 | |
|-----------------|----------------|--------|
| | | Price |
| Part No. | Shade | /Each |
| Hardened Glass | | |
| 0800505 | 4 | \$2.42 |
| 0800506 | 5 | 2.42 |
| 0800507 | 6 | 2.42 |
| 0800509 | 8 | 2.42 |
| 0800510 | 9 | 2.42 |
| 0800511 | 10 | 2.42 |
| 0800512 | 11 | 2.42 |
| 0800513 | 12 | 2.42 |
| Polycarbonate | | |
| 0800534 | 4 | \$2.42 |
| 0800535 | 5 | 2.42 |
| 0800536 | 6 | 2.42 |
| 0800537 | 9 | 2.42 |
| 0800538 | 10 | 2.42 |
| 0800539 | 11 | 2.42 |
| 0800514 | 12 | 2.42 |
| Polycarbonate G | old Reflective | |
| 0800530 | 9 | \$8.84 |
| 0800531 | 10 | 8.84 |
| 0800532 | 11 | 8.84 |
| 0800533 | 12 | 8.84 |

4-1/2" x 5-1/4" Size

| Part No. | Shade | Price /Each |
|-----------------|----------------|----------------|
| Hardened Glass | Shaue | /Lacii |
| 0800550 | 8 | \$5.36 |
| 0800551 | 9 | 5.36 |
| 0800552 | 10 | 5.36 |
| 0800553 | 11 | 5.36 |
| 0800554 | 12 | 5.36 |
| Polycarbonate | | |
| 0800555 | 9 | \$6.28 |
| 0800556 | 10 | 6.28 |
| 0800557 | 11 | 6.28 |
| 0800558 | 12 | 6.28 |
| 0800514 | 12 | 2.42 |
| Polycarbonate G | old Reflective | |
| 0800580 | 9 | \$14.73 |
| 0800581 | 10 | 14.73 |
| 0800582 | 11 | 14.73 |
| 0800583 | 12 | 14.73 |

Headgear Sweat Band

Comfortable and absorbent band. Soft horsehide leather. Surgical sponge inside for com-0 fort. Snaps on helmet and faceshield headgears. Four rustproof snaps.

Price Part No. /Each 0800271 \$4.67 Sponge Sweat Band

Cellulose sponge with elastic band. Prevents sweat from soaking eyes and streaking glasses. Soaking band in water before use cools head by evaporation. Packed 25 in a box.

| Part No. | Price /Each |
|----------|----------------|
| 0800270 | \$0.82 |
| | |

Magnifying Lenses

2" x 4-1/4" Size

| Part No. | Diopter | Price /Each |
|----------|---------|----------------|
| 0800590 | .75 | \$8.10 |
| 0800591 | 1.00 | 8.10 |
| 0800592 | 1.25 | 8.10 |
| 0800593 | 1.50 | 8.10 |
| 0800594 | 1.75 | 8.10 |
| 0800595 | 2.00 | 8.10 |
| 0800596 | 2.25 | 8.10 |
| 0800597 | 2.50 | 8.10 |
| | | |

EQC Master Variable

• 1-3/4" x 3-3/4" viewing area

- Variable shade 9-12
- · Sensitivity and delay adjustments
- Two independent redundant sensors
- Auto-Off feature
- · Solar battery life extender
- HTLS clear state
- · Low voltage indicator lamp
- Uses 2 "AAA" batteries

| Part No. | /Each |
|----------|----------|
| 0801840 | \$385.63 |
| | |

Turbo Auto-Darkening Lens

- Variable shade 9-12
- Two sensors
- · Sensitivity and delay adjustments
- Two independent redundant sensors
- Auto-Off feature · Solar battery life extender HTLS clear state
- Low voltage indicator lamp Uses 2 "AAA" batteries

| Part No. | Price /Each |
|----------|----------------|
| 0801838 | \$184.00 |

Solera

1

- 2" x 4 1/4" Solar-powered Auto
- Darkening Lens Shade 10/11
- Two sensors
- Clear state 3.0

| | Price |
|----------|---------|
| Part No. | /Each |
| 0801830 | \$89.60 |
| | |

Price

Welding Helmets & Eye Protection

LENSES, FACE SHIELDS, GOGGLES, GLASSES & GLOVES

/Each

Price

/Each

\$10.41

/Ea

\$32.80

59.20





Welding Helmets Eye Protection Helmets

20

Solar powered

· Solar powered

Vendo

No

32010

32030

32050

32181

32182

Part No.

0800424

0800425

0800426

0800427

0800428

shades.

Part No.

0800650

0800654

0800656

0800651

0800653

0800652

0800657

0800658

Single crown

0800407 32152

Part No.


0801028

Part No.

0801029

11-4 Welding

Gloves, Accessories, Jackets & Capes





Leather Cape and Bibs

- Arms and upper body protection
- Back and lower torso is open for comfort
- Brown cape sleeve with reinforced snaps
 One soapstone pocket on each sleeve
- One soapstone pocket on each sleeve
 Bib not included unless noted
- Sewn with Kevlar Thread

| Devi Ma | Description | Price |
|----------|------------------------|---------|
| Part No. | Description | /Each |
| 0800071 | Medium | \$44.15 |
| 0800072 | Large | 44.15 |
| 0800073 | X-Large | 44.15 |
| 0800057 | 2X-Large | 52.04 |
| 0800058 | 3X-Large | 52.98 |
| 0800059 | 4X-Large | 57.41 |
| 0800079 | Detachable Bib - 20" | 14.15 |
| 0800076 | Large Cape w/19" Bib | 55.95 |
| 0800077 | X-Large Cape w/19" Bib | 55.95 |

Leather Jackets

- 26" & 30" brown jacket
- One soapstone pocket on each sleeve
- Outside pocket
- Additional underarm seam
 Reinforced snaps at collar, wrists, and in back
- Has air vents under arms and at upper back for wearer comfort
- Satin lining for easy on and off

| 26 | " | 30 | | |
|----------|----------------|----------|----------------|-------------|
| Part No. | Price /Each | Part No. | Price /Each | Description |
| 0800111 | \$68.95 | 0800091 | \$80.19 | Medium |
| 0800112 | 68.95 | 0800092 | 80.19 | Large |
| 0800113 | 68.95 | 0800093 | 80.19 | Extra Large |
| | | 0800189 | 88.54 | 2X-Large |
| | | 0800192 | 90.37 | 3X-Large |
| | | 0800193 | 100.22 | 4X-Large |

Sateen Capes

- 9-1/2 oz. green firestop cape and sleeve with snap fasteners
 Bib pet included
- Bib not included
 Permanently flame retardant



| Part No. | Description | Price /Each |
|----------|--------------------|----------------|
| 0800141 | Medium | \$17.56 |
| 0800142 | Large | 17.56 |
| 0800143 | X-Large | 17.56 |
| 0800145 | 2X-Large | 18.73 |
| 0800144 | Bib for Cape - 20" | 7.18 |

Sateen Jackets

- LightweightInside pockets
- 30" 9-1/2 oz. green firestop jacket
- Snap front
- Permanently flame retardant



| | | Price |
|----------|-------------|---------|
| Part No. | Description | /Each |
| 0800171 | Medium | \$27.54 |
| 0800172 | Large | 27.54 |
| 0800173 | X-Large | 27.54 |
| 0800176 | 2X-Large | 30.47 |
| 0800188 | 3X-Large | 32.92 |
| | | |

/Each

\$5.66

Description

Reflective Protector

Part No

0800020

JACKETS & CAPES, SLEEVES, SCREENS & CURTAINS, BLANKETS

Jackets and Capes Cont.



Safety Clothing

Lightweight

- Inside pockets
- 30" 9-1/2 oz. blue firestop jacket
- Snap front · Permanently flame retardant

Part No. Description 0800174 2X-Large \$32.09 0800175 3X-Large

Welders Cotton Jacket With mesh back for extremely hot conditions

The flame retardant Cotton Welding Jacket just got cooler! Now available with a full back panel of nylon cane mesh fabric making it even lighter and cooler than a regular cotton welding jacket. The mesh back is

designed to help keep the wearer cool in extremely hot conditions.

- · Flame retardant cotton apparel recommended for protection from light exposure to sparks and spatter in warm weather or indoor applications
- · Lightweight, breathable mesh back made from 100% white cane nylon (non-flame retardant)
- 9 1/2 oz. light green cotton front, sleeves and collar
- · 30" jacket has snap front, collar and wrist

| | | Price |
|----------|----------|---------|
| Part No. | Size | /Each |
| 0800194 | Small | \$51.62 |
| 0800195 | Medium | 51.62 |
| 0800196 | Large | 51.62 |
| 0800197 | X-Large | 51.62 |
| 0800198 | 2X-Large | 55.98 |

Sleeves

Welding Sleeves 1 pair per package



| Part No. | Description | /Pair |
|----------|---------------------------------------|---------|
| 0800190 | Leather18" Long | \$21.67 |
| 0800191 | Leather with Straps 23" Long | 28.42 |
| 0800200 | Sateen with Straps 23" Long | 12.78 |
| 0800201 | Sateen with Wide Elastic on Both Ends | 7.90 |
| 0800204 | Sateen Sleeves with std. Elastic | 6.70 |

Screens & Curtains Welding Curtains

These economical multipurpose curtains come hemmed and grommeted and ready to hang on



tubing or framing you supply. Applications include protection for welding areas, cutting or brazing; isolating workers or equipment; and spray protection. Hemmed for extra strength and longer service life. These curtains are transparent, but block most UV radiation and reduce the visible flash from the welding arc. Grommets every 12". 14 mil vinyl film. Other sizes available. Fabric is not intended for use in lieu of visors, goggles or view port windows for welding operations

| Part No. | Description | Price /Each |
|----------|-----------------|----------------|
| 0800240 | 6' x 6', Orange | \$47.68 |
| 0800259 | 6' x 8' Orange | 52.84 |
| 0800241 | 6' x 6', Yellow | 47.68 |
| 0800250 | 6' x 8' Yellow | 52.84 |
| 0800258 | 6' x 6' Green | 47.68 |
| 0800251 | 6' x 8' Green | 52.84 |

Welding Curtain Rolls

Ideal for instant curtains for maintenance projects. Simply roll out the length of curtain needed and cut it off the roll with scissors. Curtain rolls are widely used in robotic welding areas where

Price

/Each

38.47

large curtains are needed to enclose the perimeter of the welding area.

- · Provides instant access to economical protection simply cut off the amount of curtain you need and hang it
- The 14 mil transparent vinyl material allows visibility through the curtain, but blocks most harmful UV rays
- The 60" wide by 25 yard long rolls have grommets every 12" on one side

| Part No. | Vendor No. | Color | Price /Each |
|----------|---------------|--------|----------------|
| 0800211 | 63225 | Gray | \$239.95 |
| 0800213 | 63425 | Yellow | 239.95 |
| 0800214 | 63825 | Orange | 239.95 |

Welding Screens - With Frame

Protects people adjacent to welding areas from the hazards of welding sparks, spatter and UV flash

Sturdy 18 gauge steel, square tube frame is designed to eliminate slipping and twisting that occurs with round tube frames. Supplied with sturdy platform legs.

Slip-fit construction permits fast, easy assembly without tools.

| | | Price |
|----------|----------------------------------|---------|
| Part No. | Description | /Each |
| 0800230 | 6' x 6' Orange (Transparent) | \$98.93 |
| 0800235 | 6' x 8' Orange (Transparent) | 124.62 |
| 0800231 | 6' x 6' Yellow (Transparent) | 98.93 |
| 0800236 | 6' x 8' Yellow (Transparent) | 124.62 |
| 0800232 | 6' x 6' Green (Transparent) | 98.93 |
| 0800237 | 6' x 8' Green (Transparent) | 124.62 |
| 0800134 | 6' x 6' Olive Drab Duck (Opaque) | 98.93 |
| 0800135 | 6' x 8' Olive Drab Duck (Opaque) | 124.62 |

Portable Welding Screen

Quick, easy set-up and take down. No hardware to install. No tools necessary. Roll open and stand on horizontal end for use as welding, grinding or safety shield. Roll up and carry away.

- 14oz Safety Yellow
- Vinvl provides resistance to flame -NFPA-701 certified
- 12 oz. Olive Drab Cotton Duck is a permanently treated cotton to repel water and resist mildew. CPAI-84 approved for flame resistance

| | Vendor | | | Price |
|----------|--------|----------------------------|----------|---------|
| Part No. | No. | Material | Size | /Each |
| 0800207 | 43134 | Vinyl Coated Polyester | 3'h x4'w | \$94.95 |
| 0800208 | 43146 | Vinyl Coated Polyester | 4'h x6'w | 139.95 |
| 0800209 | 43165 | Vinyl Coated Polyester | 5'h x6'w | 175.99 |
| 0800210 | 43196 | Vinyl Coated Polyester | 6'h x9'w | 239.95 |
| 0800218 | 40134 | Fire-Retardant Cotton Duck | 3'h x4'w | 89.95 |
| 0800219 | 40146 | Fire-Retardant Cotton Duck | 4'h x6'w | 129.95 |
| 0800220 | 40165 | Fire-Retardant Cotton Duck | 5'h x6'w | 159.95 |
| 0800221 | 40196 | Fire-Retardant Cotton Duck | 6'h x9'w | 239.95 |

Blankets



Carbon Fiber 3,000°F Weld Blanket

Steiner[™] Velvet Shield[®] Amazingly soft, lightweight and flexible yet are extremely fire and heat resistant. A 6' x 8' blan ket weighs just 5 lbs. Will withstand temperatures of 1800°F continuous and up to 3,000°F intermittent. Velvet Shield welding blankets are designed to be draped over materials and equipment to provide protection from flying sparks or slag given off by nearby grinding, welding, or cutting operations.



- · Velvet Shield welding Blankets are made with
- Carbon fiber fabric that was developed from NASA technologies and is extremely fire and heat resistant
- · Versatile blankets are soft and light weight, providing incredible ease of use
- Ideal for use in Autobody, Automotive Repair,
- HVAC and Plumbing applications
- Tough, tear resistant material
- · Easy to clean; just shake, vacuum or blow metal particles out

| | Vendor | | Price |
|----------|--------|-----------|---------|
| Part No. | No. | Size | /Each |
| 0800150 | 31618 | 18" x 18" | \$18.42 |
| 0800151 | 31634 | 3' x 4' | 46.72 |
| 0800152 | 31654 | 5' x 4' | 77.89 |
| 0800153 | 31646 | 4' x 6' | 93.39 |
| 0800154 | 31655 | 5' x 5' | 97.34 |
| 0800155 | 31665 | 6' x5' | 113.53 |
| 0800156 | 31666 | 6' x 6' | 140.11 |
| 0800157 | 31686 | 8' x 6' | 186.77 |
| 0800158 | 31688 | 8' x 8' | 249.11 |
| 0800159 | 31606 | 6' x 10' | 233.56 |
| 0800160 | 31608 | 8' x 10' | 311.50 |

BLACKSTONE Welding Blankets

Use these fire-resistant covers to protect equipment and personnel near potentially hazardous or messy operations, such as welding, grinding or spraying. Brass tie-down grommets located at corners and center of long sides.

Fiberglass material is coated on one side with neoprene which adds strength and durability, other side has acrylic coating. Withstands continuous exposure to 400°F, excursions to 1000°F. Acrylic side should be directed toward heat source. Coating is smooth and helps protect the covered surfaces.



| | | Price |
|----------|--------------|----------|
| Part No. | Description | /Each |
| 0800260 | 6' x 6' Gold | \$108.15 |
| 0800261 | 6' x 8' Gold | 123.19 |

11 - 6Welding

BLANKETS, CABLE & ELECTRODE HOLDERS

Blankets Cont.

BLACKSTONE

Shedcoat Fiberglass Welding Blanket

Fiberglass is coated on both sides with special neoprene based coating that strengthens the cloth. Withstands continuous exposure to 400°F, intermittent exposure to 750°F. Will shed molten metal up to

3000°F when on an incline of at least 15° Better abrasion resistance than Neoprene coated blankets.



| Part No. | Description | /Each |
|----------|---------------|----------|
| 0800262 | 6' x 6' Black | \$108.88 |
| 0800263 | 6' x 8' Black | 112.00 |

Silica Welding Blanket for High Heat Applications

Silica Bronze - Heat resistant material widely used as blankets for protecting materials and equip-

ment in welding areas from sparks and molten spatter. Silica dioxide material will take up to 1500°F on a horizontal plane. This excellent blanket material is not recommended for curtain use.

· Lightweight 18 oz Silica Bronze material

· Less irritable to skin and non-respirable

· Low thermal conductivity

| | | Price |
|----------|--------------------------------|---------|
| Part No. | Description | /Each |
| 0800282 | 6' x 6' Silica Bronze | \$95.67 |
| 0800283 | 6' x 8' Silica Bronze | 129.17 |
| 080028/ | 36" x 50 vd Boll Silica Bronze | 777 60 |

Thoughquard Fiberglass Welding Blanket

Toughguard - Heat cleaned fiberglass material provides economical high temperature protection. Takes temperatures up to 1000°F. Ideal for heat treating blankets, high-temperature curtains and light to moderate molten splash

protection. Material is tan in color.



| | | Price |
|----------|----------------------------------|---------|
| Part No. | Description | /Each |
| 0801054 | 4' x 6' 18 oz. Toughguard | \$44.00 |
| 0801056 | 6' x 6' 18 oz. Toughguard | 52.00 |
| 0801057 | 6' x 8' 18 oz. Toughguard | 70.00 |
| 0801053 | 8' x 10' 18 oz. Toughguard | 125.00 |
| 0801097 | 40" x 50Yd. Roll 18oz Toughguard | 334.00 |

sellst.rnm. **Emergency Fire** Blanket

The fire blanket is 5' x 6' fiberglass providing 1000°F continuous service temperature. In a hanging pouch.



| Vendor | | Price | |
|----------|-------|---------|--|
| Part No. | No. | /Each | |
| 0800264 | 97450 | \$97.13 | |

Cable

BLACKSTONE

Welding Cable (Welding Leads)



*Diagram not to scale

| | | | UOM |
|------------|------------|-----------|-----|
| Part No. | Size | Pkg. Qty. | /Ft |
| #4 Cable | | | |
| 0812000 | 250' Roll | 250 | |
| 0812001 | 25' Boxed | 25 | |
| 0812020 | 50' Boxed | 50 | |
| 0812003 | 100' Boxed | 100 | |
| #2 Cable | | | |
| 0812002 | 250' Roll | 250 | |
| 0812005 | 25' Boxed | 25 | |
| 0812021 | 50' Boxed | 50 | |
| 0812011 | 100' Boxed | 100 | |
| #1 Cable | | | |
| 0812004 | 250' Roll | 250 | |
| 0812009 | 25' Boxed | 25 | |
| 0812022 | 50' Boxed | 50 | |
| 0812023 | 100' Boxed | 100 | |
| #1/0 Cable | | | |
| 0812006 | 250' Roll | 250 | |
| 0812013 | 25' Boxed | 25 | |
| 0812014 | 50' Boxed | 50 | |
| 0812015 | 100' Boxed | 100 | |
| #2/0 Cable | | | |
| 0812008 | 250' Roll | 250 | |
| 0812017 | 25' Boxed | 25 | |
| 0812018 | 50' Boxed | 50 | |
| 0812019 | 100' Boxed | 100 | |
| #3/0 Cable | | | |
| 0812010 | 250' Roll | 250 | |
| #4/0 Cable | | | |
| 0812012 | 250' Roll | 250 | |

Welding Lead Assemblies Cables, Holders and Clamps Assembled-Ready-To-Go 20' Weld Lead Assembly

This Kit contains 2 ea #2 welding cable leads. The first lead consists of a 20' length of cable with an electrode holder on one end and a small diameter quick connect male on the other end. The second lead consists of a a 15' length of cable with a 300 amp ground clamp and another small male guick connect. These are ready to plug into 2 female quick connect receptacles (0812190) available separately.

| | Part No. | /Each |
|---|----------|-------|
| Ľ | 0816104 | |

30' Weld Lead Assembly

This Kit contains 2 ea #2 welding cable leads. The first lead consists of a 30' length of cable with an electrode holder on one end and a small diameter quick connect male on the other end. The second lead consists of a a 30' length of cable with a 300 amp ground clamp and another small male guick connect. These are ready to plug into 2 female quick connect receptacles (0812190) available separately.

| Part No. | UOM /Each |
|----------|--------------|
| 0816105 | |

50' Weld Lead Assembly

This Kit contains 2 ea #1 welding cable leads. The first lead consists of a 50' length of cable with an electrode holder on one end and a small diameter quick connect male (0812186) on the other end. The second lead consists of a a 50' length of cable with a 300 amp ground clamp and another small male quick connect (0812186). These are ready to plug into 2 female quick connect receptacles (0812190) available separately.

| Part No. | /Eacl |
|----------|-------|
| 0816106 | |
| | |

Extra Quick Connects

| | | | Price |
|---|----------|---------------------------------|---------|
| | Part No. | Description | /Each |
| l | 0812182 | Pair of LC-10 Quick Connects | \$20.17 |
| l | 0812186 | Male Only LC-10 Quick Connect | 10.09 |
| l | 0812190 | Female Only LC-10 Quick Connect | 10.09 |
| l | 0812149 | Female Quick Connect with | 13.52 |
| l | | Inch Bolt Hole to Connect to | |
| l | | Welding Machine with 1/2" Wtud | |
| | | | |

Electrode Holders (Stingers)

LENCO Electrode Holders Stingers

HT-Series

The "HT" series features a new, fully insulated upper lever with more hand clearance for operator preference.

| Part No. | Model No. | Amp. Capacity | Electrodes Up To | Price /Each |
|----------|--------------|------------------|---------------------|----------------|
| 0812058 | HT-2 | 250 | 5/32" | \$24.11 |
| 0812060 | HT-25 | 300 | 3/16" | 30.66 |
| 0812062 | HT-3 | 350 | 1/4" | 31.92 |
| 0812064 | HT-35 | 400 | 1/4" | 40.12 |
| 0812059 | HT-50 | 500 | 3/8" | 44.35 |
| | | | | |

AF-Series

The AF series holders are designed to fit comfortably in the welder's hand. The low profile design allows the LENCO electrode holder to fit a welder's hand like a glove and provide superior electrode control.

| | Model | Amp. | Electrodes | Price | | |
|----------|-------|----------|------------|---------|--|--|
| Part No. | No. | Capacity | Up To | /Each | | |
| 0812067 | AF-1 | 200 | 5/32" | \$23.51 | | |
| 0812075 | AF-2 | 250 | 5/32" | 24.11 | | |
| 0812077 | AF-25 | 300 | 3/16" | 30.66 | | |
| 0812079 | AF-3 | 350 | 1/4" | 31.92 | | |
| 0812081 | AF-35 | 400 | 1/4" | 40.12 | | |
| 0812083 | AF-50 | 500 | 3/8" | 44.35 | | |
| | | | | | | |

LT-Twister

The LT-400 "Twister"


design minimizes exposed screws, internal metal parts or any current carrying members in the holder for added user safety. The electrode may be secured or loosened with a quarter turn of the handle. Holds electrodes up to 1/4", 400 amp.

| Model | | Electrodes | Price |
|----------|--------|------------|---------|
| Part No. | No. | Up To | /Each |
| 0812065 | LT-400 | 1/4" | \$43.00 |

| A-W • 300 Ampere • 1/4" electrod • No. 3 throug • Weight: 14 d • Aluminum a • 45% duty cy | de capacity In 2/0 cable capacity Dz. Illoy | |
|---|--|----------------|
| Part No. | Description | Price /Each |
| 0801846 | A-W Electrode Holder | \$45.99 |
| | | 11_7 |

The : symbol after a price denotes that it is a Direct Ship Product (DSP) and shipping, availability & lead times may vary.

ELECTRODE HOLDERS, CLAMPS, SPLICERS & CABLE QUICK CONNECTS



| Part No. | No. | Capacity | Opening | /Each |
|----------|-----|----------|---------|---------|
| 0812180 | 200 | 200 | 1" | \$18.53 |
| 0812228 | 300 | 300 | 1-1/2" | 26.02 |
| 0812230 | 500 | 500 | 1-1/2" | 32.38 |

Rounded Style



| | Model | Amp. | Jaw | Price |
|----------|---------|----------|---------|---------|
| Part No. | No. | Capacity | Opening | /Each |
| 0812225 | LPG-200 | 200 | 1" | \$26.90 |
| 0812220 | LPG-300 | 300 | 1-1/2" | 39.59 |
| 0812222 | LPG-500 | 500 | 2" | 48.90 |

Economy Steel Ground Clamps

The Model EG-200 ground clamp is ideal for light duty welders. May be used for other light duty applications. The Model EG-300 ground clamp is ideal for the farm welder or for light shop work. The Model EG-500 is excellent for field erection or where clamping to bar stock, piping or various shapes of metal are necessary. The pure copper braided shunt allows both high copper alloy jaws to carry welding current. A rugged, all steel body protects the heavy duty spring.

| Part No. | Model No. | Amp. Capacity | Jaw Opening | Price /Each |
|----------|--------------|------------------|----------------|----------------|
| 0812179 | EG-200 | 200 | 1-1/2" | \$7.06 |
| 0812224 | EG-300 | 300 | 2" | 8.89 |
| 0812226 | EG-500 | 500 | 2" | 19.33 |

| Devit No. | Model | ć | pe of able | Pric |
|---|---|---|--|---|
| Part No. 0812234 | No. G | | nection pt. Screws | /Eac \$68.6 |
| 0812232 | MIG 600-D | LC-40 Quick | | |
| Built to er over-heat point scre to size 4/0 square in | ing due to fe ws and a co D cable to be ches of space | p r efficiency v ever junction onnection cor e utilized. Co ce-3 square on ferrous m | s. Two ova ver allow ι vers 12 inches | |
| per side. | | | | |
| per side. | Model | Amp | _ | Pric |
| Part No. | Model No. | Amp. Capacity | Weight | Pric /Eac |
| Part No. 0812221 | No. MSG-500 | Capacity 500 | Weight 4 lbs. | |
| Part No. 0812221 ACKSON GC-2 • 200 Am • 1-1/4" ja • No.4 thr | No. MSG-500 | Capacity 500 | | /Eac \$101.1 |
| Part No. 0812221 JACKSON GC-2 • 200 Am • 1-1/4" ja | No. MSG-500 Ground peres tw capacity ough 1/0 ca | Capacity 500 | 4 lbs. | /Eac |
| Part No. 0812221 Jackson GC-2 200 Am 1-1/4" jz No.4 thr Part No. 0801850 GC-3 300 Am 1-5/8" jz | No. MSG-500 Ground peres tw capacity ough 1/0 ca GC Ground peres tw capacity ugh 2/0 cabl | Clamp Clamp ble capacity Description -2 Ground Clamp | 4 lbs. | /Eac \$101.1 Price /Eacl \$15.0 |
| Part No. 0812221 GC-2 • 200 Am • 1-1/4" jz • No.4 thr Part No. 0801850 GC-3 • 300 Am • 1-5/8" jz • 1/0 throi | No. MSG-500 Ground peres tw capacity ough 1/0 ca GC Ground peres tw capacity ugh 2/0 cabl | Clamp Clamp ble capacity Description -2 Ground Clamp | 4 lbs. | /Eac |

| Part No. | Description | /Each |
|----------|-------------------|---------|
| 0801852 | GC-5 Ground Clamp | \$31.00 |
| | | |

Cable Lugs and Splicers Crimp/Solder Cable LENCO Luas

Precision made lugs from copper tubing. Extra long barrel for easy soldering or attaching by swedg-on process. Stud holes are made especially for welding machines with plenty of clearance. Flared ends make it easy to insert the cable into the lug. L-4 to L-26 have 21/64stud hole . L1-L3040 have 17/32 stud hole.

| IJ | ĥ | Î | Â | l | Ð | J | | Î |
|------|------|--------|------------|-----|-----|------|----|--------|
| | | Moo | del | Cab | ole | Barr | el | Price |
| Part | No. | No |) . | Siz | e | I.D | | /Each |
| 0812 | 2130 | L | 4 | #8- | #6 | .286 | ò" | \$0.87 |
| 0812 | 2135 | L÷ | 2 | #6- | #4 | .336 |)" | 1.14 |
| 0812 | 2132 | L-2 | 26 | #6- | #2 | .344 | ." | 1.71 |
| 0812 | 2137 | L-1 (L | 25) | #6- | #2 | .360 |)" | 1.49 |

#2-#1

#1/0-#2/0

#3/0-#4/0

.402

.495

620

1.67

2.69

3.36

0812138

0812134

0812136

L-12

L-1020

1-3040

Mechanical Cable Lugs

Mechanical lugs replace the ordinary solder lugs. Cable is easily attached using large oval-point screw connections. Include fiber insulator cover. 45 degree angle (AI) or straight (SI) available. 17/32 Opening for Lug. 610 Model uses up to 1/0 cable, 2040 Model uses up to 4/0 cable.

| | Model | Price |
|----------|-----------|---------|
| Part No. | No. | /Each |
| 0812145 | LM-610AI | \$13.19 |
| 0812146 | LM-610SI | 13.19 |
| 0812147 | LM-2040AI | 16.72 |
| 0812148 | LM-2040SI | 16.72 |

Cable Splicers

LENCO Cable Splicers are made from a special high con-

ductivity brass extrusion. Large oval-point screws on each end of the splicers make it easy to splice cables in the shop or in the field. Tough fiber sleeve insulates the splicers.

| Part No. | Model No. | Cable Size | Price /Each |
|----------|--------------|---------------|----------------|
| 0812176 | CS-610 | #6-#1/0 | \$13.52 |
| 0812177 | CS-2040 | #1/0-#2/0 | 15.01 |
| 0812178 | CS-3040 | #3/0-#4/0 | 21.37 |

Cable Quick Connects



Cable Connectors

Cable quick connects allow the welding machine operator to quickly remove the cables from the welding machine or add extensions onto the existing cables. Ideal for job sites where the length of cables needed is always changing. Cam action design of the male half pulls the two pieces together tightly. Covers are molded from special heat and cold resistant material. Two size connections, the LC-10 is compatible with Tweco® #1 connectors and the LC-40 and LC-40HD are compatible with Tweco® #2 and #4 connectors. Covers are available in colors other than black making it easier to see. The whip connector has the LC-40 size pin but takes the LC 10 size cable. (Color: Black)

| | Pkg. | | Cable | Price |
|----------|-------------|---------|-------|---------|
| Part No. | Qty. | Size | Size | /Each |
| 0812182 | Pair | LC-10 | | \$20.17 |
| 0812186 | Male Only | LC-10 | | 10.09 |
| 0812190 | Female Only | LC-10 | | 10.09 |
| 0812198 | Pair | LC-40 | 2/0 | 23.00 |
| 0812202 | Male Only | LC-40 | 2/0 | 11.50 |
| 0812206 | Female Only | LC-40 | 2/0 | 11.50 |
| 0812164 | Pair | LC-40HD | 4/0 | 25.28 |
| 0812207 | Male Only | LC-40HD | 4/0 | 12.64 |
| 0812208 | Female Only | LC-40HD | 4/0 | 12.64 |
| 0812168 | Whip-Male | LC-40 | 1/0 | 11.89 |

Quick Connect Welding Machine Terminals

Quick connect terminals offer the advantage of quickly connecting welding cables at the power source.



They are used in place of solder tube lugs and are bolted directly to the output studs of the machine. The male quick connect on the end of the welding cable will plug directly into this terminal. Terminals are at an angle of 45° to allow clearance from the welding machine panel. Two connector sizes are offered: The 10FA will accept the LC-10 plugs: the 40FA will accept the LC-40 & LC-40HD plugs. 17/32 Stud Hole Diameter.

| Model | | Price |
|----------|---------|---------|
| Part No. | No. | /Each |
| 0812149 | CT-10FA | \$13.52 |
| 0812152 | CT-40FA | 16.72 |

fastenal.com

11-8 Welding

CABLE PLUGS, CHEMICALS & ANTI-SPATTER

Machine Cable Plugs

Machine Cable Plugs

UP Style



These plugs are designed to fit welding machines using long tapered plugs and receptacles. Oval-point screws secure the cables inside the plug. UP style fits into Century™, Forney[™], Powermate[™] and others similar. Cable Size = #4-#1/0, Taper Dim. = .364"-.385", Taper Length = 1.00°

| Part No. | Model No. | Color | Price /Each |
|----------|--------------|-------|----------------|
| 0812175 | UP-10R | Red | \$13.36 |
| 0812173 | UP-10B | Black | 13.36 |

LC-10 M.P

LC-10MP

These plugs are designed to fit welding

machines using long tapered plugs and receptacles. Oval-point screws secure the cables inside the plug. LC-10MP style fits into Miller® welders. It replaces the Miller® 039608 plug. Cable Size = #4-#1/0, Taper Dim. = .330"-.352", Taper Length = 1.062"

| Part No. | Model No. | Color | Price /Each |
|----------|--------------|-------|----------------|
| 0812172 | LC-10MP-R | Red | \$13.36 |
| 0812171 | LC-10MP-B | Black | 13.36 |

Chemicals & Anti-Spatter Products



Metal Repair & Maintenance Lab-metal

Aluminum filled repair compound. Onepart, needs no catalyst. Spreads like paste, hardens into metal. Withstands temperatures to 350° F Patches fills rebuilds and repairs metal and nonmetal



Lab-metal

Lah-solvent

SHARES FOR LAR ANT

items. Lab-metal can be drilled, tapped and ground. Water resistant and rustproof. Thin it with Lab-solvent for brushing or spraying a metallic coating.

| Size of | | Price |
|----------|--------|---------|
| Part No. | Units | /Each |
| 0815225 | 12 oz. | \$22.99 |
| 0815226 | 24 oz. | 34.99 |

Hi-temp Lab-metals

Aluminum-filled repair compound. Onepart, spreads like paste, hardens into metal for repairs to 1000°F. Repairs items prior to lengthy or repeated high-temperature powder coating processes, and

repairs core boxes, boilers, mufflers, grills and engines.

| | Size of | Price | |
|----------|---------|---------|--|
| Part No. | Units | /Each | |
| 0815227 | 24 oz. | \$59.99 | |

Lab-Solvent

Thinner for Lab-metal, Hi-Temp Labmetal and also a metal cleaner. Surfaces cleaned with Lab-solvent provide superior adhesion for Lab-metal and Hi-Temp Lab-metal. Lab-solvent also protects the unused contents of

Alvin repair putties - add a capful to the unused Lab-metal and cover tightly after use. Labsolvent cuts and flushes oil, grease and dirt from precision tools, bearings, gears, motors, condensers, controls, and other valuable equipment.

| Part No. | Size of Units | Price /Each |
|----------|------------------|----------------|
| 0815228 | 16 oz. | \$14.99 |

Heat Absorbing Compound Heat Block

Heat sink / heat absorbing paste. Cost saving, non-toxic and easy to use. Protects against heat damage during welding, soldering, brazing and other heat treatments. Used in welding, automotive, plumbing, shipyard and other specialized industries.

| Part No. | Size of Units | Price /Each |
|----------|------------------|----------------|
| 0815229 | Pint | \$9.73 |
| 0815230 | Quart | 23.65 |
| | | |

BLACKSTONE

Blackstone® Nozzle Dip



CR 395 Anti Spatter

Anti-spatter spray. Water based. No solvents, fluorocarbons, hydro-carbons. Nonflammable. Ozone safe. 16 oz. can.

| | | Contrast Contrast |
|----------|---------------|-------------------|
| Part No. | Description | Price /Each |
| 0815207 | 16 oz. Can | \$5.80 |
| 0815197 | 1 Gallon Jug | 17.77 |
| 0815193 | 5 Gallon Pail | 76.29 |
| | | |

0

0

Anti-Spatter

Anti-spatter spray. Silicone free. Solvent based, 16 oz. can. -SPAT 00

| | Price |
|----------|--------|
| Part No. | /Each |
| 0815204 | \$5.63 |
| | |

Safe-De-Spat

Anti-spatter spray. No chlorinated solvents, no harmful fumes, no fluorocarbons, hydrocarbons, silicone. Non flammable, non-toxic. 16 oz. can

| Price /Each |
|----------------|
| \$5.29 |
| |

Enviro-Spat

Anti-spatter spray. 16 oz. can. No Solvents, silicones, fluorocarbons, or hydrocarbon compounds. Surfactant based. Can be welded through while wet. Can be painted over when dry. 16 oz. can.



Wire Feed Pads Designed for use on all

mig wire feeders to remove

dust and dirt from the wire prior to entry into the mig gun liner. Prevents build-

up of dirt that plugs liners. Just clip them onto the welding wire before the drive rolls. Treated pads are for steel, stainless steel, hardfacing, silicone bronze, solid and flux cored wires. Untreated pads are for aluminum wire use. 6/pkg. 60/case.

| | | Price |
|----------|-------------|--------|
| Part No. | Description | /Each |
| 0815208 | Treated | \$1.34 |
| 0815210 | Untreated | 1.29 |

Wire Feed Pad Lube

This lube is applied to the lube pad allowing the welding wire to move down the liner more smoothly.



| Part No. | Vendor No. | Price /Each |
|----------|---------------|----------------|
| 0815215 | 007040 | \$8.55 |

Crack Check Non-Destructive Testing

Crack Check Red Dve Penetrant Inspection Method

The Visible Penetrant Inspection method is a non-destructive method of locating microscopic flaws such as cracks, pores, pin holes and laps which are open to the surface of welds, castings, exotic alloys and standard materials. Visible Penetrant inspection is one of the most common



of modern non-destructive testing methods. It has achieved prominence because of the extreme simplicity of the process, which when coupled with its high degree of accuracy and low cost, makes it a favorite of many quality engineers.

| Part No. | Vendor No. | Description | Price /Each |
|-----------|---------------|------------------|----------------|
| Cleaner | | | |
| 0815500 | CNF315-12 | 15.1 oz. Aerosol | \$8.83 |
| Penetrant | | | |
| 0815503 | PHF315-12 | 9.4 oz. Aerosol | \$10.06 |
| Developer | | | |
| 0815506 | DNF315-12 | 14.2 oz. Aerosol | \$10.26 |

Startup Kit

Kit includes one can each of Penetrant and Developer, 2 cans of Cleaner, instructions and handy carrying/storage box.

| | Vendor | | Price |
|----------|-------------|-------------|---------|
| Part No. | No. | Description | /Each |
| 0815509 | DF315-KIT-S | Basic Kit | \$37.95 |

00

The : symbol after a price denotes that it is a Direct Ship Product (DSP) and shipping, availability & lead times may vary.

WELDING TOOLS

Welding Tools FASTENAL

Welding Tools & Accessories



| Part No. | Description | Pkg. Qty. | Price /Each |
|----------|-------------------------------|-----------|----------------|
| 0815050 | Box of 12 #753 Silver Pencils | 12 | \$0.81 |
| 0815051 | Red Pencil | 12 | 0.82 |
| 0815053 | Round Soapstone | 144 | 0.12 |
| 0815056 | Flat Soapstone, Bulk Box | 144 | 0.08 |
| 0815059 | Round Holder with 5 pieces | 1 | 4.72 |
| 0815060 | Round Holder Empty | 1 | 2.50 |
| 0815062 | Flat holder with 5 pieces | 1 | 4.45 |
| 0815063 | Flat Holder Empty | 1 | 2.00 |

Markal Thermomelt[®] Temperature **Indicating Sticks**



| | Melting | Price |
|----------|---------|---------|
| Part No. | Temp. | /Each |
| 0815101 | 125° | \$12.49 |
| 0815102 | 150° | 12.49 |
| 0815103 | 175° | 12.49 |
| 0815100 | 200° | 12.49 |
| 0815105 | 225° | 12.49 |
| 0815106 | 250° | 12.49 |
| 0815107 | 275° | 12.49 |
| 0815104 | 300° | 12.49 |
| 0815109 | 325° | 12.49 |
| 0815110 | 350° | 12.49 |
| 0815111 | 375° | 12.49 |
| 0815108 | 400° | 12.49 |
| 0815113 | 450° | 12.49 |
| 0815112 | 500° | 12.49 |
| 0815114 | 550° | 12.49 |
| 0815115 | 575° | 12.49 |
| 0815116 | 600° | 12.49 |
| 0815117 | 650° | 12.49 |
| 0815120 | 700° | 12.49 |
| 0815124 | 800° | 12.49 |
| 0815128 | 900° | 12.49 |
| 0815132 | 1000° | 12.49 |
| 0815118 | 1100° | 12.49 |
| 0815119 | 1150° | 12.49 |
| 0815121 | 1300° | 12.49 |

BLACKSTONE Wire Scratch Brushes

Straight Handle



| Part No. | Description | Case Qty. | Price /Each | | |
|----------|-----------------|-----------|----------------|--|--|
| 0815600 | Carbon Steel | 12 | \$2.30 | | |
| 0815610 | Stainless Steel | 12 | 2.69 | | |
| Shoe Ha | Shoe Handle | | | | |

| Part No. | Description | Case Qty. | Price /Each |
|----------|-----------------|-----------|----------------|
| 0815620 | Carbon | 12 | \$1.53 |
| 0815630 | Stainless steel | 12 | 2.83 |
| | | | |

| Smaller Scratch Brushes | | | | | | |
|-------------------------|---------------|-----------------------|--------------------|----------------|--|--|
| Part No. | Brush Size | Brush Material | Handle Material | Price /Each | | |
| 0824516 | 7-1/2" x 1/2" | .006 S/S | Plastic | \$3.09 | | |
| 5138-44167 | 7-1/2" x 1/2" | .006 S/S | Wood | 3.14 | | |
| 5138-44189 | 7-1/2" x 1/2" | .006 Straight | Wood | 3.38 | | |
| 5138-44619 | 6" x 1/2" | .005 Crimped Brass | Wood | 3.02 | | |

Chip & Oil Brushes

11-



| Stanuaru | | | | | |
|------------|-------|-----------|-------------------|----------------|--|
| Part No. | Width | Thickness | Bristle Length | Price /Each | |
| 0818832 | 1" | 5/16" | 1-11/16" | \$1.15 | |
| 5138-40132 | 2" | 5/16" | 1-11/16" | 1.66 | |
| 0818833 | 4" | 11/16" | 2-1/4" | 7.11 | |



Economy

| Part No. | Width | Thickness | Bristle Length | Price /Each |
|------------|--------|-----------|-------------------|----------------|
| 5138-40066 | 1" | 5/16" | 1-3/4" | \$0.69 |
| 5138-40067 | 1-1/2" | 5/16" | 1-3/4" | 0.97 |
| 5138-40068 | 2" | 5/16" | 1-3/4" | 1.16 |
| 5138-40069 | 2-1/2" | 3/8" | 1-3/4" | 2.12 |
| 5138-40070 | 3" | 3/8" | 1-3/4" | 2.01 |
| 5138-40071 | 4" | 5/8" | 2" | 4.88 |

Copper Tubing Brushes

For internal cleaning and deburring of copper tube fittings. Also used in trucking and marine industries as a light socket cleaning

| brush. | | | |
|------------|----------|--------|--------|
| | For Tube | | Price |
| Part No. | I.D. | OaL | /Each |
| 5138-44081 | 1/2" | 6-1/2" | \$3.41 |
| 0819000 | 3/4" | 6-1/2" | 3.68 |

Flux / Acid Brushes

Horsehair with a Tin ferrule handle

| Part No. | Size | Pkg. Qty. | Price /Each |
|----------|----------------------|-----------|----------------|
| 0818058 | 3/8"w x 5-3/4" Long | 144 | \$0.25 |
| 0818059 | 1/2" w x 5-3/4" Long | 144 | 0.51 |

Multipurpose Plumber's Brush

Cleans the outside and 22.4 inside diameters of 1/2" and 3/4" tubes and fittings. Use for soldering prep, deburring, drill hole cleaning and cleaning battery terminals. For Tube For Tube Price OaL Part No. I.D. O.D. /Each 5138-44690 1/2" &3/4' 5/8" &7/8 \$21.31



Welders File Kit

SIMONDS

"Black Maxi-Sharp Finish, designed with Welder's in mind, 5 files and 2 brushes offer great flexibility in use. Black oxide coated to resist rust, prevent clogging and stay sharper longer."





Welding C-Clamp

Drop-forged, heat steel frame and swivel pad. Copper coated spindle resists welding spatter



| Part No. | Vendor No. | Throat Depth | Nom. Opening | Price /Each |
|----------|---------------|-----------------|-----------------|----------------|
| 0825464 | CDF402C | 2" | 2" | \$23.02 |
| 0825465 | CDF403C | 2-3/8" | 3" | 28.78 |
| 0825466 | CDF404C | 2-3/4" | 4" | 32.50 |
| 0825467 | CDF406C | 3-5/8" | 6" | 40.68 |
| 0825468 | CDF408C | 4-1/2" | 8" | 52.97 |
| 0825462 | CDF410C | 5-3/8" | 10" | 70.24 |
| 0825463 | CDF412C | 5-3/4" | 12" | 85.22 |

fastenal.com

11-10 Welding

TOOLS, MAGNETIC ACCESS., ROD CONTAINERS & PIPEFITTERS

Welding Tools Cont.

BESSEY



SQ Series "Super Quick"

- Premium all-steel sliding arm clamps equipped with a replaceable economical standard swivel pad built for solid dependable performance
- Rails and fixed top jaw are drawn, heat treated, tempered and guenched under rigid controls in Bessy's own steel plant

• 2,660 lbs. clamping pressure

| | Vendor | Throat | | Price |
|----------|--------|--------|----------|---------|
| Part No. | No. | Depth | Capacity | /Each |
| 0850615 | SQ-4 | 4-3/4" | 6" | \$40.21 |
| 0850616 | SQ-8 | 4-3/4" | 8" | 70.53 |
| 0850613 | SQ-12 | 4-3/4" | 12" | 100.66 |
| 0850614 | SQ-20 | 4-3/4" | 20" | 125.39 |

Mighty Mini[™] Quick Clamp

All Steel Clamp 9 times faster than a "C" Clamp The little clamp that does the work of a 1", 3", 6" c-

clamp...but does it 9x faster Bessev's smaller version of their premium all-steel clamps



| | Vendor | Throat | | Price |
|----------|--------|--------|----------|---------|
| Part No. | No. | Depth | Capacity | /Each |
| 0850609 | MMS-4 | 2-1/4" | 4" | \$20.62 |
| 0850610 | MMS-8 | 2-1/4" | 8" | 25.01 |

Tip Cleaners

Tip Cleaners

| Part No. | Description | Price /Each | |
|----------|-------------|----------------|---|
| 0810400 | Std. Set | \$3.86 | 5 |
| 0810401 | King Set | 4.25 | 5 |
| 0810403 | Jumbo Set | 3.25 | 5 |

Tip Drill Kits

| | discussion in the second | |
|----------|---------------------------|---------|
| | | Price |
| Part No. | Description | /Each |
| 0810404 | Kit-holder with 12 drills | \$11.55 |

Magnetic Accessories

SIMONDS

Magnetic Welding Magnets

Magnetic clamps offer quick set up and secure holding of work pieces. Magnetic clamps are equally effective holding steel sheet, plate, or

pipe and tubing. The offering includes clamps with built in fixed angles as well as adjustable



| | woder | | Price |
|----------|---------|----------------------|---------|
| Part No. | No. | Description | /Each |
| 0825450 | SM951 | 22# Pull Weld Clamp | \$15.35 |
| 0825451 | SM953 | 53# Pull Weld Clamp | 18.34 |
| 0825452 | SM954 | 55# Pull Weld Clamp | 19.95 |
| 0825453 | SM955 | 110# Pull Weld Clamp | 29.13 |
| 0825454 | SM956 | 57# Pull Weld Clamp | 25.48 |
| 0825455 | SM957 | HD Mag Weld Clamp | 33.26 |
| 0825456 | SM958 | XHD Mag Weld Clamp | 70.66 |
| 0825457 | SM959 | SHD Mag Weld Clamp | 163.86 |
| 0825458 | SM920MF | ADJ Mag Weld Clamp | 47.47 |

Magnetic Squares

| wo very strong squaring clamps offer velders and fabricators a quick and | 10 |
|---|----|
| asy solution to holding work pieces at xed 90 degree angles. Each is apable of holding sheet, plate, ipe and tubing. | |

| | Model | | Price |
|---------|-------|--------------------|----------|
| art No. | No. | Description | /Each |
| 825459 | SM974 | Mag Weld Square | \$126.22 |
| 825460 | SM975 | HD Mag Weld Square | 216.18 |
| | | | |

BESSEY

T١ w

e fix Cá

p



Multipurpose welder's magnetic squares are like having a 2nd pair of hands. High

Magnetic Squares

quality rare earth and ferrite magnets are designed for fast, simple set ups. Hold work firmly at 45, 90 & 135 degree angles.

| | | | | Price |
|----------|----------------------------|-------------|---------|---------|
| Part No. | Description | Dimension | Pull | /Each |
| 0850620 | WMS-3 Compact | 3-3/8"x | 55lbs | \$10.74 |
| | Magnetic Welders Square | 3-3/3"x5" | | |
| 0850621 | WMS-5 Super | 3-3/4"x | 112lbs. | 21.82 |
| | Square | 4-3/8"x3/4" | | |

Welder's Magnetic Ground Clamps

Spring loaded electrode secures ground to work surface; rotating stud assembly allows ground wire to rotate 360°.

| Part No. | Description | Price /Each |
|----------|----------------------------------|----------------|
| 0850607 | MGC-1 (250 AMP)Mag Ground Clamp | \$29.87 |
| 0850608 | MGC-2 (800 AMP) Mag Ground Clamp | 36.16 |

Welding Rod Ovens and Storage Containers

Dynaflux Rod Oven

- Electrode Capacity: 50 lbs/22.7 Kg 12"/14"/18" (45.7 cm max.)
- 120V; 350 Watts
- Thermostat is adjustable
- Temperature Range is 150°F-300°F, 60°C-150°C · Element: 1 each 350 watt arc element for even
- heat distribution Stainless Steel Non Corrosive/Lifetime finish
- · Illuminated power indicator
- Dimensions: 23" x 9" x 9"; 8' Power Cord
- Shipping Weight: 30 lbs./13.9 Kg



0815306



| | | Ē |
|---|-------|---|
| 1 | | d |
| | | С |
| | | С |
| | Price | v |
| | 11100 | |

Price

/Each

\$404.44

5

| Description | Rod Lgth. | /Each |
|------------------|-----------|---------|
| Stick Rod Holder | 14" | \$11.48 |
| Tig/Gas Rod | 36" | 20.04 |
| | | |

Mathey Dearman Pipefitters Cutting and Welding Tools

Magnacut XM



The Revolutionary New Cutting System. Introducing the world's most innovative motorized, permanently magnetic pipe and plate cutting machine with a Remote-controlled torch arm for pinpoint torch adjustments!

Moves around the pipe, across plate or vertically up a carbon steel wall with up to 32" (813mm) travel per minute! The machine will attach and center to any magnetic receptive surface using powerful permanent magnets located in the precision aligned wheels. The machine come standard with guide wheels that can be utilized along a Guide Strip when cutting large horizontal and vertical pipe or plate by using a 1-3/8" Angle Iron.


| art No. | Price /Each |
|---------|----------------|
| 03000 | \$5133.00: |
| | |

Short Saddle

Pa

08

Short Saddle is the only pipe cutting and beveling machine available that utilizes a one piece solid cast aluminum saddle. It provides square and accurate cuts every time. A wide range of attachments and accessories make it the most versatile and easiest to use pipe cutting and beveling machine on the mar-



Manual Operation

| Part No. | Vendor No. | Spacers to Fit Pipes | Size (in) | Price /Each |
|----------|---------------|----------------------------|-----------|----------------|
| 0803037 | 2SA | 6,8,10,12 | 6-12 | \$2078.17: |
| 0803038 | 3SA | 12,14,16,18,20 | 12-20 | 4428.43: |
| | | | | - |

Cutting Torches



Torches for all above Units

| Part No. | Description | Price /Each |
|----------|--------------------------|----------------|
| 0803051 | 9" Oxy/ Acetylene Torch | \$582.90: |
| 0803052 | 12" Oxy/ Acetylene Torch | 582.90: |
| 0803053 | 32 pitch 12" torch rack | 59.81: |
| 0803110 | angled tip adapter | 241.43: |

Mini Fit Clamp

The Mathey Dearman Mini Fit (miniature version of the Mathey Dearman Chain Clamp) is designed around the same principal as its older brother: One clamp should be strong and



versatile for a wide range of applications. One Mini Fit (D230 and D230 SS) will align any two similar pipes 3/4"- 8" in diameter. Reforms up to Schedule 10. (aligns up to Schedule 40)

| | Vendor | | Price |
|----------|---------|-------------|-----------|
| Part No. | No. | Description | /Each |
| 0803062 | D230-SS | 1/4" to 4" | \$346.68: |
| 0803063 | D230 | 3/4" to 8" | 356.40: |
| | | | 11_11 |



PIPEFITTERS, CUTTING & WELDING TOOLS & WELDING RODS

Mathey Dearman Pipefitters Cutting and Welding Tools



EZ Fit Pipe Clamp

The Mathey Dearman EZ-Fit is a great clamp for aligning fittings to pipes. This handy device is both easy to use and costeffective. Stainless steel shoes and screws are available for

working with stainless pipes and joints.

| | Vendor | Fits Pipe | Price |
|----------|--------|--------------|-----------|
| Part No. | No. | Size Range | /Each |
| 0803075 | E-Z4 | 2.5" to 4.5" | \$229.72: |
| 0803076 | E-Z8 | 5" to 8" | 376.63: |
| 0803077 | E-Z12 | 9" to 12" | 595.08: |

Two Hole Leveler

The Two Hole Leveler is always a good tool to have. It can be used to level flanges with bolt holes from 3/8" to 1-1/4" (16mm up to 32mm). With this design you avoid the chance of misplacing loose parts, and you will have no need to use adjusting tools. The Two Hole Leveler has two level indicators, one for

| and one for vertical. | 0. | <u></u> | 1 |
|-----------------------|--------|---------------|----------|
| | Vendor | Fits Pipe | Price |
| Part No. | No. | Size Range | /Each |
| 0803082 | D252 | 2-1/2" to 12" | \$135.94 |

Welder's Gauge

It's just a simple tool for measuring welding gaps and "Hi-Lo". Fits in your front pocket. Has English markings.

| | Vendor | Price |
|----------|--------|---------|
| Part No. | No. | /Each |
| 0803086 | D253E | \$25.01 |

Pit-Depth Gauge

Accessory gauge mounts on the QC welder's gauge, measures pit depth, weld height and Hi-Lo. QC gauge sold separately.

| | Vendor Pric | |
|----------|-------------|--------|
| Part No. | No. | /Each |
| 0803087 | D254 | \$7.61 |

Spacing Wedges

Mathey Dearman spacing Wedges work in conjunction with our Cage Clamps and chain clamps to optimize any fit-up job. use the wedges to spread pipe ends to the precise weld gap. Two available size have a maximum thickness of 1/4" (6.4mm) which tapers to a knife edge. Made of spring steel - hardened to 40-42 Rc.

| | Vendor | | Price |
|----------|--------|--------------------|---------|
| Part No. | No. | Size | /Each |
| 0803096 | D271 | 8" x 1.5" x .25" | \$23.65 |
| 0803097 | D272 | 3.5" x 1.5" x .25" | 20.89 |

Pipefitter's Square

Marked with information to make or measure arcs, angles, tangents, saddles, miters, diagonal joints, and Y joints. Use it to determine pipe center line, both holes for flanges, and pipe circumference.

| | Vendor | Price |
|----------|--------|---------|
| Part No. | No. | /Each |
| 0803100 | D248 | \$89.18 |
| | | |

Protractor and Square Set

Mathey Dearman's Pipefitter's Protractor and Square Set includes two straight edge blades, one frame square, and one Innovative Square Holder. Simply separating tools will give the sheetmetalist, welder, carpenter or machinist multiple uses. It can be used to check or layout angles and check squareness of one surface to another.

| | Vendor | | Price |
|---------|---------|------------|----------|
| Part No | . No. | Descriptio | n /Each |
| 080310 | 1 D239S | Small | \$232.73 |
| 080310 | 2 D239L | Large | 380.83 |

Flups

Flange Line Up Pins help set precise alignment for flange welding. Flange alignment pins set precise alignment for flange welding for carbon and stainless steel flanges. One Flup slows the flange pin to quickly release by pushing on the thumb-lock pin and the other Flup is unscrewed by a 1-3/4 turn and slide release.

| | Vendor | | Price |
|----------|-------------|-------------------|---------|
| Part No. | No. | Description | /Each |
| 0803103 | 05-0100-000 | Side-Lock Locking | \$45.68 |
| 0803104 | 05-0100-010 | Thread Locking | 90.75 |

Mild Steel Welding Rods



Mild Steel SureWeld 10P-Plus -E6010



10P-Plus has been developed for the pipe welding industry but has a more consistent burn-off and a more forgiving arc burn. This provides a better bead profile and sidewall fusion with lower spatter. It will maintain the proper keyhole in an open root and will produce X-ray quality joints in the flat, horizontal, overhead, vertical-up, and vertical-down procedures. Recommended for welding API grades A25, A, B and X42 pipe and general structural, ship, barge, and storage tank fabrication. Grey Coating.

| Part No. | Diameter | Container | Pkg. Qty. | UOM | UOM /Lb |
|----------|----------|-----------|-----------|-----|------------|
| 0805604 | 3/32 | HSC | 50 | Lb | <u>^</u> |
| | 0.01 | | | | |
| 0805605 | 1/8 | HSC | 50 | Lb | |
| 0805606 | 5/32 | HSC | 50 | Lb | |
| 0805607 | 3/16 | HSC | 50 | Lb | |

SureWeld 10P - E6010

This new red-coated Sureweld 10P is an all-position cellulosic electrode developed for the pipe welding industry in order to improve ductility in the weld deposit while maintaining the standard welding characteristics needed for a pipe welding electrode. Sureweld 10P produces a steady, deep penetrating arc and maintains the proper keyhole in an open root. This electrode will produce X-ray quality joints in flat, horizontal, overhead, vertical-up, and verticaldown procedures. Recommended for welding API grades A25, A, B, and X42 pipe and general structural, ship, barge, and storage tank fabrication. It may also be used for welding root passes in higher grade pipe in some circumstances. LIOM

| | | | | | UOW |
|----------|----------|-----------|-----------|-----|-----|
| Part No. | Diameter | Container | Pkg. Qty. | UOM | /Lb |
| 0804000 | 3/32 | Box | 5 | Lb | ^ |
| 0804007 | 3/32 | Box | 10 | Lb | |
| 0804002 | 3/32 | Box | 50 | Lb | |
| 0804006 | 3/32 | HSC | 50 | Lb | |
| 0804010 | 1/8 | Box | 5 | Lb | |
| 0804008 | 1/8 | Box | 10 | Lb | |
| 0804012 | 1/8 | Box | 50 | Lb | |
| 0804013 | 1/8 | HSC | 50 | Lb | |
| 0804020 | 5/32 | Box | 5 | Lb | |
| 0804009 | 5/32 | Box | 10 | Lb | |
| 0804022 | 5/32 | Box | 50 | Lb | |
| 0804023 | 5/32 | HSC | 50 | Lb | |
| | | | | | |

HSC= hermetically sealed container

Sureweld SW-14 - E6011

Sureweld SW-14 is an all-position cellulosic electrode. It produces an easily controlled forceful arc with deep penetration and a high quality weld metal which will pass specification requirements for radiography. It is used primarily for welding mild steels. Typical applications include welding of bridges, buildings, piping, shipbuilding, pressure vessels, and tanks. It is especially suited for welding where poor groove fit up and rusty or oily steel is present. Runs on Ac or DC+.

| Part No. | Diameter | Pkg. Qty. | UOM | UOM /Lb |
|----------|----------|-----------|-----|------------|
| 0804040 | 3/32 | 5 | Lb | ^ |
| 0804041 | 3/32 | 10 | Lb | |
| 0804043 | 3/32 | 50 | Lb | |
| 0804050 | 1/8 | 5 | Lb | |
| 0804051 | 1/8 | 10 | Lb | |
| 0804053 | 1/8 | 50 | Lb | |
| 0804060 | 5/32 | 10 | Lb | |
| 0804062 | 5/32 | 50 | Lb | |

Sureweld SW-15 - E6013

Sureweld SW-15 is a versatile electrode with a wide range of applications for light gauge and heavy plate steel. High heat and speeds can be used without undercut. Slag is easy to clean and on heavy plates is often self-cleaning. Its applications include metal fixtures, road equipment, farm machinery, building structures, storage tanks, and other iron work. Recommended current is AC, DC+ and DC-.

.....

| Part No. | Diameter | Pkg. Qty. | UOM | UOM /Lb |
|----------|----------|-----------|-----|------------|
| 0804090 | 1/16 | 10 | Lb | ^ |
| 0804100 | 3/32 | 5 | Lb | |
| 0804101 | 3/32 | 10 | Lb | |
| 0804104 | 3/32 | 50 | Lb | |
| 0804110 | 1/8 | 5 | Lb | |
| 0804111 | 1/8 | 10 | Lb | |
| 0804113 | 1/8 | 50 | Lb | |
| 0804120 | 5/32 | 10 | Lb | |
| 0804122 | 5/32 | 50 | Lb | |
| 0804131 | 3/16 | 50 | Lb | |

6022

AWS 6022 is a special electrode designed for welding roof decking to beams with burn-through spot welds or similar applications. Not an ESAB™ product.

| Part No. | Diameter | Pkg. Qty. | UOM | UOM /Lb |
|----------|----------|-----------|------|------------|
| Part NO. | Diameter | PKg. Qty. | UOIW | /LD |
| 0804133 | 1/8 | 50 | Lb | ^ |

Sureweld SW-15 IP - E7014

7014 is an all-purpose electrode used when the welding efficiency of 6013 is not acceptable. Applications are similar to 6013 and 6011. It has a higher deposition efficiency due to an iron powder coating. Slag is easily removed. Recommended current is AC, DC+ and DC-

| Part No. | Diameter | Pkg. Qty. | UOM | UOM /Lb |
|----------|----------|-----------|-----|------------|
| 0804140 | 3/32 | 5 | Lb | ^ |
| 0804141 | 3/32 | 10 | Lb | |
| 0804143 | 3/32 | 50 | Lb | |
| 0804145 | 1/8 | 5 | Lb | |
| 0804146 | 1/8 | 10 | Lb | |
| 0804148 | 1/8 | 50 | Lb | |
| 0804150 | 5/32 | 5 | Lb | |
| 0804151 | 5/32 | 10 | Lb | |
| 0804153 | 5/32 | 50 | Lb | |

Welding Rods, MIG Welding Wire

Mild Steel Welding Rods Cont.

Atom Arc - 7018

Atom Arc 7018 is an iron powder, low hydrogen, moisture resistant electrode. The wider operating ranges and smooth weld metal transfer minimizes post weld clean up. This premium quality electrode meets a multitude of codes and welding specifications. The most common electrode used in fabrication and construction. Weld deposits are of X-ray quality and slag removal is fairly easy. Recommended current is AC or DC+

| | | | | | UOM |
|----------|----------|-----------|-----------|-----|-----|
| Part No. | Diameter | Container | Pkg. Qty. | UOM | /Lb |
| 0804160 | 3/32" | Box | 5 | Lb | ^ |
| 0804161 | 3/32" | Box | 10 | Lb | |
| 0805635 | 3/32" | HSC | 10/60 | Lb | |
| 0804163 | 3/32" | Box | 50 | Lb | |
| 0804164 | 3/32" | HSC | 50 | Lb | |
| 0804170 | 1/8" | Box | 5 | Lb | |
| 0804171 | 1/8" | Box | 10 | Lb | |
| 0805636 | 1/8" | HSC | 10/60 | Lb | |
| 0804173 | 1/8" | Box | 50 | Lb | |
| 0804174 | 1/8" | HSC | 50 | Lb | |
| 0804180 | 5/32" | Box | 10 | Lb | |
| 0805637 | 5/32" | HSC | 10/60 | Lb | |
| 0804182 | 5/32" | Box | 50 | Lb | |
| 0804183 | 5/32" | HSC | 50 | Lb | |
| 0804191 | 3/16" | HSC | 50 | Lb | |
| 0804192 | 1/4" | HSC | 50 | Lb | |

HSC = Hermetically Sealed Can Atom Arc - 7018 AC

7018 AC is a low hydrogen electrode designed to operate with less spatter on AC current welding machines than 7018 would. Used where only AC welding current is available. Recommended current is AC, can be used on DC+ also.

| Part No. | Diameter | Container | Pkg. Qty. | UOM | /Lb |
|----------|----------|-----------|-----------|-----|-----|
| 0804220 | 3/32" | Box | 10 | Lb | ^ |
| 0804222 | 3/32" | HSC | 50 | Lb | |
| 0804230 | 1/8" | Box | 10 | Lb | |
| 0804232 | 1/8" | HSC | 50 | Lb | |
| 0804240 | 5/32" | Box | 10 | Lb | |
| 0804242 | 5/32" | HSC | 50 | Lb | |

Sureweld 7024

Sureweld 7024 is an iron powder electrode designed for greater deposition efficiency in downhand and horizontal fillet welds. Easy slag removal and a nice weld bead appearance.

Recommended current is AC, DC+ and DC-.

| | Part No. | Diameter | Pkg. Qty. | UOM | /Lb |
|---|----------|----------|-----------|-----|-----|
| ľ | 0804261 | 1/8" | 50 | Lb | ^ |
| ľ | 0804265 | 5/32" | 50 | Lb | |
| ľ | 0804269 | 3/16" | 50 | Lb | |
| ľ | 0804267 | 1/4" | 50 | Lb | |

Cast Iron Welding Rods



Cast Iron

| Part No. | Diameter | Pkg. Qty. | UOM | /Lb |
|------------|-----------------|-----------|-----|-----|
| Low Nickel | Cast Iron Rod | I | | |
| 0804400 | 3/32" | 5 | Lb | ^ |
| 0804404 | 1/8" | 5 | Lb | |
| 0804408 | 5/32" | 5 | Lb | |
| High Nicke | I Cast Iron Roo | 4 | | |
| 0804410 | 3/32" | 5 | Lb | ^ |
| 0804414 | 1/8" | 5 | Lb | |
| 0804418 | 5/32" | 5 | Lb | |
| | | | | |

Stainless Steel Welding Rods

Stainless Steel Rod 308L-17

308L-AC/DC, AWS E308L-17

Approved by the Canadian Welding Bureau Has a heavy coating, produce a concave bead with minimum ripple and the slag is virtually self-cleaning. For welding types 304, 304L, 308 and 308L when bead appearance is important. The excellent wetting action and very fine ripple minimize crevice corrosion and grinding time. The low carbon content helps to prevent carbide precipitation.

| Part No. | Diameter | Pkg. Qty. | UOM | /Lb |
|----------|----------|-----------|-----|-----|
| 0804554 | 1/16" | 6 | Lb | ^ |
| 0804550 | 3/32" | 8 | Lb | |
| 0804551 | 1/8" | 10 | Lb | |
| 0804552 | 5/32" | 10 | Lb | |

309L-17

309L-AC/DC, AWS E309L-17

Approved by the Canadian Welding Bureau Has a heavy coating and produces a concave bead with minimal ripple. The slag is virtually self-cleaning. For welding carbon steel to stainless steel for service below 600°F and for the first layer when cladding.

| Part No. | Diameter | Pkg. Qty. | UOM | UOM /Lb |
|----------|----------|-----------|-----|------------|
| 0804560 | 3/32" | 8 | Lb | ^ |
| 0804561 | 1/8" | 10 | Lb | |

316L-17

316L AC/DC. AWS E316L-17

Approved by the Canadian Welding Bureau Has a heavy coating and produces a concave bead with minimal ripple. The slag is virtually self-cleaning. Molybdenum increases the resistance to pitting corrosion caused by corrosive media such as sulfuric and sulfurous acids, sulphites, chlorides and cellulose solutions. For welding 316 and 316L stainless when bead appearance is important.

| Part No. | Diameter | Pkg. Qty. | UOM | UOM /Lb |
|----------|----------|-----------|-----|------------|
| 0804580 | 3/32" | 8 | Lb | ^20.20 |
| 0804581 | 1/8" | 10 | Lb | 19.29 |
| 0804582 | 5/32" | 10 | Lb | 19.05 |

Arc Gouging Torches & Rods BLACKSTONE

Arc Gouging Torches

All torches come with a Torch Head, 7' Cable/Hose assembly, and connector fitting. Designed to be used up to maximum current noted.

| | | UOM |
|----------|-----------|-------|
| Part No. | Amp. max. | /Each |
| 0805406 | 450 | ^ |
| 0805407 | 1000 | |
| 0805408 | 1200 | |

DC Arc Gouging Rods

Round - Pointed - Copper Coated

| | | | | UOM |
|----------|----------|-----------|------|-------|
| Part No. | Diameter | Pkg. Qty. | UOM | /Each |
| 0805351 | 1/8" | 100 | Each | ^ |
| 0805355 | 5/32" | 50 | Each | |
| 0805352 | 3/16" | 50 | Each | |
| 0805354 | 1/4" | 50 | Each | |
| 0805350 | 5/16" | 50 | Each | |
| 0805356 | 3/8" | 50 | Each | |
| 0805358 | 1/2" | 50 | Each | |

Flat - Copper Coated

| Part No. | Description | Pkg. Qty. | UOM | UOM /Each |
|----------|-------------------|-----------|------|--------------|
| 0805379 | 3/8" x5/32" x 12" | 100 | Each | ^ |
| 0805380 | 5/8" x3/16" x 12" | 100 | Each | |



Mild Steel

| Part No. | Wire Dia. | Spool Dia. | Lbs./Spool | UOM /Lb |
|-----------|------------|---------------|------------|------------|
| ER70S-3 - | ESAB | | | |
| 0804642 | .035" | 12" | 33 | ^ |
| 0804643 | .045" | 12" | 33 | |
| 0804365 | .035" | 12" | 44 | |
| 0804366 | .045" | 12" | 44 | |
| ER70S-6-E | Blackstone | | | |
| 0804700 | .023" | 4" | 2 | ^ |
| 0804701 | .030" | 4" | 2 | |
| 0804702 | .035" | 4" | 2 | |
| 0804703 | .045" | 4" | 2 | |
| 0804710 | .023" | 8" | 11 | |
| 0804711 | .030" | 8" | 11 | |
| 0804712 | .035" | 8" | 11 | |
| 0804713 | .045" | 8" | 11 | |
| 0804720 | .023" | 12" | 33 | |
| 0804721 | .030" | 12" | 33 | |
| 0804722 | .035" | 12" | 33 | |
| 0804723 | .045" | 12" | 33 | |
| 0804731 | .035" | 12" | 44 | |
| 0804732 | .045" | 12" | 44 | |
| ER70S-6-E | SAB | | | |
| 0804367 | .030" | 12" | 33 | ^ |
| 0804762 | .035" | 12" | 33 | |
| 0804763 | .045" | 12" | 33 | |
| 0804771 | .035" | 12" | 44 | |
| 0804772 | .045" | 12" | 44 | |
| ER80S-D2- | | | | |
| 0804793 | .035" | 12" | 33 | ^ |
| 0804794 | .045" | 12" | 33 | _ |
| | | | | |

Stainless Mig Wire

| Part No. | Wire Dia. | Spool Dia. | Lbs./Spool | UOM /Lb |
|----------|-----------|---------------|------------|------------|
| ER308LSi | | | | |
| 0805072 | .030" | 8" | 10 | ^ |
| 0805073 | .035" | 8" | 10 | |
| 0805078 | .030" | 12" | 33 | |
| 0805057 | .035" | 12" | 33 | |
| 0805058 | .045" | 12" | 33 | |
| 0805062 | 1/16" | 12" | 33 | |
| ER309L | | | | |
| 0805059 | .035" | 12" | 33 | ^ |
| 0805060 | .045" | 12" | 33 | |
| ER316LSi | | | | |
| 0805064 | .035" | 12" | 33 | ^ |
| 0805065 | .045" | 12" | 33 | |
| 0805066 | 1/16" | 12" | 33 | |
| | | | | |

Aluminum Welding Wire

| | | Spool | | UOM |
|------------------------|-----------|-------|------------|-----|
| Part No. 5356 Grade | Wire Dia. | Dia. | Lbs./Spool | /Lb |
| 0804960 | .030" | 4" | 1 | ^ |
| 0804961 | .035" | 4" | 1 | |
| 0804962 | 3/64" | 4" | 1 | |
| 0804963 | 1/16" | 4" | 1 | |
| 0805000 | .030" | 12" | 16 | |
| 0805001 | .035" | 12" | 16 | |
| 0805002 | 3/64" | 12" | 16 | |
| 0805003 | 1/16" | 12" | 16 | |
| 4043 Grade |) | | | |
| 0804950 | .030" | 4" | 1 | ^ |
| 0804951 | .035" | 4" | 1 | |
| 0804952 | 3/64" | 4" | 1 | |
| 0804953 | 1/16" | 4" | 1 | |
| 0804990 | .030" | 12" | 16 | |
| 0804991 | .035" | 12" | 16 | |
| 0804992 | 3/64" | 12" | 16 | |
| 0804993 | 1/16" | 12" | 16 | |

Silicon Bronze Mig Wire (ERCuSi-A)

| | | Spool | | UOM |
|----------|-----------|-------|------------|---------|
| Part No. | Wire Dia. | Dia. | Lbs./Spool | /Lb |
| 0805070 | .035" | 12" | 25 | ^ |
| | | | | 11 - 13 |

The : symbol after a price denotes that it is a Direct Ship Product (DSP) and shipping, availability & lead times may vary.

Welding Wire, Tig & Gas Filler Rods & Soldering Equip.

Flux Cored Welding Wire



Filler Metals

E71T-1 Premium E4801T-9

E71T-1 Premium is a carbon steel electrode for fluxcored arc welding with an external shielding gas, intended to weld carbon and low alloy steels requiring a tensile strength of at least 70,000 psi. This product is formulated to reduce fume generation rate from 40-60 percent, when compared to conventional E71T-1 electrodes. Along with less fume, there is an accompanying reduction in spatter emissions. E71T-1 Premium can be shielded with carbon dioxide or a mixture of 75% argon and 25% carbon dioxide. Welder appeal is at the top of the scale with this product. It is a select choice for applications where fume and spatter must be minimized, such as fabrications with enclosures, or where painting is performed after welding. Meets AWS E71T-1 (E4801T-9)

| Part No. 12" Spool | Diameter | Pkg. Qty. | UOM | UOM /Lb |
|-----------------------|----------|-----------|-----|------------|
| 0804844 | .035" | 33 Lb | Lb | ^ |
| 0804852 | .045" | 33 Lb | Lb | |
| 0804860 | 1/16" | 33 Lb | Lb | |
| 14" Coils | | | | |
| 0804856 | .045" | 60 Lb | Lb | ^ |
| 0804864 | 1/16" | 60 Lb | Lb | |

E71T-1 General Purpose (E4801T-9)

E71T-1 General Purpose is a carbon steel electrode for flux-cored arc welding with an external shielding gas. The Shielding gas can be either 100 % carbon dioxide or a mixture of 75 % argon and 25% carbon dioxide. This product is a superb choice for those applications requiring a general purpose E71T-1fillerwire. Arc transfer is smooth, spatter is low. Welder appeal is a strong suit. Meets AWS E71T-1. (E4801T-9)

| Part No. 12" Spools | Diameter | Pkg. Qty. | UOM | UOM /Lb |
|------------------------|----------|-----------|-----|------------|
| 0804804 | .035" | 33 Lb | Lb | ^ |
| 0804812 | .045" | 33 Lb | Lb | |
| 14" Coils | | | | |
| 0804816 | .045" | 60 Lb | Lb | ^ |
| 0804824 | 1/16" | 60 Lb | Lb | |

E71T-GS, GasLess Flux Cored E4801T-GS-CH

E71T-GS GasLess is a carbon steel electrode for flux cored arc welding **without external gas shielding**. This electrode is designed to be welded on DCEN (straight polarity), making it an excellent choice for thin gauge steel welding, particularly galvanized steel. It can also be used to weld some aluminized steel, and is versatile enough to join common, uncoated sheet steel, as thin as 22 gauge. E71T-GS GasLess has tremendous welder appeal and is perfect for the 110 volt power sources which have become so popular. Meets AWS E71T-GS. (E4801T-GS)

| Part No. | Diameter | Pkg. Qty. | UOM | UOM /Lb |
|------------|----------|-----------|-----|------------|
| 4" Spools | | | | |
| 0804920 | .030" | 2 Lb | Lb | ^ |
| 0804924 | .035" | 2 Lb | Lb | |
| 8" Spools | | | | |
| 0804922 | .030" | | Lb | ^ |
| 0804926 | .035" | | Lb | |
| 0804930 | .045" | 10 Lb | Lb | |
| 12" Spools | | | | |
| 0804928 | .035" | 33 Lb | Lb | ^ |
| 0804932 | .045" | 33 Lb | Lb | |
| 0804934 | 1/16" | 33 Lb | Lb | |

11–14

Welding

E71T-11

Gasless flux-no gas shield required

| Part No. | Diameter | Pkg. Qty. | UOM | UOM /Lb |
|------------|----------|-----------|-----|------------|
| 8" Spools | | | | |
| 0804940 | 0.035" | 10 Lb | Lb | ^ |
| 0804941 | 0.045" | 10 Lb | Lb | |
| 12" Spools | | | | |
| 0804942 | .035" | 33 Lb | Lb | ^ |
| 0804943 | .045" | 33 Lb | Lb | |
| 0804944 | 1/16" | 33 Lb | Lb | |
| 0804945 | 5/64" | 33 Lb | Lb | |

E70T-1 E4802T-9

E70T-1 is a carbon steel electrode for flux cored welding with an external shielding gas. It is intended for single and multiple-pass welding of carbon, and certain low alloy steels in the flat and horizontal positions. An ideal choice for welding steels such as A36, A285, A515 and A516. This electrode is designed for use with 100% carbon dioxide. Meets AWS E70T-1.

| | | | UOM |
|----------|-------------------------|---|--|
| Diameter | Pkg. Qty. | UOM | /Lb |
| | | | |
| 1/16" | 33 Lb | Lb | ^ |
| | | | |
| 1/16" | 60 Lb | Lb | ^ |
| 5/64" | 60 Lb | Lb | |
| 3/32" | 60 Lb | Lb | |
| | 1/16" 1/16" 5/64" | 1/16" 33 Lb 1/16" 60 Lb 5/64" 60 Lb | 1/16" 33 Lb Lb 1/16" 60 Lb Lb 5/64" 60 Lb Lb |

Metal Cored Welding Wire E70C-6M



AWS E70C-6M Metal Cored Wire

E70C-6M is a composite, metal cored electrode for gas shielded arc welding, with higher manganese and silicon levels. This electrode excels in applications with more demanding requirements, such as pipe welding, structural welds, and weldments where heavy oxides or other contaminant's are present. Fastenal's E70C-6M is designed for use with argon/carbon dioxide gas mixtures, with a minimum of 75 percent argon.

| Part No. | Diameter | Pkg. Qty. | UOM | UOM /Lb |
|------------|----------|-----------|-----|------------|
| 12" Spools | | | | |
| 0805074 | .045" | 33 Lb | Lb | ^ |
| 0805076 | 1/16" | 33 Lb | Lb | |
| 14" Coils | | | | |
| 0805075 | .045" | 60 Lb | Lb | ^ |
| 0805079 | .052" | 60 Lb | Lb | |
| 0805077 | 1/16" | 60 Lb | Lb | |

Tig and Gas Filler Rods



Stainless Steel Tig Filler Rods 36" Cut Lengths - In Pounds Per Pkg.

| Part No. | Diameter | Pkg. Qty. | UOM /Lb |
|----------|----------|-----------|------------|
| ER308L | | | |
| 0805106 | 1/16" | 10 | ^ |
| 0805116 | 3/32" | 10 | |
| 0805126 | 1/8" | 10 | |
| ER309L | | | |
| 0805131 | 1/16" | 10 | ^ |
| 0805133 | 3/32" | 10 | |
| 0805135 | 1/8" | 10 | |
| ER316L | | | |
| 0805141 | 1/16" | 10 | ^ |
| 0805143 | 3/32" | 10 | |
| 0805145 | 1/8" | 10 | |

Aluminum Tig Filler Rods 36" Cut Lengths - In Pounds Per Pkg.

| Part No. | Diameter | Pkg. Qty. | UOM /Lb |
|----------|----------|-----------|------------|
| ER4043 | | | |
| 0805164 | 1/16" | 10 | ^ |
| 0805174 | 3/32" | 10 | |
| 0805184 | 1/8" | 10 | |
| ER5356 | | | |
| 0805194 | 1/16" | 10 | ^ |
| 0805204 | 3/32" | 10 | |
| 0805214 | 1/8" | 10 | |

Mild Steel Tig and Gas Welding Rod

36" Cut Lengths - In Pounds Per Pkg.

| | | | UOM |
|------------|----------|-----------|-----|
| Part No. | Diameter | Pkg. Qty. | /Lb |
| R45-Copper | Coated | | |
| 0805234 | 1/16" | 10 | ^ |
| 0805244 | 3/32" | 10 | |
| 0805254 | 1/8" | 10 | |
| 0805256 | 3/16" | 50 | |
| 0805257 | 1/4" | 50 | |
| R60-Bare | | | |
| 0805264 | 1/16" | 10 | ^ |
| 0805274 | 3/32" | 10 | |
| 0805284 | 1/8" | 10 | |
| E70S-2 | | | |
| 0805285 | 1/16" | 10 | ^ |
| 0805286 | 3/32" | 10 | |
| 0805287 | 1/8" | 10 | |
| E70S-3 | | | |
| 0805288 | 1/16" | 10 | ^ |
| 0805289 | 3/32" | 10 | |
| 0805290 | 1/8" | 10 | |
| | | | |

Bronze Gas Filler Rods

36" Cut Length - In Pounds Per Pkg.

| Part No. | Diameter | Pkg. Qty. | UOM /Lb |
|-------------|------------------|-----------|------------|
| | Flux-Coated Bror | | 760 |
| 0805312 | 3/32" | 10 | ^ |
| 0805316 | 1/8" | 10 | |
| 0805326 | 3/16" | 10 | |
| RBCuZn-C, I | Bare Bronze | | |
| 0805292 | 1/16" | 10 | ^ |
| 0805296 | 3/32" | 10 | |
| 0805300 | 1/8" | 10 | |
| 0805304 | 3/16" | 10 | |
| ERCuSi-A, S | ilicon Bronze | | |
| 0805317 | 1/16" | 10 | ^ |
| 0805318 | 3/32" | 10 | |
| 0805319 | 1/8" | 10 | |

Soldering Equipment

Weller Soldering Equipment

D550PK Professional Soldering Gun Kit • 7 piece heavy duty kit with D550 soldering gun

- Includes: 1 soldering tip; 1 sealing tip; 1 cutting tip; coil of lead free rosin core solder; hex wrench
- Sturdy plastic carrying case
- UL Listed
 260/200 Watts



| Part No. | Vendor No. | Price /Ea. |
|----------|---------------|---------------|
| 0817700 | D550PK | \$69.06 |

fastenal.com

Soldering Equip., Lead-Free Solders

Soldering Equipment Cont. Weight Soldering Equipment Cont. Weight Soldering Equipment Cont. Packer Soldering Sold

| 1 | | Vendor | Price |
|---|----------|--------|---------|
| | Part No. | No. | /Each |
| | 0817706 | P1KC | \$61.80 |

Marksman® Soldering Irons

- Fine quality consumer ironReplaceable nickel plated cop-
- Per tipsHeat and impact
- resistant plastic handle

| • l | JL | listed |
|-----|----|--------|

| | u | | |
|----------|---------------------------------|---------------|----------------|
| Part No. | Description | Vendor No. | Price /Each |
| 0817707 | Iron, 12W, 120V, MT70 Tip | SP12 | \$16.94 |
| 0817708 | Iron, Lighted, 25W, 120V | SP23L | 15.74 |
| 0817709 | Iron, Lighted, 40W, 120V | SP40L | 21.04 |
| 0817710 | Stain Glass Sldr Iron, Lighted, | SP80L | 33.85 |
| | 80W, 120V | | |
| 0817711 | Iron, 120W, 120V, MTG30 Tip | SP120 | 59.42 |

WLC100 Soldering Station

- On/Off switch with indicator light
- Variable power control produces 5 to 40 watts
- Quality light weight pencil iron
- Cushioned foam grip with replaceable heating element
- Natural sponge tip cleaning pad
 UL listed



| | venuor | Price |
|----------|--------|---------|
| Part No. | No. | /Each |
| 0817712 | WLC100 | \$62.09 |
| | | |

WTCPT Controlled Output Soldering Station

- Utilizes unique closed loop method of controlling maximum tip temperature
- A ferromagnetic temperature sensor in the tip controls tip temperature
- Quick disconnect plug for soldering iron allows fast iron change
 ESD safe to protect sensitive components
- UL listed

| Vendor | Price |
|--------|----------|
| No. | /Each |
| WTCPT | \$168.10 |
| | No. |

PT Series Tips for TC201 Series Irons

- Tips are solid copper plated with iron all over, and nickel and chromium behind the working surface
- Designed to provide maximum heat transfer from the heater to the tip

| | Vendor | | | Price |
|----------|--------|------------------|------|--------|
| Part No. | No. | Description | Size | /Each |
| 0817714 | PTA8 | Screwdriver | .062 | \$6.72 |
| 0817715 | PTA7 | Screwdriver | .062 | 6.72 |
| 0817716 | PTK8 | Long Screwdriver | .046 | 6.72 |
| 0817717 | PTD8 | Screwdriver | .187 | 6.72 |
| 0817718 | PTO8 | Long Conical | .031 | 6.72 |
| 0817719 | PTP8 | Conical | .031 | 6.72 |

Weller[®] ColdHeat™ Soldering Iron

Using the patented ColdHeat™ system, the Weller Pro Cordless melts solder instantly and is

cool to the touch in just seconds. But unlike most other products using this new technology, the Weller Pro Cordless has the punch industrial professionals need to tin wire as large as 12 gauge or join wire from 18-25 gauge. With an average yield of 700 solder joints per pack of five AA alkaline batteries, it has what it takes to be an invaluable tool anywhere field soldering is required.

| | Vendor | | Price |
|----------|--------|--|---------|
| Part No. | No. | Description | /Each |
| 0800052 | CHT100 | Weller [®] Pro Soldering Tool | \$45.58 |
| 0800053 | CHT1 | Bevel Soldering Tip | 15.27 |
| 0800054 | CHT2 | Conical Soldering Tip | 15.27 |
| 0800055 | CHT3 | Chisel Soldering Tip | 15.27 |

LENOX Lead-Free Solders

Lenox[®] Sterling[®]

- Premium lead free solder
- NSF 61 certification
- Unit lot numbering ensures complete traceability
- Completely free of antimony or nickel, 100% environmentally safe
- · Best flowing lead-free available
- Lowest melting temperature: 410°F
- Highest tensile strength 7130 psi

| | Spool | UOM |
|----------|------------|--------|
| Part No. | Size | /Spool |
| 0803387 | 1# spool | |
| 0803469 | 5# spool | |
| 0803470 | 20# spool | |
| 0803471 | 1/2# spool | |
| 0803472 | 1/4# spool | |

Lenox[®] Silver

- Premium, high silver content lead free solder
 Wide pasty range allows for
- wide pasty range all more work time
- · Ideal for use on large diameter tube

| Part No. | Spool Size | UON /Spoo |
|----------|---------------|--------------|
| 0803473 | 1# spool | · · · · |
| 0803475 | 20# spool | |

Lenox[®] Lead Free

Low melting temperature 419°F
 High tensile strength 6950 psi
 ASTM-32, ANSINSF STD
 S1 entitied

| 61 certified | 1141 | |
|--------------|---------------|---------------|
| Part No. | Spool Size | UOM /Spool |
| 0803477 | 1# spool | |
| 0803478 | 5# spool | |
| 0803479 | 1/4# spool | |
| 0803480 | 1/2# spool | |

Lenox[®] Lead Free with silver


0803484

- Melts, flows and performs better than 95/5
- NSF 61 certified; unit lot numbering ensures complete traceability
- Melting temperature: 440°F
- Tensile strength: 6600 psi
 Spool UOM
 Part No. Size /Spool
 0803481 1# spool --- 0803482 5# spool ---- 0803483 1/2# spool ------

1/4# spool

Lenox[®] Lead Free 97/3


- Melts, flows and performs better than 95/5
- NSF 61 certified; unit lot numbering ensures complete traceability
 Melting temperature: 445°F



| Part No. | Spool Size | UOM /Spoo |
|----------|---------------|--------------|
| 0803388 | 1# spool | |
| 0803485 | 1/2# spool | |
| 0803486 | 1/4# spool | |

Lenox[®] Lead Free 95/5

Tin-antimony lead-free solder with narrow pasty range
Melting temperature: 455°F





| | Spool | UOM |
|----------|------------|--------|
| Part No. | Size | /Spool |
| 0803389 | 1# spool | |
| 0803487 | 1/2# spool | |
| 0803488 | 1/4# spool | |

Lenox[®] Lead Free HVAC Wire

- Alternative to silver brazing rods.
- Used for joining copper or brass to copper or brass, copper or brass to steel or stainless, steel or stainless to steel or stainless.
- Lower melting temperature than brazing rods.
- Melting temperature:430°F
- Pasty range: 430°F 535°F
- Tensile Strength- 15,000 psi.
- NSF61 certified; unit lot numbering ensures complete traceability.

946 Lead Free HVAC • 6% silver content

| LIOM | |
|------|--|

/Spool

964 Lead Free HVAC

| 4% silver content | |
|-------------------|--------|
| | UOM |
| B 1.11 | /Spool |
| Part No. | /3µ001 |

Spool

Size

1# spool

Lenox[®] Lead-Free Rosin Core

- Used for speaker wire, motors, appli-
 - Melting temperature: 445°F
- Diameter: .062"

Part No.

0803390

| - Aller |
|---------|
| UOM |

11 - 15

Welding

| Part No. | Spool Size | UOM /Spool |
|----------|---------------|---------------|
| 0803395 | 1# spool | |
| 0803489 | 1/2# spool | |
| 0803490 | 1/4# spool | |

Lenox[®] Lead-Free Acid Core

- Used for tin repairs, sheet metal, auto radiators, metal gutters and
- non-electrical repairs
 Melting temperature: 445°F
- Diameter: .062"


| | Spool | UOM |
|----------|------------|--------|
| Part No. | Size | /Spool |
| 0803398 | 1# spool | |
| 0803491 | 1/2# spool | |
| 0803492 | 1/4# spool | |
| | | |

The : symbol after a price denotes that it is a Direct Ship Product (DSP) and shipping, availability & lead times may vary.

EachLefiux45.58• Tin-antim15.27• Melting te15.27• Tensile st

Soldering Equip & Solders

Leaded Solders, Fluxes, Brazing Alloys & Abrasives



Lenox[®] Lead-Free Paste Flux NSF61 certified; unit lot numbering

- ensures complete traceability
- Petroleum based flux
- Critical for soldering
- · Check local plumbing codes for restrictions

| Part No. | Size | UOM /Each |
|----------|--------|--------------|
| 0803408 | 2 oz. | |
| 0803407 | 8 oz. | |
| 0803517 | 16 oz. | |

Lenox[®] Tinning Paste Flux

 Critical for soldering Petroleum based lead free flux with metals for pre-tinning copper

| | | and the second s |
|----------|---------|--|
| | | UOM |
| Part No. | Size | /Each |
| 0803516 | 1.7 oz. | |

Lenox[®] Stainless Steel Liquid Flux

- Formulated for soldering stainless steel and high-chrome alloys
- Added bi-fluoride element increases etching ability
- Excellent across a broad range of base metals, solders, and temperatures
- Exerts a strong scavenging action to remove oxide coatings and other impurities
- · Exhibits excellent capillary action

Part No. Size 0803409 4 07 Lenox[®] General Purpose

Liquid Flux

- Formulated for soldering Stainless Steel, Monel, High-Chrome, Alloys, Inconel, Nickel, Copper, Brass, Ferrous Alloys and many other metals
- · Excellent across a broad range of base metals, solders, and temperatures • Exerts a strong scavenging action to
- remove oxide coatings and other impurities · Exhibits excellent capillary action

| Part No. | Size | UOM /Each |
|----------|-------|--------------|
| 0803410 | 4 oz. | |

Lenox[®] Silver Brazing Flux

- · General purpose brazing fluid
- · Brazes copper, brass, nickel, carbon steel and precious metals

| | | UOM /Each |
|----------|-------|--------------|
| Part No. | Size | /Each |
| 0803518 | 4 oz. | |
| | | |

Brazing Alloys LENOX

Lenox[®] Brazing Rods - 0%

- 0% silver content, 7.25% phosphorus, balance copper · Very fluid, medium temperature brazing alloy
- erature 1310° 1500°E

| • weiting te | inperature. 1310 | - 1500 F | |
|--------------|------------------|-------------------|--------------|
| Part No. | Size | Number of Rods | UOM /Each |
| 0803404 | 1# tube | 28 | |
| 0803500 | 1/2# tube | 14 | |
| 0803501 | 1/4# tube | 7 | |

Lenox[®] Brazing Rods -5% Silver

- 5% silver content, 6% phosphorus, balance copper · Similar to 15% silphos with the ability to fill gaps and form fillets without adversely affecting strength Melting temperature: 1190° - 1500°F

| Part No. | Size | Number of Rods | UOM /Each |
|----------|-----------------|-------------------|--------------|
| 0803403 | 1# tube | 28 | |
| 0803502 | 1/2# tube | 14 | |
| 0803503 | 1/4# tube | 7 | |
| | Dura - ins an D | a da | |

Lenox[®] Brazing Rods -6% Silver

- 15% silver content, 5% phosphorus, balance copper · Similar to 5% silphos but with a lower liquids tem-
- perature for an even, more ductile joint Melting temperature: 1190° - 1500°F

| | | Number | UOM |
|----------|-----------|---------|-------|
| Part No. | Size | of Rods | /Each |
| 0800056 | 1# tube | 28 | |
| 0803504 | 1/2# tube | 14 | |
| 0803505 | 1/4# tube | 7 | |
| - | | | |

Lenox[®] Brazing Rods -15% Silver

- 15% silver content, 5% phosphorus, balance copper.
- Similar to 5% silphos but with a lower liquids temperature for an even, more ductile joint
- Melting temperature: 1190° 1500°F

| Part No. | Size | Number of Rods | UOM /Each |
|----------|-----------|-------------------|--------------|
| 0803401 | 1# tube | 28 | |
| 0803506 | 1/2# tube | 14 | |
| 0803402 | 1/4# tube | 7 | |

Lenox[®] Brazing Alloys

 Cadmium free silver brazing wire · Very high strength joints

UOM

/Each

| | ([| N | 1 | 1 | 1 |
|---|----|---|---|---|---|
| 1 | 11 | 1 | 1 | |) |
| 1 | 1 | 4 | D | Y | 1 |

| Part No. | | Size | UOM /Each |
|----------|-----|------------|--------------|
| 0803509 | 45% | 5 troy oz. | |
| 0803508 | 45% | 3 troy oz. | |
| 0803507 | 45% | 1 troy oz. | |
| 0803512 | 56% | 5 troy oz. | |
| 0803511 | 56% | 3 troy oz. | |
| 0803510 | 56% | 1 troy oz. | |

Lenox[®] Industrial Lead Free Babbit

· Grad "A" virgin metal for tinning, pot sweetening



- and any other specialized applications · Soft alloy used to line bearings for manufacturing
- and industrial use

| Part No. | | | UOM /Each |
|----------|-----------|--------------|--------------|
| 0803521 | #3 babbit | #5 sm ingot | |
| 0803522 | Grade 2 | #5 sm ingot | |
| 0803523 | Grade 2 | #23 lg ingot | |
| 0803524 | 4X Nickel | #5 sm ingot | |
| 0803525 | #1 Bar | Pure tin | |

Abrasive Cloth Mesh & Sand LENOX

Lonov[®] Moch Cloth

| Grain bonde Lasts longer Fully waterp | d on both sides than sand cloth roof gritty residue |), |
|---|--|----------------|
| Part No. | Description | Price /Each |
| 0803411 | 25 yd. Mesh Cloth | \$18.96 |
| 0803412 | 10 yd. Mesh Cloth | 6.46 |
| 0803413 | 2 yd. Mesh Cloth | 1.45 |

fastenal.com

11-16 Welding

0803515

8 oz.

16.07

Abrasives, Brushes, Acces., Mig & Plasma Consumables

| Abrasive | Cloth Mesh | |
|------------------------------------|--|--|
| & Sand (| Cont. | |
| LEN | | |
| | and Cloth | |
| | | |
| | efficient abrasive. | |
| Flexible cloth | | |
| | nt resin coating. | |
| Long lasting v | vith superior performance | |
| Davit Ma | Description | Price |
| Part No. 0803414 | 25 yd. Sand Cloth | /Each \$7.07 |
| 0803415 | 10 yd. Sand Cloth | 3.07 |
| 0803514 | 5 yd. Sand Cloth | 2.24 |
| 0803416 | 2 yd. Sand Cloth | 0.73 |
| | , | |
| | | |
| | | |
| Fitting B | rusnes | |
| | | |
| LEN | | |
| | remium Brushe | . |
| Leliox P | remum brushe | 3 |
| | | |
| | LENOX | All Common |
| | the second se | . 0803417 |
| LENOX | der al farmannet | |
| | Pn. 0803418 | |
| | | 1000 |
| | | on the second se |
| | De | . 0803419 |
| | 668 FIL | . 0603419 |
| LENOX. | and the second sec | |
| | Pn. 0803420 | |
| | 111.0000420 | |
| | LENOX S | TITLE . |
| | | 0000404 |
| | Pn. | . 0803421 |
| (Jacobie | -176 | |
| | | |
| Pn. | 0803422 Mr. C | C 484- |
| | Dn | 0803423 |
| | | . 0000420 |
| 222 | | |
| 1 1 1 1 1 | | |
| | 17 | |
| | | |
| | | |
| | | |
| Pn. 0803424 | | |
| | | Price |
| Part No. | Description | /Each |
| 0803417 | 1/2" Fitting Brush | \$1.77 |
| 0803418 | 3/4" Fitting Brush | 1.87 |

| Part No. | Description | /Each |
|----------|----------------------|--------|
| 0803417 | 1/2" Fitting Brush | \$1.77 |
| 0803418 | 3/4" Fitting Brush | 1.87 |
| 0803419 | 1" Fitting Brush | 2.33 |
| 0803420 | 1-1/4" Fitting Brush | 2.53 |
| 0803421 | 1-1/2" Fitting Brush | 2.80 |
| 0803422 | 2" Fitting Brush | 3.23 |
| 0803423 | 4-in-1 Fitting Brush | 8.27 |
| 0803424 | 4" Acid Brush | 1.40 |

Accessories

Lenox[®] Sterling[™] Cold Coat

 Non-toxic ColdCoat[™] slows the transfer of heat in metal, wood, plastics and most other surfaces during the soldering, brazing or welding process.
 Patented freeze-stable solution



resists separation even if subjected to freezing temperatures.

| | | Price |
|----------|---------------------------------|---------|
| Part No. | Description | /Each |
| 0803425 | 32 oz. Sterling Cold Coat Paste | \$25.39 |
| 0803426 | 32 oz. Sterling Cold Coat Spray | 16.86 |

| Eliminate tubing for | s burrs a | nd pre | | | Price |
|--|---|--|--|---|--|
| Part No. | | De | escription | | /Each |
| 0803520 | | | 10 pcs | 9 | \$25.39 |
| plete tra Comple | certifica aceability ately free ny or nick | tion, u , of kel | nit lot number ensu | | COM- Price /Each |
| | | | | | |
| ESA | o [®] Cor | mpa | tible Parts | and the second se | |
| | | size | | | e Price /Each |
| Tweco | D [®] Cor | Size | Type | Qty. | /Each |
| Tweco Part No. #1 MIG Gu 0806100 | Vendor No. Jn 11-23 | Size | Type 11-23 | Qty. 25 | /Each |
| Part No. #1 MIG Gu 0806100 | D [®] Cor (1997) Vendor No. Jn 11-23 11-30 | Size .023" .030" | Type 11-23 11-30 | Qty. 25 25 | /Each \$0.73 |
| Tweco Part No. #1 MIG Gu 0806100 0806101 0806102 | Vendor No. 11-23 11-30 11-35 | Size .023" .030" .035" | Type 11-23 11-30 11-35 | Qty. 25 25 25 | /Each \$0.73 0.68 0.63 |
| Part No. #1 MIG Gu 0806100 | D [®] Cor (1997) Vendor No. Jn 11-23 11-30 | Size .023" .030" | Type 11-23 11-30 11-35 Contact Tip Nozzle Self-Insulated, | Qty. 25 25 25 25 | /Each \$0.73 0.68 0.63 0.76 |
| Part No. #1 MIG Ga 0806100 0806101 0806102 0806103 0806103 | Vendor No. 11-23 11-30 11-35 11-45 21-37F | Size .023" .030" .035" .045 3/8" | Type 11-23 11-30 11-35 Contact Tip Nozzle Self-Insulated, Flush Tip Length | Qty. 25 25 25 25 5 | /Each \$0.73 0.68 0.63 0.76 9.43 |
| Part No. #1 MIG Gu 0806100 0806101 0806102 0806103 0806103 0806141 0806140 | Vendor No. 11-23 11-30 11-35 11-45 21-37F 21-50 | Size .023" .030" .035" .045 3/8" 1/2" | Type 11-23 11-30 11-35 Contact Tip Nozzle Self-Insulated, Flush Tip Length Nozzle Self-Insulated | Qty. 25 25 25 5 5 | /Each \$0.73 0.68 0.63 0.76 9.43 14.20 |
| Part No. #1 MIG Ga 0806100 0806101 0806102 0806103 0806103 | Vendor No. 11-23 11-30 11-35 11-45 21-37F | Size .023" .030" .035" .045 3/8" | Type 11-23 11-30 11-35 Contact Tip Nozzle Self-Insulated, Flush Tip Length Nozzle Self-Insulated Nozzle Self-Insulated | Qty. 25 25 25 5 5 | /Each \$0.73 0.68 0.63 0.76 9.43 14.20 |
| Part No. #1 MIG Gu 0806100 0806101 0806102 0806103 0806104 0806104 0806104 0806104 0806104 | Vendor No. Jn 11-23 11-30 11-35 11-45 21-37F 21-50F | Size .023" .030" .035" .045 .3/8" 1/2" 1/2" | Type Type 11-23 11-30 11-35 Contact Tip Nozzle Self-Insulated, Flush Tip Length Nozzle Self-Insulated Flush Tip Length | Qty. 25 25 25 5 5 5 | /Each \$0.73 0.68 0.63 0.76 9.43 14.20 7.43 |
| Part No. #1 MIG Get 0806100 0806101 0806102 0806103 0806141 0806140 0806142 0806170 | Vendor No. Jn 11-23 11-30 11-35 11-45 21-37F 21-50 21-50F 51 | Size .023" .030" .035" .045 3/8" 1/2" | Type 11-23 11-30 11-35 Contact Tip Nozzle Self-Insulated, Flush Tip Length Nozzle Self-Insulated Nozzle Self-Insulated | Qty. 25 25 25 5 5 | /Each \$0.73 0.68 0.63 0.76 9.43 14.20 7.43 |
| Part No. #1 MIG Gu 0806100 0806101 0806102 0806103 0806104 0806104 0806104 0806104 0806105 0806106 0806107 #2 MIG Gu | Vendor No. 11-23 11-30 11-35 11-45 21-37F 21-50F 21-50F 51 Jn | Size .023" .030" .045 3/8" 1/2" 1/2" N/A | Type 11-23 11-30 11-35 Contact Tip Nozzle Self-Insulated, Flush Tip Length Nozzle Self-Insulated Nozzle Self-Insulated Nozzle Self-Insulated Nozzle Self-Insulated Nozzle Self-Insulated Flush Tip Length Tip Adapter | Qty. 25 25 25 5 5 5 5 5 | /Each \$0.73 0.68 0.63 0.76 9.43 14.20 7.43 3.10 |
| Part No. #1 MIG Gu 0806101 0806103 0806101 0806103 0806104 0806103 0806104 0806105 0806106 0806170 #2 MIG Gu 0806170 #2 MIG Gu 0806170 | Vendor No. JI 11-23 11-30 11-35 11-45 21-37F 21-50 21-50F 51 JI 14-23 | Size .023" .030" .045 3/8" 1/2" 1/2" N/A .023" | Type 11-23 11-30 11-35 Contact Tip Nozzle Self-Insulated, Flush Tip Length Nozzle Self-Insulated Nozzle Self-Insulated Flush Tip Length Tip Adapter Contact Tip | Qty. 25 25 25 5 5 5 5 25 | /Each \$0.73 0.68 0.63 0.76 9.43 14.20 7.43 3.10 \$0.60 |
| Part No. #1 MIG Ge 0806100 0806101 0806102 0806103 0806104 0806104 0806105 0806106 0806110 0806170 #2 MIG Ge 0806110 0806111 | Vendor No. JI 11-30 11-35 11-45 21-37F 21-50 21-50F 51 JI 14-23 14-30 | Size .023" .030" .045 3/8" 1/2" 1/2" N/A .023" .030" | Type 11-23 11-30 11-35 Contact Tip Nozzle Self-Insulated, Flush Tip Length Nozzle Self-Insulated Nozzle Self-Insulated Nozzle Self-Insulated Nozzle Self-Insulated Nozzle Self-Insulated Flush Tip Length Tip Adapter Contact Tip 14-30 | Qty. 25 25 25 25 5 5 5 25 25 25 25 25 25 25 25 25 25 25 | /Each \$0.73 0.68 0.63 0.76 9.43 14.20 7.43 3.10 \$0.60 |
| Part No. #1 MIG Gu 0806100 0806101 0806102 0806103 0806141 0806140 0806142 0806170 #2 MIG Gu 0806111 0806110 0806111 0806112 | Vendor No. Jn 11-23 11-30 11-35 11-45 21-37F 21-50F 21-50F 51 Jn 14-23 14-30 14-35 | Size .023" .030" .035" .045 3/8" 1/2" 1/2" N/A .023" .030" .035" | Type Type 11-23 11-30 11-35 Contact Tip Nozzle Self-Insulated, Flush Tip Length Nozzle Self-Insulated Nozzle Self-Insulated Flush Tip Length Tip Adapter Contact Tip 14-30 14-35 | Qty. 25 25 25 25 5 5 5 25 25 25 25 25 25 25 25 25 25 25 25 25 25 25 25 | /Each \$0.73 0.68 0.63 0.76 9.43 14.20 7.43 3.10 \$0.60 0.65 0.65 |
| Part No. #1 MIG Gu 0806100 0806100 0806101 0806102 0806103 0806141 0806140 0806142 0806170 #2 MIG Gu 0806170 #2 MIG Gu 0806111 0806111 0806111 0806111 0806112 0806113 | Vendor No. 11-23 11-30 11-35 11-45 21-37F 21-50F 21-50F 51 14-23 14-23 14-30 14-35 14-45 | Size .023" .030" .045 3/8" 1/2" N/A .023" .045" .030" .035" | Type 11-23 11-30 11-35 Contact Tip Nozzle Self-Insulated Flush Tip Length Nozzle Self-Insulated Nozzle Self-Insulated Nozzle Self-Insulated Nozzle Self-Insulated Nozzle Self-Insulated Contact Tip 14-30 14-35 14-45 | Qty. 25 25 25 25 5 5 5 25 25 25 25 25 25 25 25 25 25 25 25 25 25 25 25 | /Each \$0.73 0.68 0.63 0.76 9.43 14.20 7.43 3.10 \$0.60 0.65 0.65 |
| Part No. #1 MIG Gu 0806100 0806101 0806102 0806103 0806104 0806104 0806105 0806106 0806107 #2 MIG Gu 0806110 0806110 0806110 0806110 0806111 0806112 0806113 0806114 | Vendor No. 11-23 11-30 11-35 11-45 21-37F 21-50F 21-50F 51 14-23 14-35 14-45 14-415 | Size .023" .030" .045 .3/8" 1/2" 1/2" N/A .023" .030" .045" 1/16" | Type Type 11-23 11-30 11-35 Contact Tip Nozzle Self-Insulated Flush Tip Length Nozzle Self-Insulated Rozzle Self-Insulated Flush Tip Length Tip Adapter Contact Tip 14-35 14-45 Contact Tip | Qty. 25 25 25 25 5 5 25 25 25 25 25 25 25 25 25 25 25 25 25 25 25 25 25 25 25 | /Each \$0.73 0.68 0.63 0.76 9.43 14.20 7.43 3.10 \$0.60 0.65 0.65 0.65 |
| Tweck Part No. #1 MG Gu 0806101 0806102 0806103 0806103 0806110 0806140 0806140 0806140 0806170 #2 MIG Gu 0806170 #2 MIG Gu 0806110 0806110 0806111 0806111 0806111 0806113 0806113 0806114 0806116 | Vendor No. JI 11-23 11-30 11-35 11-45 21-37F 21-50 21-50F 51 JI 14-23 14-30 14-35 14-415 14-415 14-415 | Size .023" .030" .045 .045 .045 .045 .045 1/2" 1/2" .045" 1/2" .030" .033" .045" 1/16" .023" | Type 11-23 11-30 11-35 Contact Tip Nozzle Self-Insulated, Flush Tip Length Nozzle Self-Insulated Nozzle Self-Insulated Rush Tip Length Tip Adapter Contact Tip 14-30 14-35 14-45 Contact Tip Contact Tip Contact Tip | Qty. 25 25 25 25 25 5 5 25 25 25 25 25 25 25 25 25 25 25 25 25 25 25 25 25 25 25 | /Each \$0.73 0.68 0.63 0.76 9.43 14.20 7.43 3.10 \$0.60 0.65 0.65 0.65 0.65 0.65 0.65 0.65 |
| Part No. #1 MIG GG 0806100 0806100 0806101 0806102 0806103 0806110 080612 0806142 0806110 0806110 0806110 0806111 0806112 0806113 0806114 0806116 0806116 0806116 0806116 | Vendor No. Jn 11-23 11-30 11-35 11-45 21-37F 21-50F 21-50F 51 Jn 14-23 14-30 14-35 14-45 14-16 14-176 14-176 14-176 | Size .023" .030" .045 .045 .045 .045 .1/2" 1/2" N/A .030" .030" .030" .033" .033" | Type Type 11-23 11-30 11-35 Contact Tip Nozzle Self-Insulated, Flush Tip Length Nozzle Self-Insulated Nozzle Self-Insulated Nozzle Self-Insulated Nozzle Self-Insulated Contact Tip 14-30 14-35 14-45 Contact Tip Contact Tip Contact Tip Tapered Contact Tip Tapered | Qty. 25 25 25 25 25 5 5 5 25 | /Each \$0.73 0.66 0.63 0.76 9.43 14.20 7.43 3.10 \$0.66 0.65 0.65 0.65 0.65 0.65 0.65 0.65 |
| Part No. #1 MIG Gu 0806100 0806100 0806101 0806102 0806103 0806141 0806140 0806142 0806170 #2 MIG Gu 0806110 0806111 0806111 0806111 0806111 0806113 0806117 0806113 0806117 0806113 | Vendor No. Jn 11-23 11-30 11-35 11-45 21-37F 21-50F 21-50F 21-50F 51 Jn 14-23 14-30 14-35 14-45 14-45 14-116 14T-30 14T-35 | 5 Size .023" .030" .045 3/8" 1/2" 1/2" 1/2" N/A .023" .045" .045" .045" .045" .045" .045" .033" | Type Type 11-23 11-30 11-35 Contact Tip Nozzle Self-Insulated, Flush Tip Length Nozzle Self-Insulated Nozzle Self-Insulated Flush Tip Length Tip Adapter Contact Tip 14-30 14-35 14-45 Contact Tip Tapered Contact Tip Tapered Contact Tip Tapered | Oty. 25 25 25 25 5 5 25 | /Each \$0.73 0.66 0.63 0.76 9.43 14.20 7.43 3.10 \$0.66 0.65 0.65 0.65 0.65 0.65 0.65 0.65 |
| Part No. #1 MIG Gu 0806100 0806101 0806102 0806103 0806104 0806104 0806104 0806104 0806105 0806106 0806107 #2 MIG Gu 0806170 #2 MIG Gu 0806110 0806111 0806113 0806113 0806114 0806115 0806116 0806117 0806118 0806119 | Vendor No. 11-23 11-30 11-35 11-45 21-37F 21-50F 21-50F 51 14-23 14-30 14-35 14-45 14-116 14T-23 14-735 14T-45 | Size .023" .030" .045 .3/8" 1/2" 1/2" N/A .023" .045" 1/16" .023" .045" 1/16" .023" .045" | Type Type 11-23 11-30 11-35 Contact Tip Nozzle Self-Insulated, Flush Tip Length Nozzle Self-Insulated Nozzle Self-Insulated Rozzle Self-Insulated Flush Tip Length Tip Adapter Contact Tip 14-35 14-45 Contact Tip Contact Tip Tapered Contact Tip Tapered Contact Tip Tapered Contact Tip Tapered | Oty. 25 25 25 25 5 5 5 25 | /Each \$0.73 0.68 0.63 0.76 9.43 14.20 7.43 3.10 \$0.66 0.65 0.665 0.665 0.67 0.68 1.01 |
| Part No. #1 MIG Gu 0806101 0806102 0806103 0806104 0806101 0806102 0806103 0806110 0806111 0806110 0806111 0806110 0806111 0806112 0806113 0806114 0806115 0806116 0806117 0806118 0806113 080613 | Vendor No. JI 11-23 11-30 11-35 11-45 21-30F 21-50F 21-50F 51 JI 14-23 14-35 14-45 14-16 14-735 14-45 14-16 141-23 14-735 | Size .023" .030" .045 3/8" 1/2" 1/2" N/A .023" .035" .045" 1/16" .023" .030" .035" .045" 1/16" .023" .030" .045" .0 | Type Type 11-23 11-30 11-35 Contact Tip Nozzle Self-Insulated, Flush Tip Length Nozzle Self-Insulated Flush Tip Length Nozzle Self-Insulated Flush Tip Length Tip Adapter Contact Tip 14-30 14-35 14-45 Contact Tip Contact Tip Tapered Contact Tip Tapered | Oty. 25 25 25 5 5 5 25 | /Each \$0.73 0.66 0.63 0.76 9.43 14.20 7.43 3.10 \$0.66 0.65 0.65 0.65 0.66 0.65 0.65 0.66 0.65 0.65 |
| Part No. #1 MIG Gu 0806100 0806101 0806101 0806101 0806101 0806103 0806104 0806105 0806106 08061070 #2 MIG Gu 0806110 0806112 0806113 0806114 0806115 0806116 0806117 0806118 0806118 0806119 0806146 | Vendor No. JI 11-23 11-30 11-35 11-45 21-30F 21-50F 21-50F 51 JI 14-23 14-30 14-35 14-416 14-73 14-35 14-416 14-73 14-735 14-145 14-735 14-7555 14-7555 14-7555 14-7555 14-75555 | Size .023" .030" .035" .045 3/8" 1/2" 1/2" N/A .023" .030" .035" .045" 1/2" .030" .035" .045" .045" .045" .045" .045" .045" .045" .045 | Type Type 11-23 11-30 11-35 Contact Tip Nozzle Self-Insulated, Flush Tip Length Nozzle Self-Insulated Nozzle Self-Insulated Nozzle Self-Insulated Flush Tip Length Tip Adapter Contact Tip 14-30 14-35 14-45 Contact Tip Tapered Contact Tip Tapered Nozzle Nozzle | Oty. 25 25 25 25 5 5 5 25 5 5 | /Each \$0.73 0.68 0.66 0.76 9.43 14.20 7.43 3.10 \$0.60 0.65 0.65 0.65 0.65 0.65 0.65 0.65 |
| Part No. #1 MIG Gu 0806101 0806102 0806103 0806104 0806107 0806110 0806111 0806110 0806111 0806110 0806111 0806112 0806113 0806114 0806115 0806116 0806117 0806118 0806113 0806114 0806113 0806114 0806113 0806114 0806113 0806114 0806113 0806114 0806113 0806114 0806113 0806114 0806113 | Vendor No. JI 11-23 11-30 11-35 11-45 21-30F 21-50F 21-50F 51 JI 14-23 14-35 14-45 14-16 14-735 14-45 14-16 141-23 14-735 | Size .023" .030" .045 3/8" 1/2" 1/2" N/A .023" .035" .045" 1/16" .023" .030" .035" .045" 1/16" .023" .030" .045" .0 | Type Type 11-23 11-30 11-35 Contact Tip Nozzle Self-Insulated, Flush Tip Length Nozzle Self-Insulated Flush Tip Length Nozzle Self-Insulated Flush Tip Length Tip Adapter Contact Tip 14-30 14-35 14-45 Contact Tip Contact Tip Tapered Contact Tip Tapered | Oty. 25 25 25 5 5 5 25 | /Each \$0.73 0.66 0.63 0.76 9.43 14.20 7.43 3.10 \$0.66 0.65 0.65 0.65 0.66 0.65 0.65 0.66 0.65 0.65 |

Tweco[®] Compatible Parts Cont.

| Part No. | Vendor No. | Size | | | Price /Each |
|----------|----------------------|------------|-----------------------------------|--------|----------------|
| 0806176 | 52FN | N/A | Туре | | |
| 0806176 | 52FIN | IN/A | Tip Adapter | 5 | 5.50 |
| | | | Replaces 52 so | | |
| | | | #4 Nozzles Can, | | |
| | | | be Used on#2 | | |
| 0806222 | 62A-60 | N/A | Conductor Tube 60° | 1 | 15.86 |
| | 42-3035-15 | | Liner | 1 | 11.23 |
| | 42-4045-15 | | Liner | 1 | 11.72 |
| | 42N-3035-1 | 5.035" | Teflon Liner for | 1 | 29.29 |
| #4 MIG G | - | | | | |
| 0806110 | 14-23 | 023" | Contact Tip | 25 | \$0.60 |
| 0806111 | 14-30 | .030" | 14-30 | 25 | 0.65 |
| 0806112 | 14-35 | .035" | 14-35 | 25 | 0.65 |
| 0806113 | 14-45 | .045" | 14-45 | 25 | 0.65 |
| 0806153 | 14-52 | .052" | Contact Tip | 25 | 0.60 |
| 0806114 | 14-116 | 1/16" | Contact Tip | 25 | 0.60 |
| 0806120 | 14H-35 | .035" | HD contact Tip | 25 | 0.82 |
| 0806121 | 14H-45 | .045" | HD contact Tip | 25 | 0.80 |
| 0806180 | 14H-52 | .052" | HD contact Tip | 25 | 0.81 |
| 0806122 | 14H-116 | 1/16" | HD contact Tip | 25 | 0.81 |
| 0806123 | 14H-564 | 5/64" | HD contact Tip | 25 | 0.82 |
| 0806116 | 14T-23 | .023" | Contact Tip Tapered | 25 | 0.97 |
| 0806117 | 14T-30 | .030" | Contact Tip Tapered | 25 | 0.88 |
| 0806118 | 14T-35 | .035" | Contact Tip Tapered | 25 | 1.01 |
| 0806119 | 14T-45 | .045" | Contact Tip Tapered | 25 | 1.01 |
| 0806147 | 23-37 | 3/8" | Nozzle Self-Insulated | | 10.26 |
| 0806149 | 23-62 | 5/8" | Nozzle Self-Insulated | | 9.14 |
| 0806155 | 24A-50 | 1/2" | Nozzle | 5 | 3.06 |
| 0806158 | 24A-62 | 5/8" | Nozzle | 5 | 4.08 |
| 0806159 | 24A-62SS | 5/8" | Nozzle Short-Stop | 5 | 4.08 |
| 0806139 | 24CT-62S | 5/8" | Nozzle CT Style | 25 | 5.58 |
| | 24CT-025 24AT37SS | 3/8" | Nozzle Adj. Taper SS | | 9.40 |
| 0806183 | 24AI 3755 34A | 3/8 N/A | Insulator | 5 | 1.36 |
| 0806193 | 34A 34CT | N/A | Insulator CT | 5 5 | 8.36 |
| | | | | | |
| 0806179 | 54A | N/A | Tip Adapter Conductor Tube 45° | 5 | 2.78 |
| 0806224 | 64A-45 | N/A | | | 18.83 |
| 0806223 | 64A-60 | N/A | Conductor Tube 60° | 1 | 19.34 |
| | 44-3545-15 | | Liner | 1 | 12.45 |
| 0806209 | 44-116-15 | 1/16" | Liner | 1 | 12.45 |
| | 44-564-15 | | Liner | 1 | 20.53 |
| | 44N-3545-1 | | Teflon Liner for | 1 | 29.72 |
| 0806215 | 44N-116-15 | 1/16" | Teflon Liner for | 1 | 50.04 |
| | | | Aluminum Wire | | |

Plasma Consumables



Esab® Compatible Parts

| Part No. | Vendor No. | Description | Case Qtv. | Price /Each |
|-----------------------|---------------|-----------------------|-----------|----------------|
| Part No. PT-27 Tor | - | Description | case Qiy. | /Each |
| 0809000 | 21616 | Heat Shield | 1 | \$18.08 |
| 0809001 | 33369 | 50-70 Amp Nozzle | 10 | 4.22 |
| 0809002 | 33418 | 80 Amp Nozzle | 10 | 4.22 |
| 0809003 | 33367 | Swirl Baffle | 5 | 11.05 |
| 0809004 | 33366 | Electrode | 10 | 9.05 |
| 0809005 | 21619 | Valve Pin | 10 | 4.37 |
| 0809006 | 85W51 | O-Ring | 10 | 1.01 |
| 0809007 | 21610 | Torch Body | 1 | 298.65 |
| PT-31, 31L | X 31XT | | | |
| 0809010 | 18204 | Shield Cup, XL | 10 | \$9.40 |
| 0809011 | 20282 | Heat Shield | 1 | 16.83 |
| 0809012 | 18866 | Tip, 30 amp | 10 | 2.52 |
| 0809013 | 19682 | Tip, XL, 30 amp | 10 | 4.63 |
| 0809014 | 20079 | Tip, XL, 50 amp | 10 | 3.04 |
| 0809015 | 18785 | Swirl Baffle | 10 | 7.17 |
| 0809016 | 20463 | Swirl Baffle | 10 | 9.72 |
| 0809017 | 18205 | Electrode | 10 | 9.83 |
| 0809018 | 19683 | Electrode, XL | 10 | 17.71 |
| 0809019 | 950790 | O-Ring | 10 | 1.32 |
| 0809020 | 20072 | TMT-31 Hand Torch Hea | ad 1 | 297.68 |
| 0809021 | 20324 | Plunger, XT | 5 | 5.12 |
| 0809022 | 20862 | Electrode | 10 | 11.43 |
| 0809023 | 20860 | Tip, 30 amp, XT | 10 | 4.41 |
| 0809024 | 21008 | 40 Amp Tip, XT | 10 | 4.41 |
| 0809025 | 20861 | Tip, 50 amp, XT | 10 | 4.41 |
| 0809026 | 19679 | Seat | 1 | 70.75 |
| | | | | 4 4 7 |

The : symbol after a price denotes that it is a Direct Ship Product (DSP) and shipping, availability & lead times may vary.

MIG, TIG & Plasma Consumables

PLASMA CONSUMABLES & TIG CONSUMABLES

Plasma Consumables Cont.

Hypertherm[™] Compatible Parts



| | Vendor | | | Price |
|--------------------|------------------|--|----------|----------------|
| Part No. | No. | Description Cas | e Qty. | /Each |
| PAC 110 1 | | | | |
| 0806600 | 020218 | Retaining Cap | 1 | \$17.80 |
| 0806601 | 020381 | Nozzle, Extended | 10 | 3.88 |
| 0806602 | 020382 | Electrode, Extended | 10 | 6.76 |
| 0806603 | 020219 | Nozzle, 20 amp, std. | 10 | 2.86 |
| 0806604 | 020220 | Electrode, std. | 10 | 6.37 |
| 0806605 | 020239 | Swirl Ring | 5 | 20.52 |
| PAC 120 T | orch MA | X 40CS/42/43 | | |
| 0806610 | 020930 | Retaining Cap | 1 | \$16.89 |
| 0806611 | 020350 | Nozzle, 40 amp, std. | 10 | 6.44 |
| 0806612 | 020351 | Air Electrode | 5 | 17.36 |
| 0806613 | 040016 | O-Ring | 10 | 0.28 |
| 0806614 | 020361 | Swirl Ring | 5 | 18.14 |
| | | X 70/80/100 | | |
| 0806677 | 020563 | Extended Nozzle | 5 | \$4.94 |
| 0806678 | 020339 | Gouging Nozzle | 1 | 9.97 |
| 0806679 | 020203 | 40 amp Nozzle | 5 | 3.48 |
| 0806680 | 020345 | 80 amp Nozzle | 5 | 3.96 |
| 0806681 | 020195 | 100 amp Nozzle | 5 | 3.48 |
| 0806682 | 020397 | 80 amp, Shielded Nozzl | e 5 | 3.48 |
| 0806683 | 020337 | 100 amp, Shielded Nozz | | 3.48 |
| 0806684 | 020396 | 40 amp, Shielded Nozzl | e 5 1 | 3.74 |
| 0806674 | 020184 | Retaining Cap | | 24.10 |
| 0806675 0806676 | 020336 | Shielded Cap | 1 | 39.28 |
| 0806676 | 020490 020334 | Shield Cap, 40 amp Machine Shield, 100 am | 1 p 1 | 68.97 16.96 |
| 0806671 | 020334 | Hand Shield | р I 1 | 28.14 |
| 0806672 | 020335 | Machine Shield | 1 | 28.14 |
| 0806670 | 020492 | Deflector Shield | 1 | 23.09 |
| 0806685 | 020333 | Swirl Ring | 5 | 21.23 |
| 0806689 | 020194 | O-ring | 10 | 1.06 |
| 0806686 | 020018 | Extended Electrode, Air | | 8.46 |
| 0806687 | 020193 | Electrode, Nitrogen | 5 | 7.08 |
| 0806688 | 020193 | Electrode, Air | 5 | 8.03 |
| | | X 40/HT40 | | 0.00 |
| 0806620 | 020200 | Retaining Cap, Tapered | 1 1 | \$13.97 |
| 0806621 | 020104 | Retaining Cap, Wtd. | 1 | 10.74 |
| 0806622 | 020197 | Nozzle, Tapered 40 am | o 10 | 2.43 |
| 0806623 | 020115 | Nozzle, Std. 40 amp | 10 | 2.19 |
| 0806624 | 020102 | Nozzle, Machine | 10 | 2.31 |
| | | Torch, std. 40 amp | | |
| 0806625 | 020101 | Swirl Ring | 5 | 14.16 |
| 0806626 | 020103 | Electrode | 10 | 5.55 |
| | | WERMAX 800 [®] | | |
| 0806642 | 120303 | Deflector Ring | 5 | \$11.97 |
| 0806614 | 020361 | Swirl Ring | 5 | 18.14 |
| 0806613 | 040016 | O-Ring | 10 | 0.28 |
| 0806645 | 120282 | 50 amp, Shielded Nozzle | 5 | 3.63 |
| 0806646 | 020395 | Unshielded Nozzle | 10 | 3.40 |
| 0806647 | 120281 | 50 amp, Gouging Shield | 5 | 8.11 |
| 0806648 | 120304 | Extended Nozzle | 5 | 4.17 |
| 0806649 | | Extended Nozzle, Hand He | | 4.80 |
| 0806652 | 020546 | Extended Nozzle | 5 | 4.86 |
| 0806612 | 020351 | Air Electrode | 5 | 17.36 |
| 0806653 | 020547 | Extended Electrode | 5 | 20.69 |
| 0806640 | 120283 | 50 amp Heat Shield | 5 | 28.34 |
| 0806641 | 120326 | Machine Torch Shield | 5 | 31.51 |
| 0806643 | 120302 | Gouging Shield, 50 Amp | 5 | 24.20 |
| 0806644 | 120301 | Retaining Cap | 5 | 47.71 |
| 0806650 | 027055 | Lubricant | 1 | 7.15 |

Tig Consumables



HW-17, 150 Amp TIG Torch

- The industry standard for reliability
 and durability
- Rugged construction provides trouble free operation with low maintenance
- Quick electrode release for fast set-up of changeover
- Gas lens available for improved shielding and better weld quality
- Hard body w/HFC[™] provides superior heat and abrasion resistance
- One piece cable & hose assembly
- 75° head angle
- Includes long cap

| | | | Cable | Price |
|---|----------|-----------|---------|---------|
| F | Part No. | Gas Valve | Lgth. | /Each |
| (| 0817006 | Yes | 12-1/2' | \$92.66 |
| (| 0817007 | Yes | 25' | 136.21 |

HW-26, 200 Amp TIG Torch

- Advanced design provides greater current capacity
- Patented ribbed handle for efficient heat dissipation and sure grip
- Quick electrode release for fast set-up
 of changeover
- Gas lens available for improved shielding and better weld quality
- Hard body w/HFC[™] provides superior heat and abrasion resistance
- One piece cable & hose assembly
- 75° head angle
- Includes long cap

| Part No. | Gas Valve | Cable Lgth. | Price /Each |
|----------|-----------|----------------|----------------|
| 0817009 | No | 25' | \$285.37 |
| 0817011 | Yes | 25' | 325.52 |

HW-18, 350 Amp TIG Torch

- The industry standard water-cooled general purpose tig torch
- Ideal for production welding
- Lightweight reduces operator fatigue
 Watertight brazed, closed cooling sys-
- tem
- Gas lens available for improved shielding
- Hard body w/HFC[™] provides superior heat and abrasion resistance for the longest life
- Units shown have no gas shut-off valve
- 60° Head on torch Includes long cap

0817015

 Cable
 Price

 Part No.
 Lgth.
 /Each

 0817014
 12-1/2'
 \$198.29

25'

210.48

Tig Torch Parts Kits



Kit for HW-17,18, or 26 series torches

| | | Vendor | Price |
|----------|-------------------|--------|---------|
| Part No. | Description | No. | /Each |
| 0817160 | Tig Accessory Kit | 999126 | \$42.61 |

| Comes with 1 ea of the following iter | | | | |
|---------------------------------------|-------------------------|---------------|----------------|--|
| Part No. | Description | Vendor No. | Price /Each | |
| 0817073 | Short Torch Cap | 57Y04 | \$2.71 | |
| 0817020 | 1/16 Collet | 10N23 | 1.46 | |
| 0817021 | 3/32 Collet | 10N24 | 1.46 | |
| 0817022 | 1/8 Collet | 10N25 | 1.46 | |
| 0817026 | 1/16 Collet Body | 10N31 | 3.44 | |
| 0817027 | 3/32 Collet Body | 10N32 | 3.44 | |
| 0817028 | 1/8 Collet Body | 10N28 | 3.44 | |
| 0817040 | #5 Gas Cup | 10N49 | 2.14 | |
| 0817041 | #6 Gas Cup | 10N48 | 2.14 | |
| 0817043 | #8 Gas Cup | 10N46 | 2.14 | |
| 0805453 | 1/16" x 7" Lan Tungsten | 796F58 | 1.67 | |
| 0805455 | 3/32" x 7" Lan Tungsten | 796F63 | 3.25 | |
| 0805457 | 1/8" x 7" Lan Tungsten | 796F68 | 5.68 | |

Tig Torch Parts Parts for 17, 18, 26 series Torches



| | Vendor | | Price |
|---------------|------------|-------|--------|
| Part No. | No. | Size | /Each |
| Collets | | | |
| 0817018 | 10N21 | .020" | \$1.46 |
| 0817019 | 10N22 | .040" | 1.46 |
| 0817020 | 10N23 | 1/16" | 1.46 |
| 0817021 | 10N24 | 3/32" | 1.46 |
| 0817022 | 10N25 | 1/8" | 1.46 |
| 0817023 | 10N20 | 5/32" | 1.59 |
| Collet Bodies | , Standard | | |
| 0817024 | 10N29 | .020" | \$3.44 |
| 0817025 | 10N30 | .040" | 3.44 |
| 0817026 | 10N31 | 1/16" | 3.44 |
| 0817027 | 10N32 | 3/32" | 3.44 |
| 0817028 | 10N28 | 1/8" | 3.44 |
| 0817029 | 406488 | 5/32" | 3.44 |
| Collet Bodies | , Gas Lens | | |
| 0817030 | 45V29 | .020" | \$7.08 |
| 0817031 | 45V24 | .040" | 8.07 |
| 0817032 | 45V25 | 1/16" | 8.07 |
| 0817033 | 45V26 | 3/32" | 8.07 |
| 0817034 | 45V27 | 1/8" | 8.07 |
| 0817035 | 45V28 | 5/32" | 8.07 |

| Part No. | Vendor No. | Description | Case Qty. | Price /Each |
|----------|---------------|--------------------|-----------|----------------|
| Gas Cups | - Alumina | - Standard Body | | |
| 0817101 | 105Z43 | #4 | 10 | \$5.21 |
| 0817102 | 105Z42 | #5 | 10 | 5.21 |
| 0817103 | 105Z44 | #6 | 10 | 5.21 |
| 0817104 | 105Z45 | #7 | 10 | 5.21 |
| 0817105 | 08N78 | #8 | 10 | 5.40 |
| Gas Cups | - Alumina | for Gas Lens Bo | dy | |
| 0817039 | 10N50 | Size 4 ,1/4" Bore | 10 | \$2.14 |
| 0817040 | 10N49 | #5 Gas Cup | 10 | 2.14 |
| 0817041 | 10N48 | #6 Gas Cup | 10 | 2.14 |
| 0817042 | 10N47 | Size 7 ,7/16" Bore | 10 | 2.14 |
| 0817043 | 10N46 | #8 Gas Cup | 10 | 2.14 |
| 0817044 | 10N45 | Size 10 ,5/8" Bore | 10 | 2.14 |
| 0817045 | 10N44 | Size 12 ,3/4" Bore | 10 | 2.14 |
| Gas Cups | - Lava - S | tandard Body | | |
| 0817046 | 54N18 | Size 4 ,1/4" Bore | 10 | \$2.17 |
| 0817047 | 54N17 | Size 5 ,5/16" Bore | 10 | 2.17 |
| 0817048 | 54N16 | Size 6 ,3/8" Bore | 10 | 2.17 |
| 0817049 | 54N15 | Size 7 ,7/16" Bore | 10 | 2.17 |
| 0817050 | 54N14 | Size 8 ,1/2" Bore | 10 | 2.17 |

| Part No. | Vendor No. | Description | Price /Each |
|---------------|-------------------|-----------------------|----------------|
| Gasket/Insula | ator for 17, 18 a | and 26 Series Torches | |
| 0817106 | 18CG | Insulator | \$2.32 |

ESAB

Tig Consumables Cont.



Tig Torch Parts Parts for 9 and **20 Series Torches**

| | Ve | endor | | Price |
|--------------------|-----------------|------------------|-----------|--------------|
| Part No. | | | ize | /Each |
| Collets | | | | |
| 0817107 | 1: | 3N20 .0 | 20" | \$1.20 |
| 0817108 | | |)40" | 1.20 |
| 0817109 | | | /16" | 1.20 |
| 0817110 | | | /32" | 1.20 |
| 0817111 | | | /8" | 1.20 |
| Collet Bod | | | /0 | 1.20 |
| 0817112 | | 3N25 . | 02" | \$2.17 |
| 0817113 | | | 40" | 2.17 |
| 0817114 | | | /16" | 2.17 |
| 0817115 | | | /32" | 2.17 |
| 0817116 | | | /8" | 2.17 |
| | Collet Bod | | /0 | 2, |
| 0817117 | | | 20" | \$7.86 |
| 0817118 | | | 40" | 7.68 |
| 0817119 | | | /16" | 7.68 |
| 0817120 | | | /32" | 7.68 |
| 0817121 | | | /8" | 7.68 |
| | | | , . | |
| | Vendor | | | Price |
| Part No. | No. | Description | Case Qty. | /Each |
| | | Standard Size | 10 | AO 1 |
| 0817122 | 13N08 | #4 | 10 | \$2.19 |
| 0817123 | 13N09 | #5 | 10 | 2.1 |
| 0817124 | 13N10 | #6 | 10 | 2.19 |
| 0817125 | 13N11 | #7 | 10 | 2.19 |
| 0817126 | 13N12 | #8 | 10 | 2.19 |
| 0817127 | 13N13 | #10 | 10 | 2.19 |
| | | Gas Lens Size | 10 | A 1 - |
| 0817055 | 13N14 | Size 4,1/4" bore | | \$1.76 |
| 0817056 | 13N15 | Size 5,5/16" bor | | 1.76 |
| 0817057 | 13N16 | Size 6,3/8" bore | | 1.76 |
| 0817058 | 13N17 | Size 7,7/16" bor | | 1.70 |
| 0817059 | 13N18 | Size 8,1/2" bore | | 1.70 |
| 0817060 | 13N19 | Size 10,5/8" bor | e 10 | 1.76 |
| | | Gas Lens Size | 10 | ¢4 7 |
| 0817055 0817056 | 13N14 | Size 4,1/4" bore | | \$1.76 |
| | 13N15 | Size 5,5/16" bor | | 1.70 |
| 0817057 | 13N16 | Size 6,3/8" bore | | 1.70 |
| 0817058 | 13N17 | Size 7,7/16" bor | | 1.70 |
| 0817059 | 13N18 | Size 8,1/2" bore | | 1.70 |
| 0817060 | 13N19 | Size 10,5/8" bor | e 10 | 1.76 |
| | Lava, Star | #4 | 10 | 00 4 |
| 0817128 | 53N58 | | 10 | \$2.17 |
| 0817129 | 53N59 | #5 | 10 | 2.17 |
| 0817130 0817131 | 53N608 53N61 | #6 | 10 10 | 2.17 |
| 0817131 | 231/01 | #7 | 10 | 2.1 |
| | Vend | dor | | Price |
| Part No. | No | | iption | /Each |
| | | and 20 Series To | | |
| | 5988 | | | \$2.10 |

| Gasket/Ins | ulator for 9 a | nd 20 Series Torches | |
|------------|----------------|-----------------------------|---------|
| 0817132 | 598882 | 598882 insulator | |
| Back Caps | for Torches | | |
| 0817070 | 41V33 | short for 9 & 20 torch | \$3.62 |
| 0817071 | 41V35 | med. for 9 & 20 torch | 3.61 |
| 0817072 | 41V24 | long for 9 & 20 torch | 5.17 |
| 0817073 | 57Y04 | Short Torch Cap | 2.71 |
| 0817074 | 57Y02 | long for 17, 18, & 26 torch | 2.52 |
| Power Cab | le Adapters | for Torches | |
| 0817075 | 105Z57 | for 9 & 17 torch | \$22.78 |
| 0817076 | 45V11 | for 18 & 20 torch | 13.45 |
| 0817077 | 45V62 | for 26 torch | 12.28 |
| | | | |

Tungsten Electrodes

| | | Tungsten El | ectrodes 10 parat | - A Line Line |
|-------------|--------------|----------------|-------------------|----------------|
| Part No. | Diameter | Color Code | Dire Ohi | Price /Each |
| 2% Thoriat | | Code | Pkg. Qty. | /Each |
| 0805420 | 1/16" x 3" | Red Tip | 10 | \$1.88 |
| 0805422 | 1/10 × 0 | Red Tip | 10 | 2.12 |
| 0805424 | 3/32" x 3" | Red Tip | 10 | 7.40 |
| 0805426 | 0,01 X 0 | Red Tip | 10 | 4.58 |
| 0805428 | 1/8" x 7" | Red Tip | 10 | 6.90 |
| Pure Tungs | | | | 0.00 |
| 0805440 | 1/16" x 3" | Green Tip | 10 | \$1.41 |
| 0805442 | 1/16" x 7" | Green Tip | 10 | 1.56 |
| 0805444 | 3/32" x 3" | Green Tip | 10 | 2.31 |
| 0805446 | 3/32" x 7" | Green Tip | 10 | 3.08 |
| 0805448 | 1/8" x 7" | Green Tip | 10 | 5.26 |
| Lanthanate | ed Tungsten | | | |
| 0805453 | 1/16" x 7" | Gold Tip | 10 | \$1.67 |
| 0805455 | 3/32" x 7" | Gold Tip | 10 | 3.25 |
| 0805457 | 1/8" x 7" | Gold Tip | 10 | 5.68 |
| Ceriated Tu | Ingsten | | | |
| 0805469 | 1/16" x 7" | Orange Tip | 10 | \$2.10 |
| 0805471 | 3/32" x 7" | Orange Tip | 10 | 4.32 |
| 0805473 | 1/8" x 7" | Orange Tip | 10 | 8.01 |
| Zirconiated | d Tungsten | | | |
| 0805477 | 1/16" x 7" | Brown Tip | 10 | \$8.47 |
| 0805479 | 3/32" x 7" | Brown Tip | 10 | 14.85 |
| 0805481 | 1/8" x 7" | Brown Tip | 10 | 24.59 |
| Tungstens | s are sold o | nly in full pa | ckages of 10 |). |

Gas Cutting Torch Packages



The GT-250 Outfit provides exactly the right combination of medium duty components for production welding, heating, brazing and cutting.

Torch has heavy-duty, rear mounted throttle valves. Ideal for professional repair shops, auto work, maintenance jobs and farm applications. Comes with CGA540 Oxygen & CGA300 or CGA-510 Acetylene Regulator fittings

Max Welding Thickness - 3/8" Max Cutting Thickness - 4"

Max Heating output - 70 cfh acet (102,000 BTU)

| | | Price |
|----------|---------------|----------|
| Part No. | Description | /Each |
| 0810463 | GT-250 Deluxe | \$332.30 |

The GT-250 Outfit comes with:

| Part No. | Description | Price /Each |
|----------|-----------------------------|----------------|
| 0810472 | W-250 Torch Body | \$127.41 |
| 0810469 | CW-250 Cutting Attachment | 147.81 |
| 0811202 | Cutting tip for 1-1/2" | 12.82 |
| 0810442 | #6 Welding Head | 39.70 |
| 0810489 | Oxygen Regulator | 104.04 |
| 0810483 | Acet Reg CGA 510 | 104.04 |
| 0810250 | Single Flint, Flat File | 2.31 |
| 0800452 | Goggles | 10.41 |
| 0810009 | 25' x1/4" Twin Hose Grade T | 40.81 |

GT-350

A Heavy Duty Torch package includes 2-1/2" gauges on ESAB R-72 Regulators. A CW-300 cutting attachment with Ease-On Oxygen valves. Smooth, dependable performance over a considerable operating range makes this heating and cutting.



Gas Apparatus

an excellent choice for general purpose welding,

- Max Welding Thickness 1"
- Max Cutting Thickness 8"

Max Heating output - 200 cfh acet (294,000 BTU)

| | | Price |
|----------|---------------|----------|
| Part No. | Description | /Each |
| 0810464 | GT-350 Deluxe | \$510.55 |

The GT-350 Outfit comes with 1 ea of the following:

| | | Price |
|----------|-----------------------------|----------|
| Part No. | Description | /Each |
| 0810473 | W-300 Torch Body | \$143.82 |
| 0810471 | CW-300 Cutting Attachment | 171.19 |
| 0811202 | Cutting tip for 1-1/2" | 12.82 |
| 0810454 | #15 Welding Head | 42.86 |
| 0810507 | Oxy Regulator | 111.02 |
| 0810506 | Acet Regulator | 111.02 |
| 0810250 | Single Flint, Flat File | 2.31 |
| 0800452 | Goggles | 10.41 |
| 0810009 | 25' x1/4" Twin Hose Grade T | 40.81 |

OXWELD Trade Master Outfit

The OXWELD Trade Master Outfit offers a superior heavy duty combination of welding and cutting components. It handily accomplishes any craftsman's tasks and is equally versatile for contractors, general shops, maintenance, field applications, and



trade schools. It is particularly popular among journeyman users.

| | | Price |
|----------|--------------------------|----------|
| Part No. | Description | /Each |
| 0805817 | Trade Master DLX 540/510 | \$643.07 |

Precision Master Outfit

With lightweight and easily handled components, the Precision Master Outfit is the best selection for professional jewelry work, metal sculpturing, light duty repair and maintenance work on aircraft frames, auto bodies, and mufflers.



| | | Price |
|----------|---------------------------|----------|
| Part No. | Description | /Each |
| 0843767 | Precision Master DLX with | \$501.61 |
| | Tote and Tanks | |

Cutting Torch Components





CUTTING, STRAIGHT, MISC. & CUTTING TORCHES & COMPONENTS

Cutting Torch Components Cont. SAF **WH360** Heavy Duty Handle Use with 0810193 Cutting Attachment Interchangeable with Victor[®] 315 torch handle.

Part No. 0810172

W-250 Torch Body

· Ideal for all welding, brazing or medium heating applications in average

Gas Apparatus

- production repair or maintenance work. • Recommended for manual operations requiring speed
- and uninterrupted welding, heating and brazing · Operates on medium pressure acetylene and other
- fuel gases · Gas-mixer - high resistance to backfires, flame
- pops and flashbacks
- Roll stamped permanent identification Extra length Teflon[™] valve packing for improved
- backlash characteristics Used with the CW-250 Cutting attachment
- · Uses W-250 acetylene and fuel gas welding and heating tips and multiflame rosebud heads

| Part No. | /Each |
|----------|----------|
| 0810472 | \$127.41 |

W-300 Torch body

- · Ideal for all welding, brazing or medium heating applications in average production, repair or maintenance work
- · Recommended for manual operations requiring speed and uninterrupted welding, heating and brazing
- · Operates on medium pressure acetylene and other fuel gases
- · Gas-Mixer high resistance to backfires, flame pops and flashbacks
- Roll stamped permanent identification
- Extra Length Teflon[™] valve packing for improved backlash characteristics
- Used with the CW-300 cutting attachment · Uses W-300 acetylene and fuel gas cutting tips, heating tips and rosebud heads

| Part No. | Price /Each |
|----------|----------------|
| 0810473 | \$143.82 |

Torch Cutting Attachments CA350

- Medium Duty
- Uses 3-101 Tips
- Use with 0810171 torch body
- Interchangeable with Victor[®] CA1350 cutting attachment.

| | Price |
|----------|---------|
| Part No. | /Each |
| 0810192 | \$89.17 |

CA780A

- Heavy Duty
- Uses 1-101 Tips
- Use with
- 0810172 torch body
- Interchangeable with Victor[®] CA 2460 cutting attachment

Part No. 0810193

Price

/Each

\$78.00

CW-250 Cutting Attachment

CW-250 cutting attachment fits the W-250 torch handle for oxy-fuel

cutting. Features ease on oxygen control, flip over oxygen lever. Designed for Acetylene or fuel gas cutting. Cuts up to 4" with acetylene or other fuel gases. Uses 4200 series Purox cutting tips. 90 degree head.

- Unique piston-type "O" ring seals provide positive leakproof connections
- Cuts up to 4"
- Operates with all medium pressure fuel gases
- Cutting Range using Acetylene 1/16" to 4"
- Cutting Range using other fuel gases 1/16" to"

| Part No. | /Each |
|----------|----------|
| 0810469 | \$147.81 |

CW-300 Cutting Attachment

- · Adapts to W-300 or W-400 torch bodies for oxy-fuel cutting
- Unique piston-type "O"-ring seals provide positive, leak-proof connections
- · Also effective for pad washing, gouging and rivet washing
- Operates with all medium pressure acetylene and other fuel gases
- Valve packing nut contained under handwheel to reduce stem damage
- Cutting Range using Acetylene 1/16" to 8" • Cutting Range with other fuel gases - 1/16" - 4"
- Uses 4200 Series Cutting Tip
- · Features ease-on oxygen control and flip over oxyaen lever

| Part No. /Ea | се | |
|---------------|----|----------|
| 0810/71 \$171 | ch | Part No. |
| \$171 | 19 | 0810471 |

1

Price

/Each

\$183.98

Straight Cutting Torch




Straight cutting torch, one piece

- · Specifications:
- 21" long
- 90° head
- Top rear lever Uses 1-101 tips
- Similar to Victor[®] ST1600C

Part No. 0810137







Price

/Each

\$111.44

| Part No. | Description | Price /Each |
|----------|--------------------------|----------------|
| 0810250 | Single Flint, Flat File | \$2.31 |
| 0810251 | Single Flint, Round File | 2.50 |
| 0810253 | Triple Flint | 3.71 |
| 0810257 | Shoot-a-Lite | 14.07 |

Cutting Torch Accessories Cont.

Replacement Flints



| | | Price |
|----------|-------------------------------------|--------|
| Part No. | Description | /Pkg |
| 0810256 | Single Flint (5 on a Card) | \$1.56 |
| 0810259 | Triple Flint | 1.00 |
| 0810252 | Single Flint (5 per Plastic Holder) | 1.07 |
| 0810254 | Shoot-A-Lite Flints (10 on a Card) | 4.35 |

- With hose, striker, torch, shut off valve and instructions
- · 2 year limited warranty • 500.000 BTU's
- For use with PROPANE GAS ONLY
- . Use with propane tanks of 20 pounds or larger capacity
- · Used for burning weeds, removing paint, melting ice, preheating asphalt/tar, removing road markings and preheating
- ULL isted
- · Excess flow "Safety Valve" shuts off gas flow if hose is accidentally cut or burnt

| Part No. | Description | Price /Each |
|----------|---------------------------|----------------|
| 0810040 | Kit with Hose and Striker | \$86.00 |
| 0810041 | 10' Replacement Hose | 31.35 |



large castings for welding

Cutting Torch Accessories Torch Strikers

Gas Apparatus



| Part No. | Description | Price /Each | |
|-----------------------------|--------------------------------------|----------------|--|
| Self-Ignitin | g Swivel Hand Torches | | |
| 0816657 | LS20 Self-Igniting 360° Swivel Torch | \$101.84 | |
| 0816655 | LS10 360° Swivel Torch | 81.37 | |
| Swivel Replacement Assembly | | | |
| 0816658 | LS20R Self-Igniting 360° Swivel | \$39.84 | |
| | Torch Replacement Assembly | | |
| 0816656 | LS10R Swivel Torch Replacement | 21.42 | |
| Replacement Burn Tip | | | |
| 0816674 | LS20T Replacement Burn Tip for LS20 | \$7.86 | |

The : symbol after a price denotes that it is a Direct Ship Product (DSP)

and shipping, availability & lead times may vary.




MG 16 MAPP® 16 oz. MAPP[®] gas cylinder. CGA-600 cylinder connection. Non-fillable.

PG14 Propane

14.4 oz. propane cylinder. CGA-600 cvlinder connection. Non-refillable.

| Part No. | Description | Price /Each |
|----------|---------------------------|----------------|
| 0800086 | PG14 Propane Cylinder | \$4.62 |
| 0800087 | MG 16 MAPP Gas Cylinder | 9.56 |
| 0816665 | LT92KB Hand Torch Kit Box | 100.95 |



| raitino. | Deacription | /Laci |
|----------|-----------------------------------|----------|
| 0816708 | Air Propane/MAPP Piston Regulator | \$113.37 |
| | with Gaugeguard and 2" Gauge | |
| 0816709 | AP Torch Handle | 86.26 |
| 0816710 | (12-1/2') AA Hose | 57.06 |
| 0816711 | (25') AA Hose | 97.72 |
| | | |

11 - 21Welding

PROPANE TORCHES

Propane Torches Cont.

0 Self-Igniting Hand Torches

| | | Price |
|-------------|--|----------|
| Part No. | Description | /Each |
| Self-Igniti | ng Torches | |
| 0816663 | LT92 Self-Igniting Ultra Swirl Flame | \$104.06 |
| | Hand Torch with Adjustable Flame | |
| 0816661 | LT91 Self-Igniting Swirl Flame | 94.67 |
| | Hand Torch with Adjustable Flame | |
| 0816666 | LT60 Self-Igniting Heat Shrink Hand Torc | h 108.33 |
| 0816659 | LT90 Self-Igniting Swirl Flame Hand Torc | h 86.01 |
| Replacem | ent Assembly | |
| 0816664 | LT92R Self-Igniting Adjustable | \$26.93 |
| | Ultra Swirl Replacement Assembly | |
| 0816662 | LT91R Self-Igniting Adjustable | 25.83 |
| | Swirl Replacement Assembly | |
| 0816667 | LT60R Self-Igniting Heat Shrink | 28.25 |
| | Replacement Assembly | |
| 0816660 | LT90R Self-Igniting Swirl | 22.89 |
| | Flame Replacement Assembly | |
| Replacem | ent Burn Tip | |
| 0816671 | LT92T Replacement Burn Tip for LT92 | \$13.93 |
| 0816672 | LT901T Replacement Burn Tip | 7.06 |
| | for LT90 & LT91 | |
| 0816673 | LT60T Replacement Burn Tip for LT60 | 10.63 |

Air Acetylene Accessories **Air Acetylene Piston Regulator** with TANKTOTE Handle, GAUGEGUARD and 2" Gauge (0816695)

- Provides consistent fuel regulation
- Durable brass construction
- Protects Easy Read 2" gauge from damage
- Transport tank easily
- Ergonomically designed for comfort
- Integrated tank key storage AA Torch Handle (0816696)
- · Comfortable grip with on/off valve and guick connect • "A" Size fittings 3/8"
- AA Hose (0816697 & 0816698)
- · Metal strain relief keeps hose from kinking at fittings
- "A" Size fittings 3/8" Price Part No. Description /Fach

| | 0816695 | MC Air Acetylene Piston Regulator | \$126.20 | |
|--------------------------------|---|-----------------------------------|----------|--|
| | with Tanktote Handle, Gaugeguard and 2" Gauge | | | |
| 0816697 (12-1/2') AA Hose 48.6 | 0816696 | AA Torch Handle | 83.67 | |
| | 0816697 | (12-1/2') AA Hose | 48.65 | |
| 0816698 (25') AA Hose 80.0 | 0816698 | (25') AA Hose | 80.02 | |

Air Propane/Mapp[®] Kits

*All kits contain 1 of each item shown above. Tip size and quantity vary by kit. See listing below.

LX35P Propane/MAPP[®] Kit

- Piston Regulator
- GAUGEGUARD
- 12-1/2' hose
- LP3 3/8" & LP5 3/4" Swirl Flame Tips*
- LX4P Propane/MAPP[®] Kit
- Piston Regulator
- GAUGEGUARD
- 12-1/2' hose

• LP4 1/2" Swirl Flame Tip* LX300P Propane/MAPP[®] Kit

- Piston Regulator GAUGEGUARD
- 12-1/2' hose
- LP300 3/8" Self-Igniting Swirl Flame Tip*
- LX400P Propane/MAPP[®] Kit
- Piston Regulator
- GAUGEGUARD
- 12-1/2' hose
- LP400 1/2" Self-Igniting Swirl Flame Tip*

| Part No. | Description | Price /Each |
|----------|-------------------------|----------------|
| 0816699 | LX35P Propane/MAPP Kit | \$372.55 |
| 0816700 | LX4P Propane/MAPP Kit | 284.52 |
| 0816701 | LX300P Propane/MAPP Kit | 319.39 |
| 0816702 | LX400P Propane/MAPP Kit | 287.44 |

Air Propane/MAPP[®] Tips Swirl Flame Tips & Self-Igniting Swirl Flame Tips 9

Price Part No. Description /Each Swirl & Self - Igniting Flame Tips LP3 Propane/MAPP \$85.31 0816703 Flame Size: 3/8" 9.5mm 0816704 LP4 Propane/MAPP Tip 102.96 Flame Size: 1/2" 12.7mm LP5 Propane/MAPP Tip 0816705 108.18 Flame Size: 3/4" 9.5mm LP300 Self-Igniting Air Propane/MAPP 125.60 0816706 Tip Flame Size: 3/8" 12.7mm 0816707 LP400 Self-Igniting Air Propane/MAPP 127.80 Tip Flame Size: 1/2" 119mm Tip Rebuild Kits LP3/LP300 Tip Rebuild Kit 0816668 \$55.44 0816669 LP4/LP400 Tip Rebuild Kit 66.92 0816670 LP5 Tip Rebuild Kit 70.31

Air Acetylene Tips

Swirl Flame Tips A3 Acetylene Tip

- 3/16" Swirl Flame Tip
- A5 Acetylene Tip
- 1/4" Swirl Flame Tip A8 Acetylene Tip
- 5/16" Swirl Flame Tip
- A11 Acetylene Tip
- 7/16" Swirl Flame Tip
- A3 Tip Rebuild Kit

Includes Burn Tip, Orifice & "0" Ring A5/AA500 Tip Rebuild Kit

- Includes Burn Tip, Orifice & "0" Ring A8/AA800 Tip Rebuild Kit
- Includes Burn Tip, Orifice & "0" Ring
- A11 Tip Rebuild Kit
- Includes Burn Tip, Orifice & "0" Ring
- A14 Acetylene Tip
- 1/2" Swirl Flame Tip
- A32 Acetylene Tip • 5/8" Swirl Flame Tip
- A14/AA900 Tip Rebuild Kit
- Includes Burn Tip, Orifice & "0" Ring
- A32 Tip Rebuild Kit
- Includes Burn Tip, Orifice & "0" Ring

Air Acetylene Tips Self-Igniting Swirl Flame Tips AA500 Acetylene Tip

• 1/4" Swirl Flame Tip

- AA800 Acetylene Tip
- 1/2" Swirl Flame Tip
- A5/AA500 Tip Rebuild Kit
- Includes Burn Tip, Orifice & "0" Ring
- A8/AA800 Tip Rebuild Kit
- A14/AA900
 - Includes Burn Tip, Orifice & "0" Ring

Swirl & Self-Igniting Flame Tips

| Part No. | Description | Price /Each |
|--------------|-------------------------------------|----------------|
| Swirl & Self | - Igniting Flame Tips | |
| 0816684 | A3 3/16" Acetylene Torch Swirl Tip | \$72.36 |
| 0816685 | A5 1/4" Acetylene Torch Swirl Tip | 88.33 |
| 0816686 | A8 5/16" Acetylene Torch Swirl Tip | 93.72 |
| 0816687 | A11 7/16" Acetylene Torch Swirl Tip | 99.54 |
| 0816688 | A14 1/2" Acetylene Torch Swirl Tip | 121.56 |
| 0816689 | A32 5/8" Acetylene Torch Swirl Tip | 172.75 |
| 0816690 | A500 1/4" Acetylene Torch Swirl Tip | 107.95 |
| 0816691 | A800 3/8" Acetylene Torch Swirl Tip | 112.44 |
| 0816692 | A900 1/2" Acetylene Torch Swirl Tip | 117.76 |
| Tip Rebuild | Kits | |
| 0816712 | A3 Tip Rebuild Kit | \$47.05 |
| 0816713 | A5/AA500 Tip Rebuild Kit | 57.43 |
| 0816714 | A8/AA800 Tip Rebuild Kit | 60.93 |
| 0816715 | A11 Tip Rebuild Kit | 64.72 |
| 0816716 | A14/AA900 Tip Rebuild Kit | 79.00 |
| 0816717 | A32 Tip Rebuild Kit | 112.30 |



 3/8" Swirl Flame Tip AA900 Acetylene Tip

PREST-O-LITE TORCH KITS & REGULATORS

Price

/Each

/Each

Price


/Each

\$231.11

Price /Each \$223 45

\$223.45

\$171.84



X-4B POL Kit

- · Higher Capacity Kit, brazes medium/heavy gauge steel
- Uses Quick Connect tips, Compatible with TurboTorch™
- · Soft solders to 6" Silver brazes to 4"
- "B" tank connection (CGA520)

| | Price |
|----------|----------|
| Part No. | /Each |
| 0810240 | \$223.45 |

X-4B comes with 1 ea of the following:

| Part No. | Description | Price /Each |
|----------|-----------------------------|----------------|
| 0810169 | R-511-B Regulator (CGA-520) | \$64.18 |
| 0810159 | Quick Connect Handle | 55.03 |
| 0810198 | SJ-4 Tip | 48.95 |
| 0810156 | SJ-5 Tip | 57.29 |
| 0810023 | 12-1/2' Fitted Hose | 27.56 |

X-5B POL Kit

- · Flexible kit for light duty work
- Compatible with TurboTorch™
- · Soft solders to 2"
- "B" tank connection (CGA520)

X-5B comes with 1 ea of the following:

| | | Price |
|----------|-----------------------------|---------|
| Part No. | Description | /Each |
| 0810169 | R-511-B Regulator (CGA-520) | \$64.18 |
| 0810159 | Quick Connect Handle | 55.03 |
| 0810196 | SJ-3 Tip | 44.80 |
| 0810023 | 12-1/2' Fitted Hose | 27.56 |
| 0810250 | Single Flint, Flat File | 2.31 |

X-6MC POL Kit

- · All purpose kit for work using "MC"

- "MC" cylinder connection (CGA 200) Price

X-6MN comes with 1 ea of the follow-

| Part No. | Description | Price /Each |
|----------|------------------------------|----------------|
| 0810173 | R-511-MC Acetylene Regulator | \$64.18 |
| 0810159 | Quick Connect Handle | 55.03 |
| 0810196 | SJ-3 Tip | 44.80 |
| 0810198 | SJ-4 Tip | 48.95 |
| 0810023 | 12-1/2' Fitted Hose | 27.56 |

LP-1 POL Kit

- All purpose kit works with all LP gases
- Propane cylinder connection (CGA 510)

Part No.

0810222

LP-1 comes with 1 ea of the following:

| Part No. | Description | Price /Each |
|----------|-----------------------------|----------------|
| 0810525 | R-511-LPG Propane Regulator | \$64.18 |
| 0810159 | Quick Connect Handle | 55.03 |
| 0810023 | 12-1/2' Fitted Hose | 27.56 |
| 0810199 | SJ-4LP Tip | 51.93 |
| 0810428 | SJ-6LP Tip | 67.96 |
| | | |

LP-2 POL Kit

- · All purpose kit works with all LP gases
- Soft solders to 2-1/2"
- Silver Brazes to 1-1/4"
- Propane cylinder connection (CGA 510)

| Part No. | |
|----------|--|
| 0810223 | |
| | |

LP-2 comes with 1 ea of the following:

| | | Price |
|----------|-----------------------------|---------|
| Part No. | Description | /Each |
| 0810525 | R-511-LPG Propane Regulator | \$64.18 |
| 0810159 | Quick Connect Handle | 55.03 |
| 0810023 | 12-1/2' Fitted Hose | 27.56 |
| 0810197 | SJ-3LP Tip | 47.73 |
| 0810526 | SJ-5LP Tip | 57.29 |
| | | |

LP-3 POL Kit

- · All purpose kit works with all LP gases
- Soft solders to 4" Silver Brazes to 2"
- Propane cylinder connection (CGA 510)
- Price Part No. /Each 0810224 \$173.82

LP-3 comes with 1 ea of the following:

| | | Price |
|----------|-----------------------------|---------|
| Part No. | Description | /Each |
| 0810525 | R-511-LPG Propane Regulator | \$64.18 |
| 0810159 | Quick Connect Handle | 55.03 |
| 0810023 | 12-1/2' Fitted Hose | 27.56 |
| 0810199 | SJ-4LP Tip | 51.93 |
| 0810250 | Single Flint, Flat File | 2.31 |

Quick Change Torch and Tips



These Swirljet tips are designed to be used with the PREST-O-LITE® #1 Quick Disconnect torch handle. They run quieter, and cooler and give better heat transfer than other comparable tips. Tips will also fit TurboTorch® handles and replace existing TurboTorch® tips

| | | Similar to Turbo Torch™ | Price |
|-----------|----------------------|----------------------------|---------|
| Part No. | Description | Model No. | /Each |
| #1 Handle | | | |
| 0810159 | Quick Connect Handle | G-4 | \$55.03 |
| QD Tips | | | |
| 0810196 | SJ-3 Tip | A-8 | \$44.80 |
| 0810198 | SJ-4 Tip | A-14 | 48.95 |
| 0810156 | SJ-5 Tip | A-32 | 57.29 |
| 0810197 | SJ-3LP Tip | T-3 | 47.73 |
| 0810199 | SJ-4LP Tip | T-4 | 51.93 |
| 0810526 | SJ-5LP Tip | T-5 | 57.29 |
| 0810428 | SJ-6LP Tip | T-6 | 67.96 |

Regulators



R411 & R511 Prest-O-Lite Regulators

- New and Improved
- · Small and lightweight, yet rugged and dependable
- Outperforms regulators
- twice their size Oxygen models have patent
 - ed, built-in explosion protection
- · Fine mesh inlet filters prevent contamination
- · Delivery pressure gauge only, no contents gauge • 3/8-24 LH Male Threaded Outlet Connection ("A" size fitting)

5 year warranty

| Vendor | Gas/CGA | Max. | . Price |
|--------|--|---|---|
| No. | Connection | Pressu | ire /Each |
| /le | | | |
| 21807 | Acetylene (B size) CGA-52 | 20 15 | \$64.18 |
| 21806 | Acetylene (MC size) CGA-2 | 200 15 | 64.18 |
| 21820 | Propane, CGA-510 | 60 | 64.18 |
| /le | | | |
| 04X36 | Acetylene (B size) CGA-52 | 20 15 | \$64.18 |
| 04X37 | Acetylene (MC size)CGA-2 | 00 15 | 64.18 |
| 05X38 | Propane, CGA-510 | 60 | 69.17 |
| | No. /le 21807 21806 21820 /le 04X36 04X37 | No. Connection 21807 Acetylene (B size) CGA-5/ 21806 Acetylene (MC size) CGA-2/ 21820 Propane, CGA-510 /le 04X36 Acetylene (B size) CGA-5/ 04X37 Acetylene (MC size) CGA-6/ 3/ 04X37 | No. Connection Pressure 21807 Acetylene (B size) CGA-520 15 21806 Acetylene (MC size) CGA-200 15 21820 Propane, CGA-510 60 /le 04X36 Acetylene (B size) CGA-520 15 04X37 Acetylene (MC size) CGA-520 15 |

| Quick Connect Handl | е |
|---------------------|---|
| SJ-3 Tip | |
| SJ-4 Tip | |
| 12-1/2' Fitted Hose | |
| | |
| | |





REGULATORS

Regulators



Gas Apparatus

R522 Prest-O-Lite Regulators

- Light duty in size only, can supply enough gas to weld up to 3/4" and cut up to 6" steel
- All regulators have patented explosion protection built-in
- · Bodies are machined from solid brass bar stock light-
- weight and provide longer life • 2" Contents and deliver pressure gauges are color-coded for easy identification, with high strength Lexan crystals for added
- durability and protection
- 5 year warranty

| Part No. | Vendor No. | | Max. Pressure | Outlet Fitting | Price /Each |
|----------|---------------|----------------------------|---------------|--------------------------|----------------|
| 0810311 | 22241 | Acetylene - CGA 510 | 15 | 9/16-18 LH Male (B size) | \$86.01 |
| 0810312 | 22238 | Acetylene - CGA 520 ("B") | 15 | 9/16-18 LH Male (B size) | 86.01 |
| 0810313 | 22239 | Acetylene - CGA 200 ("MC") | 15 | 9/16-18 LH Male (B size) | 86.01 |
| 0810314 | 22237 | Oxygen - CGA 540 | 75 | 9/16-18 RH Male (B size) | 86.01 |
| 0810315 | 22555 | Acetylene - CGA 200 ("MC") | 15 | 3/8-24 LH Male (A size) | 86.01 |
| 0810316 | 22554 | Oxygen - CGA 540 | 75 | 3/8-24 RH Male (A size) | 86.01 |

Purox Medium-duty R-36 Regulators

- · Body machined from solid brass bar stock for maximum strength
- Color-coded pressure gauges easy-to-read 2" diameter. High impact acrylic case is more damage resistant
- The R-36-125-580 and R-36-500-580 have 1/4" flare fittings that accept standard refrigerant charging system hoses; designed for the airconditioning/refrigeration industry to perform nitrogen purging and testing of refrigerant systems
- · Patented baffle design incorporated in oxygen and other versions for suppressing internal forces in case of an cylinder-based explosion

| Part No. | Vendor No. | Gas/CGA Connection | Max. Pressure | Outlet Fitting | Price /Each |
|----------|---------------|-----------------------|---------------|-------------------|----------------|
| 0810524 | 21314 | Acetylene - CGA 300 | 15 | 9/16-18 LH Male | \$104.04 |
| 0810483 | 21184 | Acetylene - CGA 510 | 15 | 9/16-18 LH Male | 104.04 |
| 0810489 | 21185 | Oxygen - CGA 540 | 75 | 9/16-18 RH Male | 104.04 |
| 0810486 | 21313 | Nitrogen - CGA 580 | 75 | 5/8-18 RH Female | 104.04 |
| 0810488 | 21364 | Nitrogen - CGA 580 | 125 | 1/4" 37° Flare | 104.04 |
| 0810485 | 21365 | Nitrogen - CGA 580 | 500 | 1/4" 37° Flare | 112.87 |

PUROX R-72 Medium Duty

- Heavy Duty Single Stage Construction provides improved performance and longer line in any environment
- Patented explosion protection built-in
- · Preset trim screw to assure accurate and consistent delivery pressure and safer operation
- 2-1/2" Color-coded gauges for easy identification and readability
- 5 Year Warranty

| Part No. | Vendor No. | Gas/CGA Connection | Max. Pressure | Outlet Fitting | Price /Each |
|----------|---------------|-----------------------|---------------|-------------------|----------------|
| 0810506 | 21525 | Acetylene - CGA 510 | 15 | 9/16-18 LH Male | \$111.02 |
| 0810507 | 21524 | Oxygen - CGA 540 | 75 | 9/16-18 RH Male | 111.02 |
| 0810505 | 21528 | Oxygen - CGA 540 | 125 | 9/16-18 RH Male | 118.76 |

ESAB OXWELD[®] R-76 TrimLine [™] Heavy Duty

- · Heavy Duty Single Stage Construction provides improved performance and longer line in any environment
- · Patented explosion protection built-in
- Preset trim screw to assure accurate and consistent deliv erv pressure and safer operation
- · 2-1/2" Color-coded gauges for easy identification and readability
- 5 Year Warranty

| Part No. | Vendor No. | Gas/CGA Connection | Max. Pressure | Outlet Fitting | Price /Each |
|----------|---------------|-----------------------|---------------|-------------------|----------------|
| 0810523 | 998323 | Oxygen, CGA-540 | 75 | 9/16-18 RH Male | \$221.90 |
| 0810518 | 998324 | Oxygen, CGA-540 | 150 | 9/16-18 RH Male | 241.99 |
| 0810520 | 998370 | Acetylene, CGA-510 | 15 | 9/16-18 LH Male | 221.90 |
| 0810522 | 998331 | Propane, CGA-510 | 75 | 9/16-18 LH Male | 241.99 |
| 0810519 | 998334 | Nitrogen, CGA-580 | 150 | 5/8-18 RH Female | 241.99 |
| 0810521 | 998335 | Nitrogen, CGA-580 | 500 | 1/4" 45° Flare | 241.99 |

OXWELD[®] R-77 TrimLine [™] Regulators

- Rugged two stage regulator is actually two regulators in one. The heavy duty design provides accurate and consistent delivery pressure
- · Patented explosion protection built in
- Preset trim screw enables welding, cutting and heating (torches to work up to their maximum design capacity.
- The regulator bodies are machined from solid brass bar stock meaning durable construction, longer life and reduced maintenance
- Handles virtually all gas regulation related processes

| Part No. | Vendor No. | Gas/CGA Connection | Max. Pressure | Outlet Fitting | Price /Each |
|----------|---------------|-----------------------|---------------|-----------------------------|----------------|
| 0805849 | 998336 | 75 | 75 | 9/16-18 RH Male | \$328.80 |
| 0805850 | 998337 | 150 | 150 | 9/16-18 RH Male | 328.80 |
| 0805851 | 998338 | 200 | 200 | 9/16-18 RH Male | 347.07 |
| 0805852 | 998371 | 15 | 15 | 9/16-18 LH Male | 328.80 |
| 0805853 | 998340 | 15 | 15 | 9/16-18 LH Male | 328.80 |
| 0805854 | 998341 | 75 | 75 | 9/16-18 LH Male | 367.09 |
| 0805855 | 998342 | 150 | 150 | 9/16-18 LH Male | 367.09 |
| 0805856 | 19057 | 15 | 15 | 5/8-18 RH Female | 328.80 |
| 0805857 | 19590 | 30 | 30 | 5/8-18 RH Female | 393.32 |
| 0805858 | 998343 | 75 | 75 | 5/8-18 RH Female | 335.21 |
| 0805859 | 998344 | 150 | 150 | 5/8-18 RH Female | 328.80 |
| 0805860 | 998345 | 500 | 500 | 1/4, 45 Flared Tube Fitting | 347.07 |
| 0805861 | 18558 | 150 | 150 | 9/16-18 RH Male | 328.80 |
| | | | | | |

Prest-O-Lite R-22 Series Regulators

These regulators outperform many regulators twice their size and weight for oxy-fuel gas applications. They are ideal for maintenance and repair shops requiring occasional welding and cutting operations

- Can supply enough gas to weld 3/4" or cut 6" steel
- · Body and cap machined from solid brass bar stock · 2" pressure gauges have high impact acrylic cases for
- more damage resistance • Patented internal baffle design prevents injury in the event of an explosion better
- than any other known brand
- 5 vear warranty

3/8-24 Outlet (A size fitting, small)

| | • | - | | | |
|------------|---------------|-----------------------|------------------|-----------------------------|----------------|
| Part No. | Vendor No. | Gas/CGA Connection | Max. Pressure | Outlet Fitting | Price /Each |
| | | Fitting, Small) | Treodure | Thung | /Luon |
| 3/0-24 Out | ICI (A SIZE I | nung, Sman) | | | |
| 0810290 | 05X02 | Acetylene - CGA 200 | 15 | 3/8-24 LH Male (A fitting) | \$90.49 |
| 0810292 | 998765 | Acetylene - CGA 510 | 15 | 3/8-24 LH Male (A fitting) | 90.49 |
| 0810293 | 05X01 | Acetylene - CGA 520 | 15 | 3/8-24 LH Male (A fitting) | 90.49 |
| 0810295 | 18564 | Oxygen - CGA 540 | 75 | 3/8-24 RH Male | 90.49 |
| 9/16-18 Ou | tlet (B Size | Fitting, Standard) | | | |
| 0810289 | 20972 | Acetylene - CGA 200 | 15 | 9/16-18 LH Male (B fitting) | \$101.12 |
| 0810291 | 20969 | Acetylene - CGA 510 | 15 | 9/16-18 LH Male (B fitting) | 96.63 |
| 0810294 | 20971 | Acetylene - CGA 520 | 15 | 9/16-18 LH Male (B fitting) | 101.12 |
| 0810296 | 20968 | Oxygen - CGA 540 | 75 | 9/16-18 RH Male | 101.12 |
| | | | | | |







Flow Regulators/Meters & Welding Tips

Flow Regulators/Meters R-33 FM-580 Competitively Priced • Durable Lexan outer tube and flow tube with easy to read graduations Solid brass piston and machined brass body 3000 psi cylinder contents gauge • 10 - 50 CFH Argon Flow Adjustment CGA-580 Inlet • 5/8-18 RH Female Outlet Price Part No. /Each 0810255 \$125.69 Unit with 8' Fitted Hose \$127.26 0810287 R-33-FM-320 Competitively Priced · Durable Lexan outer tube and flow tube with easy to read graduations Solid brass piston and machined brass body 3000 psi cylinder contents gauge • 10 - 65 CFH CO2 (Carbon Dioxide) Flow Adjustment CGA-320 Inlet • 5/8-18 RH Female Outlet Price Part No. /Fach 0810288 \$125.69 Unit with 8' Fitted Hose \$138.11 0810258 R-36-CF-580 • 2" delivery gauge scaled in CFH • Adjustable flow rate of 10 to 40 CFH · For Argon or Argon Mixes • Inlet - CGA-580 Outlet - 5/8-18 RH Female Price Part No. /Each 0810487 \$112.85 R-36-FM-580 Mounted with the well-known L-32 flowmeter · Accurate flow control of argon, helium, C-25 and nitrogen Delivery pressure to flowmeter factory preset to 50 psi • 4-sided vertical gauge calibrated to a variety of welding gases • Inlet - CGA-580 • Outlet - 5/8-18 RH Female Price Part No. /Each 0810504 \$214.68 **R-522** Lightweight Machined from solid brass bar stock • 10-40 CFH adjustable flow rate • Standard 5/8-18 RH Female outlet connection Delivery Gauge calibrated in CFH CGA-580 cylinder connection (Inert Gas) • 5 year warranty Price Part No. /Each \$104.25 0810317

Using a refrigerant for purging contaminants from a system is no longer acceptable. To remove contaminants from a system and remain environmentally safe you must use dry nitrogen. ESAB's Nitrogen Purge Kit gives you all the necessary equipment. Includes:


Regulator Accessories

- 6' of 1/8m hose
- OSHA rated blow gun
- Regulator
- Carrying stand

B Fitting Check Valves

| Part No. | Usage | Price /Each |
|-----------------|-----------|----------------|
| Torch Mount | | |
| 0810410 | Oxygen | \$6.62 |
| 0810413 | Acetylene | 6.62 |
| Regulator Mount | | |
| 0810411 | Oxygen | \$9.03 |
| 0810412 | Acetylene | 9.03 |

Flashback Arrestors



| | eougo | mount | | 7 = 4011 |
|---------|----------|-----------|------|----------|
| 0810420 | Oxygen | Torch | Each | \$40.36 |
| 0810423 | Oxygen | Regulator | Each | 38.87 |
| 0810426 | Fuel Gas | Torch | Each | 44.84 |
| 0810429 | Fuel Gas | Regulator | Each | 38.87 |
| 0810433 | Both | Torch | Pair | 63.00 |
| 0810434 | Both | Regulator | Pair | 70.39 |
| | | | | |

| FASTENA | L |
|-------------|--------|
| Replacement | Gauges |

| PSI Rating | Price /Each |
|------------|---|
| | |
| 0-30 | \$10.21 |
| 0-100 | 10.21 |
| 0-200 | 10.21 |
| 0-400 | 10.21 |
| 0-4000 | 13.41 |
| | |
| 0-30 | \$13.21 |
| 0-100 | 13.21 |
| 0-200 | 13.21 |
| 0-400 | 13.21 |
| 0-4000 | 19.06 |
| | 0-30 0-100 0-200 0-400 0-400 0-4000 0-30 0-100 0-200 0-400 |

| De npatible | |
|----------------|----------------|
| Size | Price /Each |
| 1/2" x 300' | \$3.89 |
| | Size |

Victor Compatible Cutting, Heating and Welding Tips



Series 1-101 Cutting Tips Suitable for Victor® Torches

For use with Acetylene Gas. Compatible with the following cutting heads: MT400, MT600, 1400, ST16/1700, ST18/1900, STN2000, 2300, CA1060, 2450.

One-Piece Tip

| | • | | |
|----------|---------------|------------------|----------------|
| Part No. | Vendor No. | Cutting Depth | Price /Each |
| 0811608 | 000-1-101 | 1/8" | \$20.15 |
| 0811600 | 00-1-101 | 1/4" | 20.15 |
| 0811601 | 0-1-101 | 1/2" | 22.39 |
| 0811602 | 1-1-101 | 3/4" | 22.39 |
| 0811603 | 2-1-101 | 1-1/2" | 22.39 |
| 0811604 | 3-1-101 | 2-1/2" | 22.39 |
| 0811605 | 4-1-101 | 3" | 20.15 |
| 0811606 | 5-1-101 | 5" | 22.53 |
| 0811607 | 6-1-101 | 6" | 22.53 |

Series GPN Cutting Tips Suitable for Victor® Torches

For use with Propane and Natural Gas. Compatible with the following cutting heads: MT400, MT600, 1400, ST16/1700, ST18/1900, STN2000, 2300. CA1060, 2450.

Two-Piece Tin

| Price |
|---------|
| /Each |
| \$13.13 |
| 15.13 |
| 16.61 |
| 16.61 |
| 16.61 |
| 13.13 |
| |

Series 3-101 Cutting Tips Suitable for Victor® Torches

For use with Acetylene Gas. Compatible with the following cutting heads: CST-800, C-1400, C-1450, C-1260, C-1350 and CA-2061.

| One-Piece Tip | | | | | |
|---------------|---------------|------------------|----------------|--|--|
| Part No. | Vendor No. | Cutting Depth | Price /Each | | |
| 0811640 | 000-3-101 | 1/8" | \$17.60 | | |
| 0811641 | 00-3-101 | 1/4" | 17.60 | | |
| 0811642 | 0-03-101 | 1/2" | 22.59 | | |
| 0811643 | 1-3-101 | 3/4" | 22.59 | | |
| 0811644 | 2-3-101 | 1-1/2" | 22.59 | | |
| 0811645 | 3-3-101 | 2-1/2" | 20.55 | | |
| 0811646 | 4-3-101 | 3" | 20.55 | | |

Series 3-GPN Cutting Tips Suitable for Victor® Torches

For use with Propane and Natural Gas. Compatible with the following cutting heads: CST-800, C-1400, C-1450, C-1260, C-135



800, C-1400, C-1450, C-1260, C-1350 and CA-2061.

Two-Piece Tip

| Part No. | Vendor No. | Cutting Depth | Price /Each |
|----------|---------------|------------------|----------------|
| 0811660 | 00-3-GPN | 1/4" | \$8.80 |
| 0811661 | 0-3-GPN | 1/2" | 15.15 |
| 0811662 | 1-3-GPN | 3/4" | 15.15 |
| 0811663 | 2-3-GPN | 1-1/2" | 16.66 |
| 0811664 | 3-3-GPN | 2-1/2" | 16.66 |
| 0811665 | 4-3-GPN | 3" | 8.80 |

VICTOR & ESAB CUTTING, HEATING & WELDING TIPS

Victor Compatible Cutting, Heating and Welding Tips Cont.

Gas Apparatus

ESAB

Series W-Type Welding Tip Suitable for Victor® Torches Fits 300/WH360 Series

| Part No. | Welding Description | Bongo | Price /Each |
|----------|------------------------|-------|----------------|
| Part NO. | Description | Range | /Each |
| 0810850 | 000-W | 1/32" | \$23.77 |
| 0810851 | 00-W | 3/64" | 23.77 |
| 0810852 | 0-W | 5/64" | 23.77 |
| 0810853 | 1-W | 3/32" | 23.77 |
| 0810854 | 2-W | 1/8" | 23.77 |
| 0810855 | 3-W | 3/16" | 23.77 |
| 0810856 | 4-W | 1/4" | 23.77 |
| 0810857 | 5-W | 1/2" | 27.72 |
| 0810858 | 6-W | 3/4" | 27.72 |
| 0810859 | 7-W | 1" | 35.47 |
| 0810860 | 8-W | 2" | 36.27 |
| 0810861 | 10-W | 3" | 38.69 |

Series W-1 Style Welding Tip Suitable for Victor[®] Torches Fits 100 series/WH-260 series handles

| | Welding | | Price |
|----------|-------------|-------|---------|
| Part No. | Description | Range | /Each |
| 0810840 | 000-W-1 | 1/32" | \$15.13 |
| 0810841 | 00-W-1 | 3/64" | 27.60 |
| 0810842 | 0-W-1 | 5/64" | 21.78 |
| 0810843 | 1-W-1 | 3/32" | 21.78 |
| 0810844 | 2-W-1 | 1/8" | 21.78 |
| 0810845 | 3-W-1 | 3/16" | 24.77 |
| 0810846 | 4-W-1 | 1/4" | 24.77 |
| 0810847 | 5-W-1 | 1/2" | 24.77 |
| 0810848 | 6-W-1 | 3/4" | 24.77 |
| 0810849 | 7-W-1 | 1" | 26.33 |

Rosebud Heating Tip Suitable for Victor® Torches For acetylene use, BTU output

| Part No. | Description | Price /Each |
|------------|---|----------------|
| Fits 300/W | /H360 Series | |
| 0810862 | 4-MFA, 9,000 - 29,500. 6 to 20 | \$39.62 |
| 0810863 | 6-MFA, 20,000 - 59,000. 14 to 40 | 55.28 |
| 0810864 | 8-MFA, 44,000 - 118,000 | 55.28 |
| 0810865 | 10-MFA, 59,000 - 147,000. 40 to 100 | 86.83 |
| 0810866 | 12-MFA, 88,000 - 220,000. 60 to 150 | 86.84 |
| 0810867 | 15-MFA, 132,000 - 323,000. 90 to 220 | 63.33 |
| Fits 100 S | eries/WH-260 Series Handles | |
| 0810868 | 2-MFA-1, 4,400 13,000. 3 to 9 cfh | \$42.19 |
| 0810869 | 4-MFA-1, 9,000 - 29,500. 6 to 20 cfh | 42.19 |
| 0810870 | 6-MFA-1, 20,000 - 59,000. 14 to 40 cfh | 42.19 |
| 0810871 | 8-MFA-1, 44,000 - 118,000. 30 to 80 cfh | 42.19 |

ESAB Compatible Cutting, Heating and Welding Tips



Series 1502 Cutting Tips Suitable for Oxweld® Torches

For use with Acetylene Gas. Compatible with the following cutting heads: CW-17, CW-23, CW-400 and CW-500

| | ۲ | | |
|--------|-------|-------------------|---|
| Modium | Proho | at - One-niece Ti | n |

| wedium Preneat - One-piece Tip | | | | |
|--------------------------------|--------|---------|---------|--|
| | Vendor | Cutting | Price | |
| Part No. | No. | Depth | /Each | |
| 0811001 | 08Z67 | 1/4" | \$13.13 | |
| 0811002 | 15Z17 | 1/2" | 13.13 | |
| 0811003 | 15Z18 | 2" | 13.13 | |
| 0811004 | 15Z19 | 4" | 13.13 | |
| 0811005 | 15Z20 | 8" | 13.72 | |

Series 1535 Cutting Tips Suitable for Oxweld® Torches

For use with MAPP and Propane Gas. Compatible with the following cutting heads: CW-17, CW-23, CW-400 and CW-500.

Internal Piece for Two-Piece Tip

| Part No. | Vendor No. | Cutting Depth | Price /Each | | |
|------------------------------------|-----------------|------------------|----------------|--|--|
| Internal Piec | e for Two-Piece | Гір | | | |
| 0811020 | 14Z56 | 1/2" | \$12.10 | | |
| 0811021 | 14Z57 | 3/4" | 12.10 | | |
| 0811022 | 14Z58 | 10" | 12.10 | | |
| 0811023 | 14Z59 | 1-1/4" | 12.10 | | |
| 0811024 | 14Z60 | 1-1/2" | 12.10 | | |
| 0811025 | 14Z61 | 2-4" | 12.10 | | |
| 0811026 | 14Z64 | 5-8" | 12.10 | | |
| External Sleeve for Two Piece Tips | | | | | |
| 0811040 | 14Z38 | 1/2-1-1/2 | \$8.38 | | |
| 0811042 | 14Z39 | 2-8 | 8.38 | | |

Series 4202 Cutting Tips Suitable for Purox[®] Torches

For use with Acetylene Gas. Compatible with the following cutting heads: E, C-205, MC-300, CW-200, CW-202 and CW300.

Medium Preheat

| Part No. | Vendor No. | Cutting Depth | Price /Each |
|----------|---------------|------------------|----------------|
| 0811200 | 16K08 | 1/4" | \$12.82 |
| 0811201 | 16K09 | 1/2" | 12.82 |
| 0811202 | 16K10 | 1-1/2" | 12.82 |
| 0811203 | 16K11 | 4" | 12.53 |
| 0811204 | 16K12 | 6" | 12.53 |
| 0811205 | 16K13 | 10" | 12.53 |

Series 4203 Cutting Tips Suitable for Purox[®] Torches

For use with Propane Gas. Compatible with the following cutting heads: E, C-205, MC-300, CW-200, CW-202 and CW300.

| ۲ | |
|----------|--|
| <u> </u> | |

Medium Preheat

| Part No. | Vendor No. | Cutting Depth | Price /Each |
|----------|---------------|------------------|----------------|
| 0811240 | 16K68 | 1/4" | \$26.55 |
| 0811242 | 16K70 | 1-1/2" | 26.55 |
| 0811244 | 16K71 | 4" | 26.55 |
| 0811246 | 16K72 | 6" | 28.58 |

W-250 Acetylene Welding Heads



| Part No. | Description | Thk. | No. | /Each |
|----------|------------------|--------------|---------|---------|
| 0810438 | #2 Welding Head | 32-25 gauge | 2214378 | \$39.70 |
| 0810441 | #4 Welding Head | 25 ga -1/32" | 2214379 | 39.70 |
| 0810442 | #6 Welding Head | 1/32" -1/16" | 2214380 | 39.70 |
| 0810437 | #15 Welding Head | 1/16" -1/4" | 2214381 | 41.54 |
| 0810439 | #30 Welding Head | 1/4" - 3/8" | 2214382 | 41.54 |

W-300 Std Acetylene Welding Heads

| | | | and the | * |
|----------|------------------|-----------------|---------------|----------------|
| Part No. | Description | Welding Thk. | Vendor No. | Price /Each |
| 0810451 | #1 Welding Head | Under 32 ga. | 639438 | \$36.38 |
| 0810455 | #2 Welding Head | 32 to 25 ga. | 639439 | 36.38 |
| 0810458 | #4 Welding Head | 25 ga to 1/32" | 639440 | 36.38 |
| 0810460 | #6 Welding Head | 1/32" to 1/16" | 639441 | 36.38 |
| 0810461 | #9 Welding Head | 1/16" to 1/8" | 639442 | 42.86 |
| 0810454 | #15 Welding Head | 3/16" to 1/4" | 639443 | 42.86 |
| 0810457 | #30 Welding Head | 1/4" to 3/8" | 17263 | 42.86 |

W-250 Rosebud Multiflame Heating Heads

| | | | | 3. |
|----------|---------------------------------|---------------|---------------|----------------|
| Part No. | Description | BTU Output | Vendor No. | Price /Each |
| 0810508 | #55 Rosebud | 81,000 | 21310 | \$70.57 |
| 0810509 | #70 Rosebud Use w/ Acetylene | 103,000 | 21311 | 71.95 |

W-300 Std Multiflame Heating Heads - Acetylene Gas

| | | | | | C |
|----------|----------------------|--------------------------|---------------|---------------|----------------|
| Part No. | Description | No. of Flame Ports | BTU Output | Vendor No. | Price /Each |
| 0810447 | #55 Welding Head | 7 | 81,000 | 998089 | \$109.50 |
| 0810448 | #70 Welding Head | 7 | 102,000 | 998090 | 109.50 |
| 0810444 | #100 Welding Head | 8 | 147,000 | 998091 | 109.50 |
| 0810445 | #150 Welding Head | 12 | 221,000 | 998092 | 139.88 |

W-300 Rosebud Heating Heads - Acetylene Gas

| | Complete State | | and the second se | and the second second |
|----------|----------------|---------------|---|-----------------------|
| Part No. | Description | BTU Output | Vendor No. | Price /Each |
| 0810511 | #15 Rosebud | 22,000 | 998773 | \$82.40 |
| 0810513 | #30 Rosebud | 44,000 | 998774 | 82.40 |
| 0810514 | #55 Rosebud | 81,000 | 998775 | 82.40 |
| 0810515 | #70 Rosebud | 103,000 | 998776 | 82.40 |
| 0810510 | #100 Rosebud | 147,000 | 998777 | 95.48 |
| 0810512 | #200 Rosebud | 294,000 | 998778 | 134.32 |

Smith, Harris & Airco Cutting, Heating & Welding Tips

Smith Compatible Cutting, Heating and Welding Tips



MC-12 Series Cutting Tips suitable for use with Smith® torches For use with Acetylene Gas

| | | |) |
|----------|---------------|------------------|----------------|
| Part No. | Vendor No. | Cutting Depth | Price /Each |
| 0811400 | MC12-00 | 3/16" | \$12.32 |
| 0811401 | MC12-0 | 3/8" | 15.64 |
| 0811402 | MC12-1 | 5/8" | 15.64 |
| 0811403 | MC12-2 | 1-1/4" | 15.64 |
| 0811404 | MC12-3 | 2" | 15.64 |

SC-12 Series Cutting Tips suitable for use with Smith® Torches

For use with Acetylene Gas

| | | | • |
|----------|--------|---------|---------|
| | Vendor | Cutting | Price |
| Part No. | No. | Depth | /Each |
| 0811442 | SC12-0 | 3/8" | \$19.55 |
| 0811443 | SC12-1 | 5/8" | 19.55 |
| 0811444 | SC12-2 | 1-1/4" | 15.64 |
| 0811445 | SC12-3 | 2" | 15.64 |
| 0811446 | SC12-4 | 4" | 15.64 |
| 0811447 | SC12-5 | 8" | 20.55 |
| 0811448 | SC12-6 | 10" | 20.55 |

Rosebuds suitable for use with Smith® Torches



| Part No. | Vendor No. | Heat Output | Price /Each |
|----------|---------------|---|----------------|
| 0810872 | ST603 | 71,000 btu Output Fits SW1A & SW2 Handles | \$81.21 |
| 0810873 | ST605 | 124,000 btu Output Fits | 81.21 |
| 0810874 | ST610 | SW1A & SW2 Handles 194,000 btu Output Fits | 75.79 |
| | | SW1A & SW2 Handles | |

Harris Compatible Cutting, Heating and Welding Tips



6290 Series

For use with Acetylene Gas

| | Vendor | Cutting | Price |
|----------|----------|---------|---------|
| Part No. | No. | Depth | /Each |
| 0810300 | 6290-000 | 3/16" | \$12.75 |
| 0810301 | 6290-00 | 3/8" | 12.91 |
| 0810302 | 6290-0 | 5/8" | 14.22 |
| 0810303 | 6290-1 | 1" | 14.18 |
| 0810304 | 6290-2 | 2" | 14.18 |
| 0810305 | 6290-3 | 3" | 12.90 |
| 0810306 | 6290-4 | 6" | 13.20 |
| | | | |

6290-AC

Heavy preheat, acetylene - two piece tip

| | | | |
|----------|---------------|------------------|----------------|
| Part No. | Vendor No. | Cutting Depth | Price /Each |
| 0810704 | 6290-00AC | 3/16" | \$13.24 |
| 0810705 | 6290-0AC | 3/8" | 12.27 |
| 0810706 | 6290-1AC | 5/8" | 12.76 |
| 0810713 | 6290-2AC | 1" | 12.81 |
| 0810714 | 6290-3AC | 2" | 12.81 |
| 0810715 | 6290-4AC | 4" | 12.81 |
| 0810716 | 6290-5AC | 7" | 12.81 |
| 0810717 | 6290-6AC | 10" | 12.81 |

6290 NX Series Cutting Tips For use with Propane and Natural Gas



| | | all all and a second and a | |
|----------|---------------|--|----------------|
| Part No. | Vendor No. | Cutting Depth | Price /Each |
| | | • | |
| 0810320 | 6290-000NX | 3/16" | \$11.79 |
| 0810321 | 6290-00NX | 3/8" | 13.20 |
| 0810322 | 6290-0NX | 5/8" | 12.90 |
| 0810323 | 6290-1NX | 1" | 14.18 |
| 0810324 | 6290-2NX | 2" | 14.18 |
| 0810325 | 6290-3NX | 3" | 12.90 |
| 0810326 | 6290-4NX | 6" | 13.20 |
| 0810327 | 62905NX | 8" | 13.20 |
| 0810328 | 6290-6NX | 12" | 13.20 |

6290 NXP Series Cutting Tips For use with Propylene Gas

| (| 0 | | |
|----------|---------------|------------------|----------------|
| Part No. | Vendor No. | Cutting Depth | Price /Each |
| 0810350 | 6290-000NXP | 3/16" | \$12.81 |
| 0810351 | 6290-00NXP | 3/8" | 12.81 |
| 0810352 | 6290-0NXP | 5/8" | 12.81 |
| 0810353 | 6290-1NXP | 1" | 12.81 |
| 0810354 | 6290-2NXP | 2" | 12.81 |
| 0810355 | 6290-3NXP | 3" | 12.81 |
| 0810356 | 6290-4NXP | 6" | 12.81 |
| 0810357 | 6290-5NXP | 8" | 12.81 |

Tip Mixers



| Part No. | Vendor No. | Description | Price /Each |
|----------|---------------|-------------------------------|----------------|
| 0810394 | W-2030 | Use w/0-10, Series 23A90 and | \$24.64 |
| | | #1 & 2 Rosebud | |
| 0810395 | H-2030 | Use w/13 and 15, Series 23A90 | 29.20 |
| | | and #3 & 4 Rosebud | |

23A90 Series Brazing Tips For use with Acetylene Gas on

Bronze, Silver and Gold Series Torches; use with mixers below

| | Vendor | | Price |
|----------|---------|------|---------|
| Part No. | No. | Size | /Each |
| 0810380 | 1600840 | 0 | \$11.47 |
| 0810381 | 1600850 | 1 | 11.42 |
| 0810382 | 1600860 | 2 | 11.47 |
| 0810383 | 1600870 | 3 | 12.00 |
| 0810384 | 1600880 | 4 | 11.79 |
| 0810385 | 1600890 | 5 | 11.31 |
| 0810386 | 1600900 | 6 | 12.76 |
| 0810387 | 1600910 | 7 | 12.76 |
| 0810388 | 1600920 | 8 | 12.76 |
| 0810389 | 1600930 | 9 | 13.19 |
| 0810390 | 1600940 | 10 | 12.76 |
| 0810393 | 1600960 | 13 | 31.29 |
| 0810396 | 1600970 | 15 | 31.55 |
| | | | |

Rosebuds

Mixer sold separately above



| | Vendor | | | Price |
|----------|---------|------|-----------------|---------|
| Part No. | No. | Size | BTU Output | /Each |
| 0810374 | 1800710 | 1 | 30,000-50,000 | \$69.31 |
| 0810375 | 1800720 | 2 | 44,000 - 74,000 | 73.01 |
| 0810376 | 1800730 | 3 | 74,000-118,000 | 89.83 |
| 0810377 | 1800740 | 4 | 118,000-206,500 | 89.83 |

Airco Compatible Cutting, Heating and Welding Tips



Series 144/164 Cutting Tips Suitable for Airco/Concoa® Torches

For use with use in Acetylene Gas. Compatible with the following cutting heads: 3500, 3700, 3790, 4960, 4700, 4800, 5700, and 5800.


| Ð | | | |
|--------------|---------------|------------------|----------------|
| Part No. | Vendor No. | Cutting Depth | Price /Each |
| Medium Preh | leat | | |
| 0810800 | 144-00 | 1/8" | \$17.60 |
| 0810801 | 144-0 | 1/4" | 15.64 |
| 0810802 | 144-1 | 3/8" | 12.91 |
| 0810803 | 144-2 | 3/4" | 12.91 |
| 0810804 | 144-3 | 1-1/2" | 12.91 |
| 0810805 | 144-4 | 2-1/2" | 12.91 |
| 0810806 | 144-5 | 3" | 12.91 |
| 0810807 | 144-6 | 6" | 12.91 |
| High Preheat | | | |
| 0810830 | 164-00 | 1/8" | \$15.64 |
| 0810831 | 164-0 | 5/16" | 15.64 |
| 0810832 | 164-1 | 1/2" | 15.64 |
| 0810833 | 164-2 | 1" | 15.64 |
| 0810834 | 164-3 | 1.5" | 15.64 |
| 0810835 | 164-4 | 2.5" | 15.64 |
| 0810836 | 164-5 | 4" | 15.64 |
| 0810837 | 164-6 | 6" | 15.64 |
| 0810838 | 164-7 | 8" | 10.89 |
| 0810839 | 164-8 | 10" | 10.89 |

Gas Apparatus

Hose & Hose Fittings & Acces

Hose

Twin Hose with Fittings Attached



| 0810014 | 3/8" x 25' B-B |
|---------|----------------|
| 0810017 | 3/8" x 50' B-B |
| | |

"A"-3/8-24 threaded nut

"B"-9/16-18 threaded nut

Bulk Gas Hose



55.37

94.84

| Part No. | Description | Size | Price /Ft. |
|----------|---|------|---------------|
| 0810016 | 1/4" Twin Oxygen/Fuel Hose, Bulk Reel, Grade R | 700' | \$0.80 |
| 0810018 | 1/4" Green Single Inert Gas Hose | 750' | 0.64 |
| 0810021 | 1/4" Red Single Fuel Gas Hose | 750' | 0.64 |
| 0810024 | 3/16" Red Single Fuel Gas Hose | 750' | 0.69 |

Hose Fittings and Accessories



Hose Reels

Twin Hose reel. Holds up to 50' of 1/4" twin welding hose. Also available without hose. 8 position guide arm. Safety banded drive spring. In event of an O-ring failure the gases will go to atmosphere instead of mixing.

| | | Price |
|----------|--------------------------------------|----------|
| Part No. | Description | /Each |
| 0810026 | Hose Reel w/50' Hose and Stop | \$396.91 |
| 0810025 | Hose Reel Empty | 367.56 |
| 0810027 | Hose Stop for Hose (Need w/ 0810025) | 16.90 |

* Scott Fetzer company **Quick Connects**

Color-coded twin-fitted hose quick connects.

Green - Oxy, Red- fuel. Reverse flow check valves included. Pressures up to 125 psi. Durable solid brass construction. 9/16-18 standard industry threads. Unique connection does not allow you to mis-connect gases.

| Part No. | Price /Pair |
|----------|----------------|
| 0810430 | \$57.24 |

Hose Repair Kit

- Has most commonly used parts for repairing 1/4" twin fitted welding hoses
- · Crimping tool sold separately above to allow for a more economical kit
- Kit is labeled for easy replacement of parts



Price Part No. /Fach 99115 \$33.22

Hose Ferrule Crimping Tool

| | R.0 |
|----------|---------|
| | Price |
| Part No. | /Each |
| 0810584 | \$24.01 |

Hose Repair Kit

3/16" & 1/4" Hose Repair Kit with **Crimping Tools**



| | Vendor | | Price |
|----------|--------|----------------------------|---------|
| Part No. | No. | Description | /Each |
| 0810586 | CK-24 | Kit with C-5 Crip Tool For | \$86.74 |
| | | 3/16,1/4 ID Hose | |

| Brass Nuts | |
|------------------|-----|
| Pressures to 200 | PSI |

| | | , | | |
|----------|--------|--------------|-------------|--------|
| | Vendor | | | Price |
| Part No. | No. | Size | Description | /Each |
| 0810556 | 9 | A,3/8-24 RH | Oxygen | \$0.57 |
| 0810559 | 10 | A,3/8-24 LH | Acetelyne | 0.53 |
| 0810550 | 7 | B,9/16-18 RH | Oxygen | 0.70 |
| 0810553 | 8 | B,9/16-18 LH | Acetelyne | 0.70 |

Brass Barbed Hose Nipples Pressures to 200 PSI

| :22ni 62 | ω | 200 | гы | 10-3 | - | à |
|----------|---|-----|----|--|------------|---|
| | | | | | 2 8 | ŝ |
| | | | | Contraction of the local division of the loc | | ł |
| | | | | | 41 | r |

| | Vendor | | | | Price |
|----------|--------|--------|--------------|----------|--------|
| Part No. | No. | Size | Description | Length | /Each |
| 0810572 | 19 | A-Size | 3/16 ID Hose | 1-1/4" | \$0.52 |
| 0810570 | 17 | B-Size | 1/4 ID Hose | 1-15/32" | 0.66 |
| 0810573 | 18 | B-Size | 5/16 ID Hose | 1-15/32" | 0.53 |

Brass Spiral Hose Nipples Pressures to 200 PSI

| | | | _ | | |
|----------|--------|--------|--------------|----------|--------|
| | Vendor | | | | Price |
| Part No. | No. | Size | Description | Length | /Each |
| 0810568 | 13 | A-Size | 3/16 ID Hose | 1-1/4" | \$0.63 |
| 0810562 | 12 | B-Size | 3/16 ID Hose | 1-13/32" | 0.87 |
| 0810565 | 11 | B-Size | 1/4 ID Hose | 1-19/32" | 1.14 |

Brass Hose Couplers Pressures to 200 PSI Vendor

| Part No. | No. | Size | Description | /Each |
|----------|-----|--------|------------------|--------|
| 0810571 | 30 | B-Size | Oxygen RH | \$1.17 |
| 0810574 | 31 | B-Size | Acet/F. Gases LH | 1.17 |
| | | | | |

Brass Hose Splicers

| Pressure | es to 200 | P31 | |
|----------|-----------|--------------------|--------|
| | Vendor | | Price |
| Part No. | No. | Description | /Each |
| 0810583 | 44 | 1/4 TO 1/4 ID Hose | \$1.98 |
| 0810620 | 45 | for 3/16 ID hose | 1.39 |
| 0810621 | 47 | for 3/8 ID Hose | 1.69 |

| Brass Pressur | | | | |
|------------------|--------|-------------|------|--------|
| | Vendor | | | Price |
| Part No. | No. | Description | Size | /Each |
| 0810592 | AW-14A | Male RH | В | \$1.59 |
| 0810593 | AW-14 | Male LH | В | 1.49 |

Brass Inert Gas Nipples

Pressures to 200 PSI

| | Vendor | | | Price |
|----------|--------|------|------------------------|--------|
| Part No. | No. | Size | Description | /Each |
| 0810589 | AW-17 | В | Barbed for 1/4 ID Hose | \$2.47 |
| 0810591 | AW-18 | В | for 3/16 Hose | 1.86 |
| 0810613 | AW-20 | В | for 5/16 Hose | 3.56 |

1111

Brass Inert Gas Hose Couplers

| Pressu | ires to 2 | 200 PSI | |
|----------|---------------|---|----------------|
| Part No. | Vendor No. | Description | Price /Each |
| 0810595 | AW-430 | B-Size CGA-032 RH Fem to B-Size RH Fem | \$4.00 |

| Ferrules Length - 1" | | | | _ |
|-------------------------|--------|-------------|-----------|--------|
| - | Vendor | | | Price |
| Part No. | No. | Description | Case Qty. | /Each |
| 0810596 | 7322 | .500 I.D. | 100 | \$0.76 |
| 0810597 | 7323 | .525 I.D. | 100 | 0.76 |
| 0810604 | 7325 | .562 I.D. | 100 | 0.69 |
| 0810599 | 7326 | .593 I.D. | 100 | 0.74 |
| 0810598 | 7327 | .625 I.D. | 100 | 0.68 |
| 0810601 | 7328 | .656 I.D. | 100 | 0.80 |
| 0810630 | 7330B | .718 I.D. | 100 | 0.74 |
| 0810632 | 7332 | .781 I.D. | 100 | 0.76 |



11 - 28Welding

Welding & Gas Cylinder Supports & Hand Trucks

Gas Cylinder Brackets, Racks. and Stands



Wall and Bench Mounted Cylinder Brackets: Allsteel construction bracket with many quality construction features. 11 Gauge hot rolled steel. Edges are protected with steel reinforced vinyl edge guarding to maintain and protect your cylinders and provide extra grip. Steel parts are sealed with powder paint. Straps and cinch style buckles support cylinders. Support straps are 1.5" wide by 54" long with steel cinch buckle rated 1200 PSI. Bench bracket option clamps to table edges 1 to 3" thick using two threaded posts. Supports hold cylinders from 4.0 to 12.0 diameter. Chain sets (0830834) are optional and can be easily retrofit.



Adjustable Cylinder Bracket

Adjustable bracket in High Density polyethylene. Straps and cinch style buckles support cylinders. Supports hold cylinders from 4 to 14" diameter. Chain set included.

 Part No.
 Description
 //Each

 0830535
 Single Cylinder Poly Wall Bracket
 \$19.90

Single Cylinder Stand

For cylinders up to 10" diameter, single cylinder stand shares construction features with out cylinder brackets, holding cylinders in place with a combination of cylinder straps and heavy gauge steel band clamp. Welded with powder paint finish.

| | | Price |
|----------|-----------------------------|----------|
| Part No. | Description | /Each |
| 0830537 | Single Cylinder Floor Stand | \$141.50 |

Multiple Cylinder and Stainless Steel Wall Brackets



In-Line Cylinder Stands

For cylinders up to 12" diameter. Two and three cylinder capacity racks. Welded with powder paint finish.



| Part No. | Description | Price /Each |
|----------|---------------------------------|----------------|
| 0830544 | Two Cylinder Wall/Floor Stand | \$149.50 |
| 0830546 | Three Cylinder Wall/Floor Stand | 212.50 |

Multiple Cylinder Racks

For cylinders up to 12" in diameter, 4, 6, and 8 cylinder stand shares construction features with our cylinder brackets. Welded with powder paint finish. Ships partially assembled for freight savings.



Cylinder Barricade Racks

Structural Tube Design racks are recommended for indoor or outdoor bulk cylinder storage. Structural Tube series racks surround cylinders with 2" square steel tube continuously seam welded and sealed with exterior grade powder paint. Two levels of welded steel chains with snaps for each cylinder. Standard configurations from one to 16 cylinder capacity, up to 12" diameter standard or 33" cryogenic. Units meet or exceed UF, NFPA, CGA, and OSHA, as well as Seismic Zone 4 requirements. Ships motor freight.



| | | Price |
|----------|---------------------------------------|-----------|
| Part No. | Description | /Each |
| 0830561 | Barricade Rack 1 Cyl Wide x1 Cyl Deep | \$380.80: |
| 0830562 | Barricade Rack 1 Cyl Wide x2 Cyl Deep | 469.20: |
| 0830563 | Barricade Rack 1 Cyl Wide x3 Cyl Deep | 544.00: |
| 0830564 | Barricade Rack 1 Cyl Wide x4 Cyl Deep | 591.60: |
| 0830565 | Barricade Rack 2 Cyl Wide x1 Cyl Deep | 528.70: |
| 0830566 | Barricade Rack 2 Cyl Wide x2 Cyl Deep | 610.30: |
| 0830567 | Barricade Rack 2 Cyl Wide x3 Cyl Deep | 666.40: |
| 0830568 | Barricade Rack 2 Cyl Wide x4 Cyl Deep | 782.00: |
| 0830569 | Barricade Rack 3 Cyl Wide x1 Cyl Deep | 593.30: |
| 0830570 | Barricade Rack 3 Cyl Wide x2 Cyl Deep | 695.30: |
| 0830571 | Barricade Rack 3 Cyl Wide x3 Cyl Deep | 885.70: |
| 0830572 | Barricade Rack 3 Cyl Wide x4 Cyl Deep | 1030.20: |
| 0830573 | Barricade Rack 4 Cyl Wide x1 Cyl Deep | 790.50: |
| 0830574 | Barricade Rack 4 Cyl Wide x2 Cyl Deep | 1001.30: |
| 0830575 | Barricade Rack 4 Cyl Wide x3 Cyl Deep | 1183.20: |
| 0830576 | Barricade Rack 4 Cyl Wide x4 Cyl Deep | 1494.30: |
| 0830577 | Cryogenic Cyl Rack 1 Wide x22 in Dia. | 544.00: |
| 0830578 | Cryogenic Cyl Rack 1 Wide x22 in Dia | 688.50: |
| 0830579 | Cryogenic Cyl Rack 2 Wide x22 in Dia | 676.00: |
| 0830580 | Cryogenic Cyl Rack 2 Wide x33 in Dia | 795.60: |

Cylinder Pallets

Designed for transport of multiple cylinders. Available in 4 configurations with 6, 14, 21 standard (9.25°) or storage/transport for 1, 2, or 4 cryogenic bottles. Model 0830584 is sized to load easily into standard pickup truck beds. 10,000 lb rated ratchet straps, included, attaches at 3 different heights. Steel construction with textured powder paint finish to provide nonskid surface. Two way fully enclosed forklift channels.

| | 830542 | 6-4 | Width | |
|--|--|---|---|----------------------------|
| Part No. | Des | scription | x Depth | Price /Each |
| 0830540 | | r Forklift Pallet | 24x36 in. | \$593.30: |
| 0830542 | | er Forklift Pallet | 48x32 in. | 731.00: |
| 0830584 | 14 Cylinde | er Pallet-Pickup | 32x48 in. | 781.74 |
| Truck Orie 0830543 | | er Forklift Pallet | 48x48 in. | 795.60: |
| Cyline | der Ca | arts 👘 | | |
| 11 gauge hold four 12" diam | e steel. W or six cy eter each Powder p | tructed from heeled carts linders up to a, feature 4" painted and | 08305 | 51 |
| Part No. | D | escription | Cylinde | Price rs /Each |
| 0830549 | | nder Wheeled Ca | - | \$469.00 |
| 0830551 | | der Wheeled Ca | | 551.00 |
| Truck | S | nder Har | | 0830554 |
| 12" diam single cy pneumat matic ma Models c | eter. Thes linder with ic or 10.5 tin wheels offer optio | s. nal fold-down | 6 | 6 |
| 12" diam single cy pneumat matic ma Models c rear cast cinch buc | eter. Thes linder with ic or 10.5 tin wheels offer optio ers. Heav ckles holo | se units are h 8" semi- " pneu- s. nal fold-down ry poly straps Is cylinders. F | | 0830553 |
| 12" diam single cy pneumat matic ma Models c rear cast cinch buc welded a | eter. Thes linder with ic or 10.5 tin wheels offer optio ers. Heav ckles holo | se units are h 8" semi- " pneu- s. nal fold-down ry poly straps Is cylinders. F er painted. | ully | 0830553 Price |
| 12" diam single cy pneumat matic ma Models c rear cast cinch buc welded a | eter. Thes linder with ic or 10.5 in wheels offer optio ers. Heav ckles hold nd powde | se units are h 8" semi- " pneu- s. nal fold-down y poly straps ls cylinders. F er painted. Description | ully 4 | Price /Each |
| 12" diam single cy pneumat matic ma Models c rear cast cinch buc welded a | eter. Thes linder with ic or 10.5 in wheels offer optio ers. Heav ckles hold nd powde | se units are h 8" semi- " pneu- s. nal fold-down y poly straps Is cylinders. F er painted. Description avy Duty 2 Whee | ully 4 n eled Hand | Price |
| 12" diam single cy pneumat matic ma Models c rear cast cinch buc welded a | eter. These linder with ic or 10.5 in wheels offer optio ers. Heav ckles hold and powder Heat Truck, 1 Cy | se units are h 8" semi- " pneu- s. nal fold-down y poly straps Is cylinders. F er painted. Description awy Duty 2 Whee 1 Cylinder Pneur dinder 4 Wheel H | n eled Hand matic Wheels Hand Truck | Price /Each |
| 12" diam single cy pneumat matic ma Models o rear cast cinch buo welded a Part No. 0830553 | eter. These linder with ic or 10.5 in wheels offer optio ers. Heav ckles holo ind powde Heat Truck, 1 Cy | se units are h 8" semi- " pneu- s. nal fold-down y poly straps ls cylinders. F er painted. Description avy Duty 2 Whee 1 Cylinder Pneur | n eled Hand matic Wheels Hand Truck Wheels Hand Truck | Price /Each \$467.25 |
| 12" diam single cy pneumat matic ma Models c rear cast cinch buc welded a Part No. 0830554 0830554 0830555 Two C Trucks fo eter. Moc rear cast cinch buc optional f | eter. These linder with ic or 10.5 in wheels fifer optio ers. Heav xkles hold and powder Heav Truck, 1 C, 1 C, 2 Cylind r gas cyli lels s. Cons R Steel w and 10 a | se units are h 8" semi- "" pneu- s. nal fold-down y poly straps ls cylinders. F er painted. Description avy Duty 2 Wheel 1 Cylinder Pneur dinder 4 Wheel H Pneumatic Wheel Pneumatic While er Hand nders up to 12 n also offer og n also offer og struction is hea vith 3/16" thick und 14 gauge poly straps wi ocking pated | n eled Hand matic Wheels 4and Truck Wheels 4and Truck ieels Trucks 2" diam- otional avy 11 : steel | Price /Each \$467.25 |

Cylinder Carts & Racking

0830559

0830557 4 wheel 2 Cyl Hand Truck w/ Locking post

Description

4 Wheel 2 Cylinder Hand Truck

Welding Cart 20 in. Steel Wheels

0830583

Price

/Each

\$474.30

375.00

283.60

11 - 29

Welding

spoke wheels, other models 10.5"

Pneumatics.

Part No.

0830559

0830583

Cylinder Trucks, Plasma Cutters

Hand Trucks Cont. ESAE Tank Tote Molded stand for 2.85 and 3.0" diameter cylinders is typically used for soldering bottles. The TankTote attaches using compression fit design. Price /Each \$4.34 costs Cylinder Caddv™ protection Designed to lift and transport gas cylinders. Manual lift versions have an 11" lift capacity and are geared to make lifting easy. All-welded units are 115v plug powder painted. chain clamping system.

| | Price |
|----------|----------|
| Part No. | /Each |
| 0830539 | \$439.00 |
| | |

Two Cylinder Hand Trucks

Welding & Gas Cylinder

Heavy Duty Construction individually welded from 11 gauge and heavier Hot Rolled Steel. 10.5" pneumatic main wheels. Powder coated for durability.

Features Include:

- Optional Fold-down rear swivel casters for stability
- · Heavy duty strap with steel cinch buckle for each cylinder • Optional Tool Trays, open or locking lid with torch
- set access slot · Safety features include No-Lift cylinder loading and
- calculated balance point



0830558

| | Price |
|----------|----------|
| Part No. | /Each |
| 0830558 | \$219.00 |
| 0830559 | 297.00 |
| 0830581 | 48.72 |
| 0830582 | 83.62 |

Job Site Firewall Equipped Hand Trucks

For two cylinders up to 12" diameter. Firewall models allow storage of fuel and oxygen cylinders in compliance with regulations using Marinite I™ One Hour rated fire barrier material. Hoist loop and cylinder lock rings included. Locking torch tray. 16" Speed Rated pneumatic wheels to handle finished or unfinished surfaces. Exterior grade powder coated for durability

Price

/Each

\$1088.98

Part No. 0830585



Plasma Cutters



Handy Plasmarc 125

- Cuts up to 1/8" thickness carbon steel
- Plugs into a standard 115v outlet
- · Portable, weighs just 60 lbs carry it anywhere
- · Built-in air supply, no compressor needed
- Equipped with patented, repairable PT-34 torch with double ended electrode for reduced operating
- 1 year warranty on console and torch
- · Fixed output makes it easy to use
- Over-temperature light with thermal
- Torch start up kit provided · Includes everything you need to cut: Power source,torch,spare parts
- kit,work cable and clamp,input cord with

| | Vendor | Price |
|----------|--------|----------|
| Part No. | No. | /Each |
| 0816346 | 37884 | \$977.67 |

HandyPlasmarc 125 Consumables

| Part No. | Description | Vendor No. | Price /Each |
|----------|--------------|---------------|----------------|
| 0806562 | Electrode | 37888 | \$26.14 |
| 0806563 | Nozzle/Tip | 37887 | 10.47 |
| 0809015 | Swirl Baffle | 18785 | 7.17 |
| 0809011 | Heat Shield | 20282 | 16.83 |
| 0806561 | O-Ring | 17672 | 34.74 |

Handy Plasma[™] 550 **Cutting Package**

- Manually cuts 1/2" and severs 5/8'
- · Compact portable design Adjustable output
- Drag or standoff cutting easy operation with little or
- no training · Arrives fully assembled

| | Vendor | Price /Each |
|----------|------------|----------------|
| Part No. | No. | /Each |
| 0816372 | 0558002612 | \$1930.84 |

PowerCut 650 Plasmarc[™] Cutting Package

• Manually cuts 5/8" and severs 3/4" · Compact portable design Arrives ready to cut Drag or standoff cutting easy operation with little or no training Vendor Price Part No. /Each No. 0843706 0558003180 \$2209.35

PowerCut 875 **Plasmarc**[™] Cutting Package

- Designed for rugged treatment and outdoor use, making it the perfect choice for use on the jobsite
- Cuts 7/8" and severs 1-1/4" material
- Arrives ready to cut. for the ultimate in operator convenience

| Part No. | Vendor No. | Price /Each |
|----------|---------------|----------------|
| 0843708 | 0558002788 | \$2993.18 |

PowerCut 1125 Plasmarc[™] **Cutting Package**

· Designed for rugged treatment and outdoor use, making it an excellent choice for the jobsite Cuts 1-1/8" and severs 1-1/2" material Arrives ready to cut, for the ultimate in in operator convenience Vendo Price Part No. /Each No. 0558002792 \$3332.81 0843709

PowerCut 1250 Plasmarc[™] Cutting Package



PowerCut 1500 Plasmarc[™] Cutting Package

· Designed for rugged treatment and outdoor use Cuts 1-1/2" and severs 1-3/4" material · Arrives ready to cut Vendor Price Part No. No. /Each 0843710 0558001942 \$4090.82

fastenal.com

Part No.

0830552

Patented.



Wire Feed (MIG) Welding **Machines**



MultiMaster 160

- Multiprocess Mig, Tig, or Stick
- DC welding output from 20 to 160 amps; rated 160 amps at 60% duty cycle
- Adjustable HOT start feature for Stick mode
- Very portable at only 33 lbs.
- · Comes complete with carrying strap
- Multimaster 160 packages include power source with built in wire feeder, primary input cable, drive roll, welding gun, work cable with clamp, 10 lbs. spool of .035 Core Shield 15 wire, and 1 lb. of sample stick electrodes



| | Vendor | | Price |
|----------|------------|-------------------|-----------|
| Part No. | No. | Description | /Each |
| 0843715 | 0558002772 | MM160 w/10' GM250 | \$2236.50 |
| 0843716 | 0558002773 | MM160 w/10' GM250 | 2256.45 |
| | | GM250/Stinger | |
| 0843717 | 0558002774 | MM160 w/10' | 2481.15 |
| | | Stinger/HW17/Reg | |

MultiMaster 260

- Advanced SuperSwitch[™] technology makes multiprocess welding a breeze. Simplified setup makes it easy to select Mig, Tig, or Stick welding.
- DC welding output from 15 to 300 amps; rated 260 amps at 50% Duty Cycle
- Output Pre-Set Capability for quick set-up Two digital meters for easy fine tuning
- Heavy Duty Four Drive Roll stand
- · Convenient, large capacity built-in tool box
- Dual "Easy-On" Cylinder Tray
- Ready to run .035/.045 wires

Package comes with:

- · Power source with built-in four roll wire feeder
- Factory installed undercarriage and cylinder rack
- Gun Master 250 Amp 12' Mig Torch
- Gas Regulator/flowmeter with hose, CGA-580
- Work Cable and Clamp
- · Primary input cable
- Mig Welding Handbook
- 10 lbs. sample of 035 S-6 wire
- 5 lbs. sample of stick rods

Specifications:

- Rated 260 Amps at 27 Vdc 50% Duty cycle
- Wire feed Range 65-675 IPM



MM-260 Unit

| Part No. | Vendor No. | Veltere | Gun | Price |
|------------|---------------|------------------|---------|-----------|
| | | Voltage | Lengt | |
| 0816356 | 0558001519 | 208/230vac 1ph | 12' | \$3583.50 |
| 0843718 | 0558001520 | | 15' | 3553.20 |
| | Vendor | | | Price |
| Part No. | No. | Descriptio | n | /Each |
| Optional I | tems | | | |
| 0816365 | 33646 | FC-5B Foot Co | ontrol | \$299.94: |
| 0816362 | 0558001793 | Spool Gun Mo | odule | 112.48 |
| 0816360 | 37707 | MT-250Sg Spoo | ol Gun | 889.09 |
| 0816361 | 19164 | St-23A Spool | Gun | 1267.93 |
| 0816363 | 35857 | HW-17V-2TL Tig | g Torch | 208.31 |
| 0817160 | 999126 | Tig Accessor | y Kit | 42.61 |
| Consuma | ibles | | | |
| 0806504 | 20543 | .023 Tip, st | d | \$2.40 |
| 0806505 | 20544 | .030 Tip, st | d | 1.38 |
| 0806506 | 996995 | .035 Tip, st | d | 1.38 |
| 0816377 | 37290 | .045 Tip, st | d | 2.26 |
| 0806507 | 996999 | .045 /3/64 Tip | , std | 1.38 |
| 0806528 | 37286 | .045 Tip, H | D | 4.20 |
| 0806529 | 17765 | 3/64 Tip, H | D | 3.99 |
| 0816382 | 0558001609 | 3/8" Nozzle, F | lush | 13.09 |
| 0816385 | 0558001612 | 1/2" Nozzle, Red | cessed | 11.15 |
| 0816386 | 0558001613 | 1/2" Nozzle, Sti | ck Out | 11.47 |
| 0816389 | 0558001608 | Nozzle Adap | oter | 11.95 |
| 0806552 | 37032 | .035 Line | r | 22.40 |

Migmaster 210

 Output current range 30 to 210 amps DC • Use with both solid wire and self shielding cored

WIRE FEED MACHINES

- wire from .023 to .035 in diameter Comes complete with GM-250 welding torch, 11'
- work cable with clamp, 15' primary power cable with plug, undercarriage and gas cylinder rack, 5' gas hose, contact tips, and feed roll
- Optional spool gun capability for aluminum welding



| | Vendor | | Price |
|----------|------------|--------------------|-----------|
| Part No. | No. | Description | /Each |
| 0843711 | 0558002431 | MM210 w/10' Gun | \$1521.45 |
| 0843712 | 0558002607 | MM210 w/12' Gun | 1548.06 |
| 0843713 | 0558003065 | MM210 w/10' | 2142.77 |
| | | MT-250SG Spool Gur | ۱ |

Migmaster 250

- Rated 250 amps at 50% duty cycle
- DC welding output from 30 to 280 amps
- 24 overlapping heat steps for accurate fine tuning Feeds wire from 20 to 650 ipm; pulse width modulated, solid state speed control
- Built in spool on gun control
- Features 15' torch unit



| | Price |
|----------|-----------|
| Part No. | /Each |
| 0843714 | \$2481.15 |
| | |

350 mpi

- Third generation inverter power supply puts reliability and ease of use into a powerful, versatile package
- · Microprocessor controlled power supply makes it easy to tune in an excellent welding condition
- Operates on single phase or three phase power



| | | Price |
|----------|------------------|-----------|
| Part No. | Description | /Each |
| 0843719 | 350 mpi Inverter | \$4011.85 |

• Output Mig current - 35-300 amps Output Stick current - 40-300 Amps Output Tig current - 10-300 Amps • Net weight - 250 lbs. • 25.3"w x 39.5"L x 33.5"h

WIRE FEED, STICKWELDERS & TIG WELDERS

Wire Feed (MIG) Welding **Machines Cont.**



460



- · Multiprocess, three phase power source designed for heavy duty industrial DC welding applications
- Use for high performance Mig, Pulse Mig, Flux Cored Wire, Stick Electrode Welding, Tig and Air Carbon Arc Gouging
- Compatible with DuraDrive 4-30 and DuraDrive 4-48 wire feeders
- Synergic/Non-Synergic Mig Pulse welding capability with the intelligence built into the power source (Standard on the pulse unit and optional on the standard unit). Allows you to do Pulse Mig with

| aimost any wi | e leeuel. | |
|---------------------|-----------------------|----------------|
| | Vendor | Price |
| Part No. | No. | /Each |
| 0843708 | 0558002788 | \$2993.18 |
| | | |
| Dort No. | Description | Price (Each |
| Part No. | Description | Price /Each |
| Part No. 0843726 | Description MP 460 | |

MT-250 SG Spool Gun Package

- Medium duty 200 amp, 100% duty performance
- · Spool holder adjusts to balance in the operator's hand



DuraDrive 4–30 Wire Feeder

· Heavy duty compact wire feed motor Quick release feed roll system · All cable and hose connections are quickly detachable • .035 to .045 driveroll included

| | | Price |
|------------|--|-----------|
| Part No. | Description | /Each |
| 0843730 | DD 4–30 | \$1893.15 |
| 0843731 | DD 4–30 w/Cable | 2029.65 |
| Options & | Accessories | |
| 0805863 | Dual Schedule Option | \$125.36 |
| 0805864 | Dual Schedule/Digital Meter Option | 303.52 |
| 0805865 | Dual Sched./Digital Meter/Pulse Option | 511.44 |
| 0805866 | Pre/Postflow/Spot/Trigger Lock Option | 100.04 |
| 0805867 | Control Cable, 8' | 237.86 |
| DD 4-30 Fe | edroll Kits | |
| 0805868 | Hard Wire V–.023–.30" | \$109.34 |
| 0805869 | Hard Wire V035045" | 109.34 |
| 0805870 | Hard Wire V052-1/16" | 109.34 |
| 0805871 | Cored Wire K035045" | 109.34 |
| 0805872 | Cored Wire K045052" | 109.34 |
| 0805873 | Cored Wire K-1/16-5/64" | 109.34 |
| 0805874 | Soft Wire U035-3/64" | 109.34 |
| 0805875 | Soft Wire U-3/64-1/16" | 109.34 |

DuraDrive 4–48 Wire Feeder

- · Heavy duty compact wire feed motor
- · Quick release feed roll system
- · Heavy Duty 48 millimeter feed rolls, ideal for medium to low speed heavy wire applications



| Part No. | Description | Price /Each |
|----------|-----------------|----------------|
| 0843728 | DD 4–48 | \$2101.05 |
| 0843729 | DD 4–48 w/Cable | 2235.45 |

Mobile Master IV Wire Feeder

- Arc voltage feeder capable of use with CC
- or CV units
- 4 roll drive unit
- · Totally enclosed, impact resistant case protects welding wire form dirt, metal grit, moisture and other contaminants
- · Metal reinforced, flame retardant, molded composite plastic case will withstand extreme abuse like hot slag, grinding sparks, corrosive chemicals, knocks, bumps, drops and more
- · Designed to meet the most rigid standards. CSA certified for USA and Canadian requirements.



| Part No. | Description | Price /Each |
|----------|---------------------|----------------|
| 0843732 | MM IV, CC | \$1832.25 |
| 0843733 | MM IV, NAS w/Meters | 1996.05 |

Stickwelders and Tig Welders **MiniArc 150 APS**

- The MiniArc 150 APS operates on either 110 vac or 203 vac and will automatically configure for the primary input supplied by the customer
- · Designed to provide outstanding welding performance for touch start Tig and Stick welding
- Weighs only 18 lbs., making it portable and easy to carry right to the job
- Sturdy plastic carrying case accommodates the MiniArc, welding cables, torch, and
- other accessories



| Deut Na | Description | Price |
|----------|---------------|-----------|
| Part No. | Description | /Each |
| 0843734 | Stick Package | \$1098.30 |
| 0843735 | Tig Package | 1323.00 |

Heliarc 161 AC/DC Tig Welder

- Square wave AC output gives superior welding with improved cleaning and lack of rectification
- Arc force control fine tunes arc for stick welding from soft to a high penetration, digging arc
- Direct connections for Tig torch and electrode holder for maximum convenience



| Part No. | Description | Price /Each |
|----------|------------------------------------|----------------|
| 0843720 | Heliarc 161 12' | \$2646.00 |
| 0843721 | Heliarc 161 12' w/Electrode Holder | 2752.05 |
| 0843722 | Heliarc 161 25' | 2667.00 |
| 0843723 | Heliarc 25' w/Electrode Holder | 2774.10 |

Heliarc 252/352 AC/DC

- · Square wave AC output gives superior welding with improved cleaning and lack of rectification
- · Direct connections for Tig torch and quick lock output cable for maximum convenience
- · Protected against overheating and overcurrent



| Part No. | Description | /Each |
|----------|-------------------|-----------|
| 0843724 | Heliarc 252 AC/DC | \$2788.07 |
| 0843725 | Heliarc 352 AC/DC | 4252.61 |

fastenal.com

11-32 Welding

